



TRAFFIC IMPACT STUDY

KING SOOPERS 142

Louisville, CO

PREPARED FOR:
King Soopers

PREPARED BY:
Brian Horan, PE, PTOE
Daniela Gonzalez
Cooper Riddell-Brosig

Galloway & Company, Inc.
5500 Greenwood Plaza Blvd, Suite 200
Greenwood Village, CO 80111

DATE:
February 7, 2025
REVISED: April 14, 2025



TABLE OF CONTENTS

Executive Summary	5
Site Location and Study Area	5
Description of Proposed Development	5
Conclusions and Recommendations	5
Conclusions	5
Recommendations	6
I. Introduction	7
Overview	7
Site Location and Study Area	7
Site Description and Access	8
Figure 1-1 Site Location	9
Figure 1-2 Site Plan	10
Figure 1-3 Existing Zoning	11
II. Background Information	12
Study Area	12
Study Assumptions	12
Study Methodology	12
Existing Roadway Network	12
Figure 2-1 Existing Lane Use and Traffic Control	14
III. Analysis of Existing Conditions	15
Traffic Volumes	15
Existing Levels of Service	15
Existing Intersection Queues	15
Figure 3-1 Existing Volumes	16
Figure 3-2 Existing Levels of Service	17
Table 3-1 Existing Levels of Service	18
Table 3-2 Existing Queues	19
IV. Analysis of Future Conditions without Site Development	20
Methodology	20
Regional Growth	20
Pipeline Developments	20
Background Traffic Forecasts	20
Background Future Levels of Service	20
Background Future Queueing	21

Figure 4-1 Background Growth 2026.....	22
Figure 4-2 Background Growth 2045.....	23
Figure 4-3 Pipeline Location	24
Figure 4-4 Pipeline Site Trips.....	25
Figure 4-5 Background Future Forecasts 2026	26
Figure 4-6 Background Future Forecasts 2045	27
Figure 4-7 Background Future Levels of Service 2026	28
Figure 4-8 Background Future Levels of Service 2045	29
Table 4-1 Background Levels of Service	30
Table 4-2 Background Queues	31
V. Site Analysis	32
Overview	32
Proposed Site Access	32
Trip Generation	32
Figure 5-1 Pass-by Trips.....	34
Figure 5-2 Site Trips.....	35
Table 5-1 Site Trip Generation.....	36
VI. Analysis of Future Conditions with Site Development.....	37
Total Future Traffic Forecasts	37
Total Future Levels of Service with Proposed Development.....	37
Total Future Queuing	37
Figure 6-1 Total Future Forecasts 2026	38
Figure 6-2 Total Future Forecasts 2045	39
Figure 6-3 Total Future Levels of Service 2026.....	40
Figure 6-4 Total Future Levels of Service 2045.....	41
Table 6-1 Future Levels of Service	42
Table 6-2 Future Queues.....	43
VII. Conclusions and Recommendations	44
Conclusions.....	44
Recommendations	44

Appendices:

- A. Full Sized Conceptual Site Plan
- B. LOS Descriptions
- C. Traffic Counts
- D. Existing Synchro Outputs
- E. Background (without site development) Synchro Outputs
- F. Future (with site development) Synchro Outputs

Executive Summary

Site Location and Study Area

The property that comprises the application area for the proposed redevelopment is approximately 13.5 acres in size and is identified as Boulder County Parcel Numbers 157713016001 and 157713016002. It is located south of Centennial Pkwy, north of Dillon Rd, east of Century Pl, and west of McCaslin Blvd in Louisville, CO. It is zoned Planned Community Commercial (P-C) and is currently occupied by a vacant commercial building, previously serving as a home improvement superstore use.

The study area is generally bounded by Centennial Pkwy to the north, Century Pl to the west, McCaslin Blvd to the east, and Dillon Rd to the south. The study area for the project includes intersections that could be affected by the proposed development which were confirmed by review of City Staff:

- Centennial Pkwy & Century Pl
- Centennial Pkwy & N Site Access
- Centennial Pkwy & McCaslin Blvd
- E Site Access & McCaslin Blvd
- Dillon Rd & McCaslin Blvd
- Dillon Rd & S Site Access
- Dillon Rd & Century Pl

Description of Proposed Development

The Applicant, King Soopers, seeks to redevelop the property with commercial uses consisting of supermarket and gas station uses. No change to the site access is proposed.

Conclusions and Recommendations

Conclusions

Based on the results of this traffic impact study, the following may be concluded:

- Under existing traffic conditions, the signalized intersections in the study area currently operate at acceptable overall levels of service (LOS) "D" or better during the weekday peak hours. The unsignalized intersection movements in the study area currently operate at acceptable LOS "B" or better during the weekday peak hours. All queues are contained within their effective storage.
- Under background future 2026 and 2045 traffic conditions, without the development of the subject site, delays would increase slightly at study intersections due to regional traffic growth. The signalized intersections in the study area are forecasted to operate at acceptable overall LOS "D" or better during the weekday peak hours with the exception of the Dillon Rd & McCaslin Blvd intersection which is forecasted to operate at LOS "E" during the long range (2045) weekday PM peak hour. The unsignalized intersection movements in the study area would operate at acceptable LOS "C" or better during the weekday peak hours. All queues are expected to be contained within their effective storage with the exception of the eastbound left movement at the Centennial Pkwy & McCaslin Blvd intersection during the long range (2045) weekday AM peak hour.
- The proposed site redevelopment would generate, upon completion and full occupancy, 399 net new weekday AM and 755 net new weekday PM peak hour vehicle trips as well as 10,301 net new weekday daily trips.

- Under total future 2026 and 2045 traffic conditions with development of the site, the signalized intersections within the study area would continue to operate at acceptable overall LOS “D” or better during the weekday peak hours in all total future scenarios with the exception of the Dillon Rd & McCaslin Blvd intersection which would operate at LOS “E” during the weekday PM peak hour for total future 2026 and 2045 conditions. The unsignalized intersection movements in the study area would operate at acceptable LOS “D” or better during the weekday peak hours in all future scenarios.
- Under total future 2026 and 2045 traffic conditions with development of the site, all queues are expected to be contained within their effective storage with the exception of the eastbound left turn lane at the intersection of Centennial Pkwy & McCaslin Blvd which would exceed the available storage during all total future scenarios.

Recommendations

- It is recommended that the Applicant provide access consistent with the site plan contained herein.
- It is recommended that the signal timings at Dillon Rd & McCaslin Blvd be optimized once the subject site is operational to improve overall operations of the intersection including better LOS and accommodate anticipated queues.
- It is recommended that the eastbound left turn lane at Centennial Pkwy & McCaslin Blvd be extended to accommodate the queue.

I. Introduction

Overview

This report presents the results of a Traffic Impact Study (TIS) conducted in support of a site plan to redevelop a property with commercial uses consisting of supermarket and gas station uses in Louisville, CO. Currently the site is occupied by a vacant commercial building, previously serving as a home improvement superstore use.

Per the requirements of the City of Louisville, a Transportation Impact Study is required to support the proposed redevelopment.

Site Location and Study Area

The property that comprises the application area for the proposed redevelopment is approximately 13.5 acres in size and is identified as Boulder County Parcel Numbers 157713016001 and 157713016002. It is located south of Centennial Pkwy, north of Dillon Rd, east of Century Pl, and west of McCaslin Blvd in Louisville, CO, as shown in Figure 1-1. It is zoned Planned Community Commercial (P-C) and is occupied by a vacant commercial building, previously serving as a home improvement superstore use. Site access is proposed via the existing right-in/right-out (RIRO) access on Centennial Pkwy, full movement access on Centennial Pkwy, $\frac{3}{4}$ movement access on McCaslin Blvd, RIRO access on Dillon Rd, two full movement accesses on Dillon Rd, and two full movement accesses on Century Pl. No change in site access is proposed.

The Applicant, King Soopers Stores, seeks to redevelop the property with a supermarket and a gas station use. A reduction of the Applicant's proposed conceptual site plan is provided in Figure 1-2. A full-size copy of the plan is provided in Appendix A.

The study area is generally bounded by Centennial Pkwy to the north, Century Pl to the west, McCaslin Blvd to the east, and Dillon Rd to the south.

Tasks undertaken during this study included the following:

1. Reviewed the Applicant's proposed development plans and other background data.
2. Conducted a virtual field reconnaissance of existing roadway and intersection geometries, traffic controls, and speed limits.
3. Collected peak hour turning movement counts at the key intersections.
4. Analyzed existing levels of service at each of the key study intersections based on the methodologies set forth in the Highway Capacity Guidelines (HCM) 7th Edition and reports generated by Synchro as reported by Synchro version 12 software.
5. Forecasted background future traffic volumes based on baseline traffic counts, pipeline projects, and regional traffic growth for 2026 (build-out) and 2045 (long-range) conditions.
6. Calculated background levels of service at each of the key study intersections for the projected build-out years based on background future traffic forecasts, and the existing lane use and traffic controls.

7. Estimated the number of AM and PM peak hour trips that would be generated by the proposed uses based on the Institute of Transportation Engineers (ITE) Trip Generation 11th Edition rates/equations and methodologies.
8. Prepared AM and PM peak hour total future traffic forecasts based on background traffic forecasts plus site traffic assignments for the 2026 (build-out), as well as 2045 (long-range) conditions.
9. Calculated total future levels of service for each of the key study intersections based on projected total future traffic forecasts, and existing lane use and traffic controls.
10. Identified roadway improvements required to accommodate future traffic volumes, as necessary.

Sources of data for this analysis included the Institute of Transportation Engineers (ITE) Trip Generation, 11th edition, the Highway Capacity Guidelines HCM 7th, Synchro 12, King Soopers Stores, City of Louisville, Colorado, CDOT, and the files/library of Galloway.

Site Description and Access

Site Conditions

The terrain proximate to and surrounding the site is generally classified as “level”.

Hazardous Conditions

Based on the field reconnaissance in the vicinity of the subject site, no hazardous features or constraints were identified.

Proposed Site Access

Access to the site is proposed via the existing right-in/right-out (RIRO) access on Centennial Pkwy, full movement access on Centennial Pkwy, $\frac{3}{4}$ movement access on McCaslin Blvd, RIRO access on Dillon Rd, two full movement accesses on Dillon Rd, and two full movement accesses on Century Pl.

Existing Zoning

The subject site is currently zoned Planned Community Commercial (P-C) and is currently occupied by a vacant commercial building, previously serving as a home improvement superstore use. Figure 1-3 depicts the existing zoning associated with the subject property, as well as neighboring properties as shown on the City of Louisville zoning map.

Nearby Uses

The properties surrounding the subject site are generally developed with commercial uses to the east and south, and office uses to the west and north.




FIGURE 1-1
SITE LOCATION






FIGURE 1-3
EXISTING ZONING



II. Background Information

Study Area

The study area was determined by a review of intersections that would experience a significant portion of turning movement volumes generated by the site. As such, the traffic study focuses primarily on the following intersections:

Study Intersections

- Centennial Pkwy & Century Pl
- Centennial Pkwy & N Site Access
- Centennial Pkwy & McCaslin Blvd
- E Site Access & McCaslin Blvd
- Dillon Rd & McCaslin Blvd
- Dillon Rd & S Site Access
- Dillon Rd & Century Pl

Study Assumptions

For purposes of this analysis only, the proposed use was assumed to be built and occupied in one distinct phase. It was assumed that the use would be built and operational in study year 2026. A long-term analysis of 2045 is also provided.

Study Methodology

Synchro software version 12 was used to evaluate levels of service at each of the study intersections during the weekday AM and PM peak hours. Synchro is a macroscopic model used for optimizing traffic signal timing and performing capacity analyses. The software can model existing traffic signal timings or optimize splits, offsets, and cycle lengths for individual intersections, an arterial, or a complete network. Synchro allows the user to evaluate the effects of changing intersection geometrics, traffic demands, traffic control, and/or traffic signal settings as well as optimize traffic signal timings.

The levels of service reported for the signalized and unsignalized intersections analyzed herein were taken from the Highway Capacity Manual (HCM) 7th and reports generated by Synchro. Level of service descriptions are included in Appendix B.

A default percent heavy vehicle (%HV) factor of 2% was used for all movements in the study area.

Existing Roadway Network

Regional access to the subject site is provided by McCaslin Blvd, and local access is provided via Centennial Pkwy/Cherry St and Dillon Rd. Figure 2-1 depicts existing lane use and traffic controls in the vicinity of the subject site. The following provides a description of each of the roadways within the study network.

McCaslin Blvd

McCaslin Blvd is constructed as a six-lane median divided section with turn lanes at major intersections. The posted speed limit is 35 mph in the vicinity of the subject site. The roadway functions as an arterial and provides north-south connection through the County and connection to Hwy 36 to the south. The intersections with Centennial Pkwy and Dillon Rd operate under signalized control.

Centennial Pkwy

Centennial Pkwy is constructed as a two-lane median divided roadway with turn lanes at major intersections. The roadway functions as an arterial providing east-west connection for a number of commercial and residential areas. The intersections along its length operate under stop control with the exception of the intersection with McCaslin Blvd which operates under signalized control.

Dillon Rd

Dillon Rd is constructed as a four-lane median divided roadway in the vicinity of the subject site. The posted speed limit is 30-40 mph going westbound in the vicinity of the subject site. There was no posted speed limit going eastbound on the roadway, so 30 mph was used for the analysis to be consistent with westbound speed limits. The roadway functions as an arterial providing east-west connection for a number of commercial and residential areas. The intersections along its length operate under stop control with the exception of the intersection with McCaslin Blvd which operates under signalized control.



FIGURE 2-1
EXISTING LANE USE AND TRAFFIC CONTROL

KING SOOPERS
LOUISVILLE, CO

(A/A) INTERSECTION LOS
0000/0000 (AM PEAK HOUR/PM PEAK HOUR)

← MOVEMENT
 SIGNALIZED INTERSECTION
 STOP SIGN
 YIELD SIGN



III. Analysis of Existing Conditions

Traffic Volumes

Weekday AM and PM peak hour traffic volume counts were conducted on Tuesday January 14, 2025, from 7:00 AM to 9:00 AM and 4:00 PM to 6:00 PM at the study intersections by IDAX Data Solutions.

The existing volumes are summarized in Figure 3-1. Copies of traffic counts are included in Appendix C. Existing peak hour factors (PHF) were also computed by approach from the traffic counts and applied to the analysis with a minimum of 0.85 and a maximum of 0.92.

Existing Levels of Service

Capacity/level of service (LOS) analyses were conducted at the study intersections based on the existing lane use and traffic controls shown in Figure 2-1 and existing baseline vehicular traffic volumes shown in Figure 3-1. The capacity analysis results are presented in Appendix D and summarized in Table 3-1 and in Figure 3-2.

As shown in Table 3-1 the signalized intersections in the study area currently operate at acceptable overall levels of service (LOS) “D” or better during the weekday peak hours. The unsignalized intersection movements in the study area currently operate at acceptable LOS “B” or better during the weekday peak hours.

Existing Intersection Queues

An analysis of intersection 95th-percentile queues was performed at key locations. The results of the queuing analysis, as reported by Synchro, are summarized in Table 3-2. As shown in the table, all queues are contained within their effective storage.




**FIGURE 3-1
EXISTING VOLUMES**

KING SOOPERS
LOUISVILLE, CO

(A/A) INTERSECTION LOS
0000/0000 (AM PEAK HOUR/PM PEAK HOUR)

← MOVEMENT
 SIGNALIZED INTERSECTION
 STOP SIGN
 YIELD SIGN






FIGURE 3-2
EXISTING LEVELS OF SERVICE

KING SOOPERS
LOUISVILLE, CO

(A/A) INTERSECTION LOS
0000/0000 (AM PEAK HOUR/PM PEAK HOUR)

← MOVEMENT
 SIGNALIZED INTERSECTION
 STOP SIGN
 YIELD SIGN



Table 3-1
King Soopers - Louisville, CO
Existing Intersection Level of Service Summary ⁽¹⁾ ⁽²⁾

Intersection	Operating Condition	Street Name	Approach/ Movement	Existing 2025	
				AM Peak Hour	PM Peak Hour
1 Centennial Pkwy & Century Pl	STOP	Centennial Pkwy	EBL	A [0.0]	A [7.3]
			EBTR	A [0.0]	A [0.0]
		Centennial Pkwy	WBL	A [0.0]	A [0.0]
			WBTR	A [0.0]	A [0.0]
		Century Pl	NBLTR	B [10.5]	A [9.9]
		Century Pl	SBL	B [10.2]	B [10.3]
			SBTR	B [10.3]	A [9.9]
2 Centennial Pkwy & N Site Access	STOP	Centennial Pkwy	EBL	A [7.7]	A [7.3]
			EBTR	A [0.0]	A [0.0]
		Centennial Pkwy	WBL	A [7.4]	A [7.9]
			WBT	A [0.0]	A [0.0]
		N Site Access Driveway	WBR	A [0.0]	A [0.0]
			NBLTR	A [9.9]	B [10.4]
			SBLTR	B [11.2]	B [11.6]
3 Centennial Pkwy & McCaslin Blvd	SIGNAL	Centennial Pkwy	EBL	E (55.5)	D (53.7)
			EBT	D (51.4)	D (51.9)
			EBR	A (0.0)	A (0.0)
		Centennial Pkwy	WBL	E (56.4)	E (56.8)
			WBT	D (49.5)	D (49.2)
			WBR	A (0.0)	A (0.0)
		McCaslin Blvd	NBL	B (10.1)	B (11.7)
			NBT	A (0.7)	A (7.8)
			NBR	A (0.0)	A (0.0)
		McCaslin Blvd	SBL	B (10.7)	A (10.0)
			SBT	B (15.3)	B (15.9)
			SBR	<u>A (0.0)</u>	<u>A (0.0)</u>
		Overall		B (15.9)	B (18.6)
4 E Site Access & McCaslin Blvd	STOP	E Site Access	EBR	A [9.7]	B [10.6]
			WBR	B [10.4]	B [10.2]
		Centennial Marketplace Access	NBL	B [10.7]	B [13.5]
			NBT	A [0.0]	A [0.0]
		McCaslin Blvd	NBTR	A [0.0]	A [0.0]
			SBL	B [12.2]	B [11.7]
		McCaslin Blvd	SBT	A [0.0]	A [0.0]
			SBTR	A [0.0]	A [0.0]
5 Dillon Rd & McCaslin Blvd	SIGNAL	Dillon Rd	EBL	E (58.9)	E (59.3)
			EBT	D (52.1)	E (56.1)
			EBR	A (0.0)	A (0.0)
		Dillon Rd	WBL	E (63.7)	E (65.7)
			WBT	D (38.5)	D (36.9)
			WBR	A (0.0)	A (0.0)
		McCaslin Blvd	NBL	E (67.8)	E (59.4)
			NBT	C (22.6)	C (25.0)
			NBR	A (0.0)	A (0.0)
		McCaslin Blvd	SBL	E (57.8)	F (119.6)
			SBT	A (0.6)	C (30.8)
			SBR	<u>A (0.0)</u>	<u>A (0.0)</u>
		Overall		C (30.3)	D (43.7)
6 Dillon Rd & S Site Access	STOP	Dillon Rd	EBLT	A [0.0]	A [7.4]
			EBTR	A [0.0]	A [0.0]
		Dillon Rd	WBL	A [7.5]	A [7.9]
			WBT	A [0.0]	A [0.0]
		Colony Square Access	WBTR	A [0.0]	A [0.0]
			NBLTR	A [8.7]	A [9.7]
		S Site Access	SBLTR	B [11.8]	B [13.6]
7 Dillon Rd & Century Pl	STOP	Dillon Rd	EBLT	A [7.6]	A [0.0]
			EBTR	A [0.0]	A [0.0]
		Dillon Rd	WBLT	A [7.3]	A [7.4]
			WBTR	A [0.1]	A [0.1]
		Home Depot Access	NBLTR	A [8.7]	A [9.1]
		Century Pl	SBLTR	B [10.8]	B [10.3]

Notes : (1) Numbers in brackets [] represent delay at unsignalized intersections in seconds per vehicle.

(2) Numbers in parenthesis () represent delay at signalized intersections in seconds per vehicle.

Table 3-2
King Soopers - Louisville, CO
Existing Intersection Queueing Summary ⁽¹⁾

Intersection	Operating Condition	Street Name	Approach/ Movement	Available Storage	Existing 2025	
					AM Peak Hour	PM Peak Hour
1 Centennial Pkwy & Century Pl	STOP	Centennial Pkwy	EBL	100	0	0
			EBTR	-	0	0
		Centennial Pkwy	WBL	100	0	0
			WBTR	-	0	0
		Century Pl	NBLTR	-	3	3
		Century Pl	SBL	100	0	8
			SBTR	-	0	3
2 Centennial Pkwy & N Site Access	STOP	Centennial Pkwy	EBL	80	0	0
			EBTR	-	0	0
		Centennial Pkwy	WBL	100	0	3
			WBT	-	0	0
		N Site Access Driveway	WBR	50	0	0
			NBLTR	-	3	5
			SBLTR	-	13	8
3 Centennial Pkwy & McCaslin Blvd	SIGNAL	Centennial Pkwy	EBL	100	87	69
			EBT	-	24	37
			EBR	100	0	0
		Centennial Pkwy	WBL	300	135	142
			WBT	-	50	33
			WBR	-	0	0
		McCaslin Blvd	NBL	325	26	6
			NBT	-	377	70
			NBR	125	0	0
		McCaslin Blvd	SBL	315	45	63
			SBT	-	245	432
			SBR	50	0	0
4 E Site Access & McCaslin Blvd	STOP	E Site Access	EBR	-	3	5
			WBR	-	10	8
		Centennial Marketplace Access	NBL	150	5	3
			NBT	-	0	0
		McCaslin Blvd	NBTR	-	0	0
			SBL	250	8	8
		McCaslin Blvd	SBT	-	0	0
			SBTR	-	0	0
5 Dillon Rd & McCaslin Blvd	SIGNAL	Dillon Rd	EBL	130	26	49
			EBT	-	53	110
			EBR	150	0	0
		Dillon Rd	WBL	500	263	336
			WBT	-	79	82
			WBR	250	0	0
		McCaslin Blvd	NBL	450	119	79
			NBT	-	360	372
			NBR	150	0	0
		McCaslin Blvd	SBL	250	110	189
			SBT	-	176	319
			SBR	100	0	0
6 Dillon Rd & S Site Access	STOP	Dillon Rd	EBLT	-	0	0
			EBTR	-	0	0
		Dillon Rd	WBL	175	3	8
			WBT	-	0	0
		Colony Square Access	WBTR	-	0	0
			NBLTR	-	3	13
		S Site Access	SBLTR	-	3	3
7 Dillon Rd & Century Pl	STOP	Dillon Rd	EBLT	-	0	0
			EBTR	-	0	0
		Dillon Rd	WBLT	-	3	3
			WBTR	-	0	0
		Home Depot Access	NBLTR	-	5	5
			SBLTR	-	3	5
		Century Pl				

Notes : (1) Queue length, in feet, is based on the 95th percentile queue as reported by Synchro, Version 12.

IV. Analysis of Future Conditions without Site Development

Methodology

The future traffic forecasts, without the proposed new use, were developed for 2026 and 2045 conditions based on a composite of existing baseline traffic volumes, regional traffic growth, and pipeline developments. A 1.0% growth factor per year was applied to all movements of existing traffic on the study intersections.

Regional Growth

Increases in traffic associated with regional growth were estimated at 1.0 percent per year compounded for all movements on study intersections up to 2026 as well as to 2045. This growth was determined using CDOT'S Online Transportation Information System's (OTIS) count station #104952 on McCaslin Blvd south of Dillon Rd, and accounts for increases in traffic resulting from influences outside of the immediate study area. The resulting increases in volumes within the study area are reflected in Figure 4-1 for 2026 conditions and Figure 4-2 for 2045 conditions.

Pipeline Developments

One unbuilt/unoccupied (i.e., "pipeline") development was identified for consideration within the study. CU Boulder Faculty Housing is planned to be built at 1164 W Dillon Rd at the site of the vacant Cinebarre. No plans have been submitted to the City for this development, therefore the use for this site was assumed to be Multi-Family Housing (Low-Rise). The existing Cinebarre building is 45,000 square feet (SF), therefore it was assumed that the development could provide 50 dwelling units (DU). With this information, and the proximity to the park and ride, the following development program was included in the background and total future analysis for 2045 conditions:

CU Boulder Faculty Housing

50	DU	Multi-Family Housing (Low-Rise) - Close to Rail Transit
----	----	---

The location of the pipeline developments in relation to the Applicant's property is shown in Figure 4-3. The pipeline development site was assumed to have 80% of its trips going to and from the south on McCaslin Blvd, 10% going to and from the north on McCaslin Blvd, 5% going to and from the east on Centennial Pkwy/Cherry St, and 5% going to and from the east on Dillon Rd. The pipeline site trips are shown in Figure 4-4 for 2045 conditions.

Background Traffic Forecasts

The existing traffic forecasts depicted in Figure 3-1, the regional growth shown in Figure 4-1 (2026) and Figure 4-2 (2045), and the pipeline development site trips shown in Figure 4-4 (2045) were added together to yield the background future traffic forecasts shown in Figure 4-5 for 2026 conditions and Figure 4-6 for 2045 conditions.

Background Future Levels of Service

Capacity analyses of 2026 and 2045 future traffic conditions without the proposed development are provided in Appendix E and summarized in Table 4-1. The forecasted levels of service are also depicted graphically in Figure 4-7 for 2026 conditions and Figure 4-8 for 2045 conditions.

As shown on Table 4-1, under background future 2026 conditions the intersections in the study area are forecasted to operate consistent with existing conditions.

Under background future 2045 conditions the signalized intersections in the study area are forecasted to operate at acceptable overall LOS "D" or better during the weekday peak hours with the exception of the Dillon Rd & McCaslin Blvd intersection which is expected to operate at LOS "E" in the 2045 weekday PM peak hour. The unsignalized intersection movements in the study area are expected to operate at acceptable LOS "C" or better during the weekday peak hours.

Background Future Queueing

An analysis of intersection queues was performed at key locations under background future traffic conditions. The results of the queueing analysis are summarized in Table 4-2.

As shown in the table, queues within the study network will increase due to assumed regional traffic growth. All queues are expected to be contained in their effective storage during background conditions with the exception of the eastbound left movement at the Centennial Pkwy & McCaslin Blvd intersection during the background future long range (2045) weekday AM peak hour.




FIGURE 4-2
BACKGROUND GROWTH 2045

KING SOOPERS
LOUISVILLE, CO

(A/A) INTERSECTION LOS
0000/0000 (AM PEAK HOUR/PM PEAK HOUR)

← MOVEMENT
 SIGNALIZED INTERSECTION
 STOP SIGN
 YIELD SIGN






FIGURE 4-3
PIPELINE LOCATION






**FIGURE 4-4
PIPELINE SITE TRIPS**

KING SOOPERS
LOUISVILLE, CO

(A/A) INTERSECTION LOS
0000/0000 (AM PEAK HOUR/PM PEAK HOUR)

← MOVEMENT
 SIGNALIZED INTERSECTION
 STOP SIGN
 YIELD SIGN






**FIGURE 4-5
BACKGROUND FUTURE FORECASTS 2026**

KING SOOPERS
LOUISVILLE, CO

(A/A) INTERSECTION LOS
0000/0000 (AM PEAK HOUR/PM PEAK HOUR)

← MOVEMENT
SIGNALIZED INTERSECTION
STOP SIGN
YIELD SIGN






**FIGURE 4-6
BACKGROUND FUTURE FORECASTS 2045**

KING SOOPERS
LOUISVILLE, CO

(A/A) INTERSECTION LOS
0000/0000 (AM PEAK HOUR/PM PEAK HOUR)

← MOVEMENT
 SIGNALIZED INTERSECTION
 STOP SIGN
 YIELD SIGN






FIGURE 4-7
BACKGROUND FUTURE LEVELS OF SERVICE 2026

KING SOOPERS
LOUISVILLE, CO

(A/A) INTERSECTION LOS
0000/0000 (AM PEAK HOUR/PM PEAK HOUR)

← MOVEMENT
 SIGNALIZED INTERSECTION
 STOP SIGN
 YIELD SIGN






FIGURE 4-8
BACKGROUND FUTURE LEVELS OF SERVICE 2045

KING SOOPERS
LOUISVILLE, CO

(A/A) INTERSECTION LOS
0000/0000 (AM PEAK HOUR/PM PEAK HOUR)

← MOVEMENT
 SIGNALIZED INTERSECTION
 STOP SIGN
 YIELD SIGN



Table 4-1
King Soopers - Louisville, CO
Background Future Intersection Level of Service Summary ^{(1) (2)}

Intersection	Operating Condition	Street Name	Approach/ Movement	Existing 2025		Background 2026		Background 2045	
				AM Peak Hour	PM Peak Hour	AM Peak Hour	PM Peak Hour	AM Peak Hour	PM Peak Hour
1 Centennial Pkwy & Century Pl	STOP	Centennial Pkwy	EBL	A [0.0]	A [7.3]	A [0.0]	A [7.3]	A [0.0]	A [7.3]
			EBTR	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
		Centennial Pkwy	WBL	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
			WBTR	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
		Century Pl	NBLTR	B [10.5]	A [9.9]	B [10.4]	A [9.8]	B [11.1]	B [10.3]
			SBL	B [10.2]	B [10.3]	B [10.2]	B [10.2]	B [10.9]	B [11.0]
		Century Pl	SBTR	B [10.3]	A [9.9]	B [10.2]	A [9.9]	B [10.8]	B [10.3]
2 Centennial Pkwy & N Site Access	STOP	Centennial Pkwy	EBL	A [7.7]	A [7.3]	A [7.7]	A [7.3]	A [7.9]	A [7.4]
			EBTR	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
		Centennial Pkwy	WBL	A [7.4]	A [7.9]	A [7.4]	A [7.8]	A [7.5]	A [8.0]
			WBT	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
		N Site Access	WBR	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
			NBLTR	A [9.9]	B [10.4]	A [9.9]	B [10.3]	B [10.4]	B [10.8]
		Driveway	SBLTR	B [11.2]	B [11.6]	B [11.2]	B [11.3]	B [12.0]	B [12.2]
3 Centennial Pkwy & McCaslin Blvd	SIGNAL	Centennial Pkwy	EBL	E (55.5)	D (53.7)	E (55.2)	D (53.7)	E (56.2)	D (54.2)
			EBT	D (51.4)	D (51.9)	D (51.5)	D (51.9)	D (51.4)	D (51.9)
			EBR	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)
			WBL	E (56.4)	E (56.8)	E (56.7)	E (56.7)	E (55.6)	E (55.5)
		Centennial Pkwy	WBT	D (49.5)	D (49.2)	D (50.1)	D (49.0)	D (48.3)	D (47.1)
			WBR	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)
			NBL	B (10.1)	B (11.7)	A (9.8)	B (12.0)	B (11.4)	B (15.6)
			NBT	A (0.7)	A (7.8)	A (0.7)	A (8.0)	A (1.2)	A (1.2)
		McCaslin Blvd	NBR	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)
			SBL	B (10.7)	A (10.0)	B (10.4)	B (10.1)	B (12.3)	B (10.7)
			SBT	B (15.3)	B (15.9)	B (14.9)	B (16.3)	B (18.2)	C (21.0)
			SBR	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)
		Overall		B (15.9)	B (18.6)	B (15.3)	B (18.9)	B (16.5)	B (18.6)
		E Site Access	EBR	A [9.7]	B [10.6]	A [9.7]	B [10.5]	A [9.9]	B [11.1]
			WBR	B [10.4]	B [10.2]	B [10.3]	B [10.1]	B [10.7]	B [10.5]
			NBL	B [10.7]	B [13.5]	B [10.6]	B [14.0]	B [11.3]	C [16.8]
			NBT	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
4 E Site Access & McCaslin Blvd	STOP	Centennial Marketplace Access	NBTR	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
			SBL	B [12.2]	B [11.7]	B [12.3]	B [11.9]	B [13.7]	B [12.9]
			SBT	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
			SBTR	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
		McCaslin Blvd	EBL	E (58.9)	E (59.3)	E (59.0)	E (59.1)	E (58.7)	E (60.0)
			EBT	D (52.1)	E (56.1)	D (52.0)	E (55.7)	D (52.3)	E (57.8)
			EBR	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)
			WBL	E (63.7)	E (65.7)	E (64.3)	E (66.6)	F (84.4)	F (117.0)
		Dillon Rd	WBT	D (38.5)	D (36.9)	D (38.2)	D (36.5)	D (37.4)	D (36.9)
			WBR	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)
			NBL	E (67.8)	E (59.4)	D (38.3)	E (59.4)	F (95.7)	E (59.9)
			NBT	C (22.6)	C (25.0)	C (22.8)	C (25.5)	C (28.3)	C (28.8)
		McCaslin Blvd	NBR	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)
			SBL	E (57.8)	F (119.6)	E (56.8)	F (124.3)	E (60.4)	F (203.6)
			SBT	A (0.6)	C (30.8)	A (0.8)	C (31.3)	A (2.0)	D (44.5)
			SBR	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)
		Overall		C (30.3)	D (43.7)	C (31.0)	D (44.4)	D (39.2)	E (64.7)
5 Dillon Rd & McCaslin Blvd	SIGNAL	Dillon Rd	EBLT	A [0.0]	A [7.4]	A [0.0]	A [7.4]	A [0.0]	A [7.5]
			EBTR	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
			WBL	A [7.5]	A [7.9]	A [7.5]	A [7.9]	A [7.5]	A [8.1]
			WBT	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
		Dillon Rd	WBTR	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
			NBLTR	A [8.7]	A [9.7]	A [8.6]	A [9.6]	A [8.8]	A [10.0]
			SBLTR	B [11.8]	B [13.6]	B [11.6]	B [13.1]	B [12.7]	C [15.4]
		Colony Square Access	EBLT	A [7.6]	A [0.0]	A [7.5]	A [0.0]	A [7.7]	A [0.0]
			EBTR	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
			WBLT	A [7.3]	A [7.4]	A [7.3]	A [7.5]	A [7.4]	A [7.6]
			WBTR	A [0.1]	A [0.1]	A [0.1]	A [0.1]	A [0.2]	A [0.1]
6 Dillon Rd & S Site Access	STOP	Dillon Rd	NBLTR	A [8.7]	A [9.1]	A [8.7]	A [9.1]	A [8.8]	A [9.5]
			SBLTR	B [10.8]	B [10.3]	B [10.6]	B [10.3]	B [11.3]	B [11.2]
		Home Depot Access	EBLT	A [7.6]	A [0.0]	A [7.5]	A [0.0]	A [7.7]	A [0.0]
			EBTR	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
			WBLT	A [7.3]	A [7.4]	A [7.3]	A [7.5]	A [7.4]	A [7.6]
			WBTR	A [0.1]	A [0.1]	A [0.1]	A [0.1]	A [0.2]	A [0.1]
		Century Pl	NBLTR	A [8.7]	A [9.1]	A [8.7]	A [9.1]	A [8.8]	A [9.5]
			SBLTR	B [10.8]	B [10.3]	B [10.6]	B [10.3]	B [11.3]	B [11.2]
7 Dillon Rd & Century Pl	STOP	Dillon Rd	EBLT	A [7.6]	A [0.0]	A [7.5]	A [0.0]	A [7.7]	A [0.0]
			EBTR	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
			WBLT	A [7.3]	A [7.4]	A [7.3]	A [7.5]	A [7.4]	A [7.6]
			WBTR	A [0.1]	A [0.1]	A [0.1]	A [0.1]	A [0.2]	A [0.1]
		Home Depot Access	NBLTR	A [8.7]	A [9.1]	A [8.7]	A [9.1]	A [8.8]	A [9.5]
			SBLTR	B [10.8]	B [10.3]	B [10.6]	B [10.3]	B [11.3]	B [11.2]
		Century Pl	EBLT	A [7.6]	A [0.0]	A [7.5]	A [0.0]	A [7.7]	A [0.0]
			EBTR	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
			WBLT	A [7.3]	A [7.4]	A [7.3]	A [7.5]	A [7.4]	A [7.6]
			WBTR	A [0.1]	A [0.1]	A [0.1]	A [0.1]	A [0.2]	A [0.1]

Notes : (1) Numbers in brackets [] represent delay at unsignalized intersections in seconds per vehicle.
(2) Numbers in parenthesis () represent delay at signalized intersections in seconds per vehicle.

Table 4-2
King Soopers - Louisville, CO
Background Future Intersection Queueing Summary ⁽¹⁾

Intersection	Operating Condition	Street Name	Approach/ Movement	Available Storage	Existing 2025		Background 2026		Background 2045	
					AM Peak Hour	PM Peak Hour	AM Peak Hour	PM Peak Hour	AM Peak Hour	PM Peak Hour
1 Centennial Pkwy & Century Pl	STOP	Centennial Pkwy	EBL	100	0	0	0	0	0	0
			EBTR	-	0	0	0	0	0	0
		Centennial Pkwy	WBL	100	0	0	0	0	0	0
			WBTR	-	0	0	0	0	0	0
		Century Pl	NBLTR	-	3	3	3	3	3	3
		Century Pl	SBL	100	0	8	0	8	0	8
			SBTR	-	0	3	0	3	0	3
2 Centennial Pkwy & N Site Access	STOP	Centennial Pkwy	EBL	80	0	0	0	0	0	0
			EBTR	-	0	0	0	0	0	0
		Centennial Pkwy	WBL	100	0	3	0	3	0	3
			WBT	-	0	0	0	0	0	0
		N Site Access Driveway	WBR	50	0	0	0	0	0	0
			NBLTR	-	3	5	3	3	5	5
			SBLTR	-	13	8	10	5	13	8
3 Centennial Pkwy & McCaslin Blvd	SIGNAL	Centennial Pkwy	EBL	100	87	69	88	72	103	82
			EBT	-	24	37	25	38	28	44
			EBR	100	0	0	0	0	0	0
		Centennial Pkwy	WBL	300	135	142	139	145	160	168
			WBT	-	50	33	53	33	58	38
			WBR	-	0	0	0	0	0	0
		McCaslin Blvd	NBL	325	26	6	24	6	36	6
			NBT	-	377	70	350	68	517	83
			NBR	125	0	0	0	0	0	0
		McCaslin Blvd	SBL	315	45	63	44	35	56	83
			SBT	-	245	432	238	447	333	670
			SBR	50	0	0	0	0	0	0
4 E Site Access & McCaslin Blvd	STOP	E Site Access	EBR	-	3	5	3	5	3	5
			WBR	-	10	8	8	8	10	8
		Centennial Marketplace Access	NBL	150	5	3	5	5	5	5
			NBT	-	0	0	0	0	0	0
		McCaslin Blvd	NBTR	-	0	0	0	0	0	0
			SBL	250	8	8	8	8	8	10
		McCaslin Blvd	SBT	-	0	0	0	0	0	0
			SBTR	-	0	0	0	0	0	0
5 Dillon Rd & McCaslin Blvd	SIGNAL	Dillon Rd	EBL	130	26	49	26	49	32	58
			EBT	-	53	110	53	112	63	129
			EBR	150	0	0	0	0	0	0
		Dillon Rd	WBL	500	263	336	273	347	365	457
			WBT	-	79	82	80	83	93	96
			WBR	250	0	0	0	0	0	0
		McCaslin Blvd	NBL	450	119	79	123	79	163	102
			NBT	-	360	372	370	380	481	501
			NBR	150	0	0	0	0	0	0
		McCaslin Blvd	SBL	250	110	189	111	191	130	244
			SBT	-	176	319	180	329	216	443
			SBR	100	0	0	0	0	0	0
6 Dillon Rd & S Site Access	STOP	Dillon Rd	EBLT	-	0	0	0	0	0	0
			EBTR	-	0	0	0	0	0	0
		Dillon Rd	WBL	175	3	8	3	8	3	8
			WBT	-	0	0	0	0	0	0
		Colony Square Access	WBTR	-	0	0	0	0	0	0
			NBLTR	-	3	13	3	10	3	13
		S Site Access	SBLTR	-	3	3	3	3	3	3
7 Dillon Rd & Century Pl	STOP	Dillon Rd	EBLT	-	0	0	0	0	0	0
			EBTR	-	0	0	0	0	0	0
		Dillon Rd	WBLT	-	3	3	3	3	3	3
			WBTR	-	0	0	0	0	0	0
		Home Depot Access	NBLTR	-	5	5	5	5	5	5
		Century Pl	SBLTR	-	3	5	3	5	3	5

Notes : (1) Queue length, in feet, is based on the 95th percentile queue as reported by Synchro, Version 12.

V. Site Analysis

Overview

The Applicant is proposing to redevelop the approximately 13.5-acre site with commercial uses consisting of a supermarket and gas station use. For purposes of this study, the site is assumed complete and occupied in 2026. The following use and development programs were analyzed:

Build-Out 2026:

136,380	SF	Supermarket
14	FP	Gas Station

Proposed Site Access

As shown on the Applicant's conceptual plan (Figure 1-2), access to the development is being proposed via the existing right-in/right-out (RIRO) access on Centennial Pkwy, full movement access on Centennial Pkwy, $\frac{3}{4}$ movement access on McCaslin Blvd, RIRO access on Dillon Rd, two full movement accesses on Dillon Rd, and two full movement accesses on Century Pl. No change to the lane use and traffic control is being proposed.

Trip Generation

Overview

Trip generation estimates for the weekday AM and PM peak hours, as well as the weekday average daily traffic (ADT), were derived from the standard Institute of Transportation Engineers (ITE) Trip Generation Manual rates/equations, as published in the 11th edition. The trip generation analysis is presented in Table 5-1.

Internal Capture

Due to the mixed-use nature of the proposed development, it is assumed that a number of trips would be shared between the uses. These are trips that are going from one use on site to another use on site and should not be counted as separate trips for each use. An internal capture reduction of 10% was applied to the trip generation analysis consistent with ITE methodologies:

- Internal Capture: 10%

Pass-by Trips

According to ITE, in some cases the driveway volumes at a particular land use are different from the amount of traffic added to the adjacent street system. Uses such as commercial establishments attract a portion of their trips from traffic that is already present on the road network. Pass-by trips are those trips which are made as intermediate stops on the way to a primary destination. An example of a pass-by trip would be one in which a driver stops at a grocery store or a gas station on his/her way from work.

The proposed use would experience pass-by trips consistent with the primary uses located on site. In recognition of this phenomenon and consistent with ITE published data, the following pass-by reductions were applied to the trip generation analysis:

- Supermarket: 0% AM / 24% PM
- Gas Station: 63% AM / 57% PM

As shown in Table 5-1, the site in total is anticipated to generate 82 weekday AM and 315 weekday PM peak hour pass-by trips. Therefore, these trips would be drawn from the existing road network and assigned to the future site entrances accordingly. Trip distributions for pass-by trips were considered only along northbound and southbound McCaslin Blvd. It was assumed that 40% of pass-by trips would come from the north and 60% would come from the south. Pass-by trip assignments at key study intersections are shown in Figure 5-1.

Net Site Trips

The vehicle trips that would be generated by the proposed development plan are summarized in Table 5-1. As shown in Table 5-1, the site would generate upon completion and full occupancy 399 net new weekday AM and 755 net new weekday PM peak hour vehicle trips, as well as 10,301 net new weekday daily trips.

Site Trip Distributions

The distribution of the anticipated trips generated by the completion of the proposed development was based on an examination of existing traffic counts and local knowledge. Existing travel patterns indicate the following distribution is appropriate in the forecasting of net new future site traffic:

- To/from the north on McCaslin Blvd: 25%
- To/from the south on McCaslin Blvd: 40%
- To/from the east on Centennial Pkwy/Cherry St: 10%
- To/from the west on Centennial Pkwy/Cherry St: 5%
- To/from the east on Dillon Rd: 20%

Site Trip Assignments

The assignment of the new vehicle trips generated upon the future build-out of the development project was based on the above distribution. The net new trips assignments are depicted in Figure 5-2.




FIGURE 5-1
PASS-BY TRIPS

KING SOOPERS
LOUISVILLE, CO

(A/A) INTERSECTION LOS
0000/0000 (AM PEAK HOUR/PM PEAK HOUR)

← MOVEMENT
 SIGNALIZED INTERSECTION
 STOP SIGN
 YIELD SIGN






FIGURE 5-2
SITE TRIPS

KING SOOPERS
LOUISVILLE, CO

(A/A) INTERSECTION LOS
0000/0000 (AM PEAK HOUR/PM PEAK HOUR)

← MOVEMENT
 SIGNALIZED INTERSECTION
 STOP SIGN
 YIELD SIGN



Table 5-1

King Soopers - Louisville, CO

Site Trip Generation

Land Use	Land Use Code	Amount	Units	AM Peak Hour			PM Peak Hour			Average Daily Trips
				In	Out	Total	In	Out	Total	
<i>Proposed ⁽¹⁾</i>										
Supermarket	850	136,380	SF	230	160	390	497	497	994	11,912
			<i>Internal Capture (10%)</i>	(23)	(16)	(39)	(50)	(49)	(99)	(1,191)
			External Trips	207	144	351	447	448	895	10,721
			<i>Pass-by's (0% AM / 24% PM)</i>	<u>0</u>	<u>0</u>	<u>0</u>	<u>(107)</u>	<u>(108)</u>	<u>(215)</u>	<u>(1,287)</u>
			Net New Trips	207	144	351	340	340	680	9,434
Gas Station	944	14	FP	72	72	144	98	97	195	2,408
			<i>Internal Capture (10%)</i>	(7)	(7)	(14)	(10)	(10)	(20)	(241)
			External Trips	65	65	130	88	87	175	2,167
			<i>Pass-by's (63% AM / 57% PM)</i>	<u>(41)</u>	<u>(41)</u>	<u>(82)</u>	<u>(50)</u>	<u>(50)</u>	<u>(100)</u>	<u>(1,300)</u>
			Net New Trips	24	24	48	38	37	75	867
Total Proposed Site Trips				302	232	534	595	594	1,189	14,320
<i>Internal Capture (10%)</i>				(30)	(23)	(53)	(60)	(59)	(119)	(1,432)
Total Proposed External Trips				272	209	481	535	535	1,070	12,888
<i>Total Proposed Pass-by Trips</i>				<u>(41)</u>	<u>(41)</u>	<u>(82)</u>	<u>(157)</u>	<u>(158)</u>	<u>(315)</u>	<u>(2,587)</u>
Proposed Net New Total				231	168	399	378	377	755	10,301

Note(s):

(1) Trip generation based on the Institute of Transportation Engineers' Trip Generation Manual, 11th Edition

VI. Analysis of Future Conditions with Site Development

Total Future Traffic Forecasts

The 2026 and 2045 total future traffic forecasts associated with the proposed development were developed by combining the background future forecasts shown in Figure 4-5 (2026) and Figure 4-6 (2045), the pass-by trips shown in Figure 5-1, and the site trip assignments shown in Figure 5-2. The resulting total future traffic forecasts are provided in Figure 6-1 for 2026 conditions and Figure 6-2 for 2045 conditions.

Total Future Levels of Service with Proposed Development

Future levels of service with the proposed development plan were estimated at key study intersections based on the future traffic volumes shown in Figures 6-1 and Figure 6-2, the existing lane use in Figure 2-1, and the HCM 7th methodologies for signalized and unsignalized intersections. The results of these analyses are provided in Appendix F and presented in Table 6-1. Total future levels of service are also presented graphically in Figure 6-3 (2026) and Figure 6-4 (2045).

As shown in Table 6-1, levels of service under future site development conditions would remain generally consistent with future background conditions (i.e., without site development). Overall delays would experience a minor increase due to site trips. The signalized intersections within the study area would continue to operate at acceptable overall LOS “D” or better during the weekday peak hours in all total future scenarios with the exception of the Dillon Rd & McCaslin Blvd intersection which would operate at LOS “E” during the total future 2026 and 2045 PM scenarios. The unsignalized intersection movements would operate at acceptable LOS “D” or better during the weekday peak hours in all future scenarios.

To mitigate the increased delay at the Dillon Rd & McCaslin Blvd intersection for total future conditions, it is recommended that the timings of the signal be optimized. As shown in Table 6-1, with signal timing adjustments, the intersection of Dillon Rd & McCaslin Blvd is expected to operate at overall acceptable LOS “D” for all total future scenarios.

Total Future Queuing

Total future queues were forecasted using Synchro software. The results of the queuing analysis are summarized in Table 6-2. All queues are expected to be contained in their effective storage with the exception of the eastbound left turn lane at the Centennial Pkwy & McCaslin Blvd intersection which would exceed its storage in all total future scenarios with existing signal timing. As shown in Table 6-2, with signal timing adjustments to the Dillon Rd & McCaslin Blvd intersection, all queues for that intersection are expected to continue to be contained within their effective storage for all total future scenarios.




FIGURE 6-1
TOTAL FUTURE FORECASTS 2026

KING SOOPERS
LOUISVILLE, CO

(A/A) INTERSECTION LOS
0000/0000 (AM PEAK HOUR/PM PEAK HOUR)

- ← MOVEMENT
- ◫ SIGNALIZED INTERSECTION
- STOP STOP SIGN
- YIELD YIELD SIGN






FIGURE 6-2
TOTAL FUTURE FORECASTS 2045

KING SOOPERS
LOUISVILLE, CO

(A/A) INTERSECTION LOS
0000/0000 (AM PEAK HOUR/PM PEAK HOUR)

← MOVEMENT
SIGNALIZED INTERSECTION
STOP SIGN
YIELD SIGN






FIGURE 6-3
TOTAL FUTURE LEVELS OF SERVICE 2026

KING SOOPERS
LOUISVILLE, CO

(A/A) INTERSECTION LOS
0000/0000 (AM PEAK HOUR/PM PEAK HOUR)

← MOVEMENT
 SIGNALIZED INTERSECTION
 STOP SIGN
 YIELD SIGN






FIGURE 6-4
TOTAL FUTURE LEVELS OF SERVICE 2045

KING SOOPERS
LOUISVILLE, CO

(A/A) INTERSECTION LOS
0000/0000 (AM PEAK HOUR/PM PEAK HOUR)

← MOVEMENT
 SIGNALIZED INTERSECTION
 STOP SIGN
 YIELD SIGN



Table 6-1
King Soopers - Louisville, CO
Total Future Intersection Level of Service Summary ^{(1) (2)}

Intersection	Operating Condition	Street Name	Approach/ Movement	Background 2026		Background 2045		Total Future 2026		Total Future 2045	
				AM Peak Hour	PM Peak Hour	AM Peak Hour	PM Peak Hour	AM Peak Hour	PM Peak Hour	AM Peak Hour	PM Peak Hour
1 Centennial Pkwy & Century Pl	STOP	Centennial Pkwy	EBL	A [0.0]	A [7.3]	A [0.0]	A [7.3]	A [0.0]	A [7.3]	A [0.0]	A [0.0]
			EBTR	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
		Centennial Pkwy	WBL	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
			WBTR	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
		Century Pl	NBLTR	B [10.4]	A [9.8]	B [11.1]	B [10.3]	B [10.2]	A [10.0]	B [10.8]	B [10.6]
2 Centennial Pkwy & N Site Access	STOP	Centennial Pkwy	SBL	B [10.2]	B [10.2]	B [10.9]	B [11.0]	B [10.5]	B [10.9]	B [11.3]	B [11.8]
			SBTR	B [10.2]	A [9.9]	B [10.8]	B [10.3]	B [10.4]	B [10.2]	B [11.0]	B [10.7]
		Centennial Pkwy	EBL	A [7.7]	A [7.3]	A [7.9]	A [7.4]	A [7.8]	A [7.4]	A [7.9]	A [7.4]
			EBTR	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
		N Site Access Driveway	WBL	A [7.4]	A [7.8]	A [7.5]	A [8.0]	A [7.5]	A [8.1]	A [7.6]	A [8.3]
3 Centennial Pkwy & McCaslin Blvd	SIGNAL	Centennial Pkwy	WBT	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
			WBR	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
		Centennial Pkwy	NBL	A [9.8]	B [12.0]	B [11.4]	B [15.6]	B [10.8]	B [17.3]	B [12.7]	C [22.8]
			NBT	A [0.7]	A [8.0]	A [1.2]	A [1.2]	A [0.8]	A [1.6]	A [1.3]	A [4.9]
		McCaslin Blvd	NBR	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
			SBL	B [10.4]	B [10.1]	B [12.3]	B [10.7]	B [11.5]	B [13.9]	B [13.8]	B [15.8]
		McCaslin Blvd	SBT	B [14.9]	B [16.3]	B [18.2]	C [21.0]	B [16.4]	C [23.7]	C [20.4]	C [32.0]
			SBR	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
		Overall		B [15.3]	B [18.9]	B [16.5]	B [18.6]	B [18.2]	C [24.5]	B [19.2]	C [28.4]
		E Site Access	EBR	A [9.7]	B [10.5]	A [9.9]	B [11.1]	B [10.2]	B [12.6]	B [10.5]	B [13.4]
			WBR	B [10.3]	B [10.1]	B [10.7]	B [10.5]	B [10.3]	A [10.0]	B [10.7]	B [10.4]
		Centennial Marketplace Access	NBL	B [10.6]	B [14.0]	B [11.3]	C [16.8]	B [11.7]	C [20.6]	B [12.8]	D [34.9]
		McCaslin Blvd	NBT	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
			NBTR	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
		McCaslin Blvd	SBL	B [12.3]	B [11.9]	B [13.7]	B [12.9]	B [12.1]	B [11.6]	B [13.4]	B [12.5]
			SBT	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
			SBTR	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
5 Dillon Rd & McCaslin Blvd	SIGNAL	Dillon Rd	EBL	E (59.0)	E (59.1)	E (58.7)	E (60.0)	E (58.8)	E (60.2)	E (58.7)	E (60.1)
			EBT	D (52.0)	E (55.7)	D (52.3)	E (57.8)	D (53.0)	E (61.1)	D (53.3)	E (60.5)
		Dillon Rd	EBR	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)
			WBL	E (64.3)	E (66.6)	F (84.4)	F (117.0)	E (64.3)	E (66.6)	F (84.4)	F (117.0)
		Dillon Rd	WBT	D (38.2)	D (36.5)	D (37.4)	D (36.9)	D (38.9)	D (37.4)	D (38.1)	D (37.1)
			WBR	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)
		McCaslin Blvd	NBL	D (38.3)	E (59.4)	F (95.7)	E (59.9)	F (126.6)	E (76.2)	F (189.1)	F (107.7)
			NBT	C (22.8)	C (25.5)	C (28.3)	C (28.8)	C (23.7)	C (26.1)	C (29.7)	C (30.7)
		McCaslin Blvd	NBR	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)
			SBL	E (56.8)	F (124.3)	E (60.4)	E (58.5)	F (195.2)	F (185.2)	E (64.8)	F (276.4)
		McCaslin Blvd	SBT	A (0.8)	C (31.3)	A (2.0)	D (44.5)	A (1.0)	D (44.0)	B (13.9)	D (49.5)
			SBR	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)	A (0.0)
		Overall		C (31.0)	D (44.4)	D (39.2)	E (64.7)	D (37.2)	E (56.2)	D (51.6)	E (75.9)
	Optimized Signal Timings	Dillon Rd	EBL	-	-	-	-	-	E (60.2)	-	E (60.1)
			EBT	-	-	-	-	-	E (61.1)	-	E (60.7)
		Dillon Rd	EBR	-	-	-	-	-	A (0.0)	-	A (0.0)
			WBL	-	-	-	-	-	E (74.5)	-	E (74.6)
		Dillon Rd	WBT	-	-	-	-	-	D (38.1)	-	C (34.7)
			WBR	-	-	-	-	-	A (0.0)	-	A (0.0)
		McCaslin Blvd	NBL	-	-	-	-	-	E (68.7)	-	E (55.4)
			NBT	-	-	-	-	-	C (28.6)	-	D (44.2)
		McCaslin Blvd	NBR	-	-	-	-	-	A (0.0)	-	A (0.0)
			SBL	-	-	-	-	-	E (71.9)	-	E (56.0)
6 Dillon Rd & S Site Access	STOP	Dillon Rd	EBLT	A [0.0]	A [7.4]	A [0.0]	A [7.5]	A [0.0]	A [7.9]	A [0.0]	A [8.0]
			EBTR	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
		Dillon Rd	WBL	A [7.5]	A [7.9]	A [7.5]	A [8.1]	A [7.5]	A [7.9]	A [7.6]	A [8.2]
			WBT	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
		Colony Square Access	WBTR	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
			NBLTR	A [8.6]	A [9.6]	A [8.8]	A [10.0]	A [8.7]	A [9.7]	A [8.8]	B [10.1]
		S Site Access	SBLTR	B [11.6]	B [13.1]	B [12.7]	C [15.4]	B [13.0]	C [22.8]	B [14.6]	D [33.7]
		Dillon Rd	EBLT	A [7.5]	A [0.0]	A [7.7]	A [0.0]	A [7.6]	A [0.0]	A [7.7]	A [0.0]
			EBTR	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]	A [0.0]
		Dillon Rd	WBLT	A [7.3]	A [7.5]	A [7.4]	A [7.6]	A [7.3]	A [7.5]	A [7.4]	A [7.6]
			WBTR	A [0.1]	A [0.1]	A [0.2]	A [0.1]	A [0.1]	A [0.1]	A [0.2]	A [0.1]
		Home Depot Access	NBLTR	A [8.7]	A [9.1]	A [8.8]	A [9.5]	A [8.7]	A [9.2]	A [8.8]	A [9.5]
			SBLTR	B [10.6]	B [10.3]	B [11.3]	B [11.2]	B [10.9]	B [10.5]	B [11.6]	B [11.5]
		Century Pl									

Notes : (1) Numbers in brackets [] represent delay at unsignalized intersections in seconds per vehicle.
(2) Numbers in parenthesis () represent delay at signalized intersections in seconds per vehicle.

Table 6-2
King Soopers - Louisville, CO
Total Future Intersection Queueing Summary ⁽¹⁾

Intersection	Operating Condition	Street Name	Approach/ Movement	Available Storage	Background 2026		Background 2045		Total Future 2026		Total Future 2045	
					AM Peak Hour	PM Peak Hour	AM Peak Hour	PM Peak Hour	AM Peak Hour	PM Peak Hour	AM Peak Hour	PM Peak Hour
1 Centennial Pkwy & Century Pl	STOP	Centennial Pkwy	EBL	100	0	0	0	0	0	0	0	0
			EBTR	-	0	0	0	0	0	0	0	0
		Centennial Pkwy	WBL	100	0	0	0	0	0	0	0	0
			WBTR	-	0	0	0	0	0	0	0	0
		Century Pl	NBLTR	-	3	3	3	3	5	5	5	5
		Century Pl	SBL	100	0	8	0	8	0	8	0	10
			SBTR	-	0	3	0	3	0	3	0	3
2 Centennial Pkwy & N Site Access	STOP	Centennial Pkwy	EBL	80	0	0	0	0	0	0	0	0
			EBTR	-	0	0	0	0	0	0	0	0
		Centennial Pkwy	WBL	100	0	3	0	3	3	8	3	8
			WBT	-	0	0	0	0	0	0	0	0
		N Site Access Driveway	WBR	50	0	3	0	0	0	0	0	0
			NBLTR	-	3	5	5	5	13	40	13	45
			SBLTR	-	10	5	13	8	15	13	15	15
3 Centennial Pkwy & McCaslin Blvd	SIGNAL	Centennial Pkwy	EBL	100	88	72	103	82	154	253	166	282
			EBT	-	25	38	28	44	34	53	36	57
		Centennial Pkwy	EBR	100	0	0	0	0	0	0	0	0
			WBL	300	139	145	160	168	143	153	165	176
		Centennial Pkwy	WBT	-	53	33	58	38	66	58	71	60
			WBR	-	0	0	0	0	0	0	0	0
		McCaslin Blvd	NBL	325	24	6	36	6	29	8	65	8
			NBT	-	350	68	517	83	407	256	539	511
		McCaslin Blvd	NBR	125	0	0	0	0	0	0	0	0
			SBL	315	44	35	56	83	51	88	63	109
		McCaslin Blvd	SBT	-	238	447	333	670	278	627	371	871
			SBR	50	0	0	0	0	0	0	0	0
4 E Site Access & McCaslin Blvd	STOP	E Site Access	EBR	-	3	5	3	5	13	35	13	38
			WBR	-	8	8	10	8	8	8	10	8
		Centennial Marketplace Access	NBL	150	5	5	5	5	18	55	20	93
			NBT	-	0	0	0	0	0	0	0	0
		McCaslin Blvd	NBTR	-	0	0	0	0	0	0	0	0
			SBL	250	8	8	8	10	5	8	8	10
		McCaslin Blvd	SBT	-	0	0	0	0	0	0	0	0
			SBTR	-	0	0	0	0	0	0	0	0
5 Dillon Rd & McCaslin Blvd	SIGNAL	Dillon Rd	EBL	130	26	49	32	58	29	59	34	68
			EBT	-	53	112	63	129	76	151	83	167
		Dillon Rd	EBR	150	0	0	0	0	0	0	0	0
			WBL	500	273	347	365	457	273	347	365	457
		Dillon Rd	WBT	-	80	83	93	96	104	116	116	128
			WBR	250	0	0	0	0	0	0	0	0
		McCaslin Blvd	NBL	450	123	79	163	102	189	188	228	228
			NBT	-	370	380	481	501	396	408	513	536
		McCaslin Blvd	NBR	150	0	0	0	0	0	0	0	0
			SBL	250	111	191	130	244	120	230	144	241
		McCaslin Blvd	SBT	-	180	329	216	443	186	456	222	581
			SBR	100	0	0	0	0	0	0	0	0
	Optimized Signal Timings	Dillon Rd	EBL	130	-	-	-	-	-	60	-	68
			EBT	-	-	-	-	-	-	151	-	167
		Dillon Rd	EBR	150	-	-	-	-	-	0	-	0
			WBL	500	-	-	-	-	-	359	-	422
		Dillon Rd	WBT	-	-	-	-	-	-	114	-	123
			WBR	250	-	-	-	-	-	0	-	0
		McCaslin Blvd	NBL	450	-	-	-	-	-	176	-	165
			NBT	-	-	-	-	-	-	427	-	760
		McCaslin Blvd	NBR	150	-	-	-	-	-	0	-	0
			SBL	250	-	-	-	-	-	180	-	157
		McCaslin Blvd	SBT	-	-	-	-	-	-	456	-	740
			SBR	100	-	-	-	-	-	0	-	0
6 Dillon Rd & S Site Access	STOP	Dillon Rd	EBLT	-	0	0	0	0	0	0	0	0
			EBTR	-	0	0	0	0	0	0	0	0
		Dillon Rd	WBL	175	3	8	3	8	3	8	3	8
			WBT	-	0	0	0	0	0	0	0	0
		Colony Square Access	WBTR	-	0	0	0	0	0	0	0	0
			NBLTR	-	3	10	3	13	3	10	3	13
		S Site Access	SBLTR	-	3	3	3	3	10	53	13	78
7 Dillon Rd & Century Pl	STOP	Dillon Rd	EBLT	-	0	0	0	0	0	0	0	0
			EBTR	-	0	0	0	0	0	0	0	0
		Dillon Rd	WBLT	-	3	3	3	3	3	3	3	3
			WBTR	-	0	0	0	0	0	0	0	0
		Home Depot Access	NBLTR	-	5	5	5	5	5	5	5	5
		Century Pl	SBLTR	-	3	5	3	5	3	8	3	8

Notes : (1) Queue length, in feet, is based on the 95th percentile queue as reported by Synchro, Version 12.

VII. Conclusions and Recommendations

Conclusions

Based on the results of this traffic impact study, the following may be concluded:

- Under existing traffic conditions, the signalized intersections in the study area currently operate at acceptable overall levels of service (LOS) “D” or better during the weekday peak hours. The unsignalized intersection movements in the study area currently operate at acceptable LOS “B” or better during the weekday peak hours. All queues are contained within their effective storage.
- Under background future 2026 and 2045 traffic conditions, without the development of the subject site, delays would increase slightly at study intersections due to regional traffic growth. The signalized intersections in the study area are forecasted to operate at acceptable overall LOS “D” or better during the weekday peak hours with the exception of the Dillon Rd & McCaslin Blvd intersection which is forecasted to operate at LOS “E” during the long range (2045) weekday PM peak hour. The unsignalized intersection movements in the study area would operate at acceptable LOS “C” or better during the weekday peak hours. All queues are expected to be contained within their effective storage with the exception of the eastbound left movement at the Centennial Pkwy & McCaslin Blvd intersection during the long range (2045) weekday AM peak hour.
- The proposed site redevelopment would generate, upon completion and full occupancy, 399 net new weekday AM and 755 net new weekday PM peak hour vehicle trips as well as 10,301 net new weekday daily trips.
- Under total future 2026 and 2045 traffic conditions with development of the site, the signalized intersections within the study area would continue to operate at acceptable overall LOS “D” or better during the weekday peak hours in all total future scenarios with the exception of the Dillon Rd & McCaslin Blvd intersection which would operate at LOS “E” during the weekday PM peak hour for total future 2026 and 2045 conditions. The unsignalized intersection movements in the study area would operate at acceptable LOS “D” or better during the weekday peak hours in all future scenarios.
- Under total future 2026 and 2045 traffic conditions with development of the site, all queues are expected to be contained within their effective storage with the exception of the eastbound left turn lane at the intersection of Centennial Pkwy & McCaslin Blvd which would exceed the available storage during all total future scenarios.

Recommendations

- It is recommended that the Applicant provide access consistent with the site plan contained herein.
- It is recommended that the signal timings at Dillon Rd & McCaslin Blvd be optimized once the subject site is operational to improve overall operations of the intersection including better LOS and accommodate anticipated queues.
- It is recommended that the eastbound left turn lane at Centennial Pkwy & McCaslin Blvd be extended to accommodate the queue.

APPENDIX A – Full Sized Conceptual Plan

PARCEL L, LOT 5, FILING NO.1,
CASE #: PUPD-000530-2024

500 Greenwood Plaza Blvd., Suite 200
Greenwood Village, CO 80111
303.770.8884
GallowayUS.com

NOT FOR CONSTRUCTION

COPYRIGHT
THESE PLANS ARE AN INSTRUMENT OF SERVICE
AND ARE THE PROPERTY OF GALLOWAY, AND MAY
NOT BE DUPLICATED, DISCLOSED, OR REPRODUCED
WITHOUT THE WRITTEN CONSENT OF GALLOWAY.
COPYRIGHTS AND INFRINGEMENTS WILL BE
ENFORCED AND PROSECUTED.



KING SOOPERS STORE #142
5TH PUD AMENDMENT

1171 W. DILLON ROAD
CITY OF LOUISVILLE, BOULDER COUNTY, COLORADO

[illegible]

Project No:	KSS0000142.02
Drawn By:	SE
Checked By:	JDP
Date:	APRIL 11, 2025

SITE PLAN

2
F 19



PROPERTY LINE

ADJACENT PROPERTY LINE

EXISTING EASEMENT LINE

PROPOSED SAWCUT LINE

EXISTING FENCE TO REMAIN

PROPOSED SWALE FLOWLINE

PROPOSED CURB AND GUTTER

EXISTING CURB AND GUTTER

PROPOSED ADA STRIPING

PROPOSED STANDARD DUTY ASPHALT

PROPOSED CONCRETE PAVEMENT

- 1 PROPOSED CURB AND GUTTER
- 2 EXISTING CURB AND GUTTER TO REMAIN
- 3 PROPOSED SIDEWALK (MIN. WIDTH 5')
- 4 EXISTING SIDEWALK TO REMAIN (MIN. WIDTH 5')
- 5 PROPOSED PAVEMENT MARKING
- 6 EXISTING FIRE HYDRANT TO REMAIN
- 7 PROPOSED TRASH ENCLOSURE
- 8 PROPOSED TRASH COMPACTOR
- 9 PROPOSED PEDESTRIAN RAMP (MIN. WIDTH 5')
- 10 EXISTING LOADING DOCK
- 11 PROPOSED STANDARD DUTY ASPHALT PAVEMENT
- 12 PROPOSED CONCRETE PAVEMENT
- 13 PROPOSED ADA STRIPING
- 14 PROPOSED ADA SIGN
- 15 PROPOSED CONCRETE VALLEY PAN
- 16 PROPOSED AIR STAND
- 17 PROPOSED PROPANE CAGE
- 18 PROPOSED DISPENSER ISLAND (TYP. 5 LOCATIONS)
- 19 PROPOSED UNDERGROUND FUEL TANKS
- 20 PROPOSED 208 SF KIOSK
- 21 PROPOSED FUEL CANOPY
- 22 PROPOSED BUILDING INGRESS AND EGRESS LOCATION
- 23 EXISTING DETENTION POND TO REMAIN, MAINTENANCE AND CLEANING TO BE DETERMINED DURING CONSTRUCTION
- 24 EXISTING OUTLET STRUCTURE TO BE REPLACED WITH PROPOSED OUTLET STRUCTURE
- 25 EXISTING CHASE DRAIN
- 26 EXISTING PEDESTRIAN RAMP TO BE BROUGHT TO CURRENT ADA STANDARDS
- 27 EXISTING SIDEWALK TO BE BROUGHT TO CURRENT ADA STANDARDS
- 28 PROPOSED MONUMENT SIGN LOCATION
- 29 PROPOSED TRASH ENCLOSURE DRAIN
- 30 PROPOSED ROOF DRAIN, REFER TO PLUMBING PLANS FOR CONTINUATION IN THE BUILDING
- 31 EXISTING ROOF DRAIN TO REMAIN

NGS BENCHMARK P-453, LOCATED 3.06 KM NORTHWEST OF THE INTERCHANGE OF US 36 AND INTERLOCKEN LOOP/STORAGE TECH DRIVE, IN COLORADO DEPARTMENT OF TRANSPORTATION RIGHT-OF-WAY.

LEGAL DESCRIPTION

LOT 5, CENTENNIAL VALLEY PARCEL L, FILING NO. 1, ACCORDING TO THE PLAT THEREOF RECORDED AT RECEPTION NUMBER 1616847, CITY OF LOUISVILLE, BOULDER COUNTY, COLORADO.

WOKing Scoopers - City Market/CO, Louisville - KSS00142 - Hwy 30 & McGuffin/OCN2-Plan KSS142_SITE PLAN.dwg - Natl Robinson - 4/11/2025

APPENDIX B – LOS Descriptions

Level of Service for Signalized Intersections

Level of service for signalized intersections is defined in terms of delay, which is a measure of driver discomfort and frustration, fuel consumption, and lost travel time. Specifically, level-of-service (LOS) criteria are stated in terms of the average stopped delay per vehicle for a 15-min analysis period. The criteria are given in Exhibit 16-2. Delay may be measured in the field or estimated using procedures presented later in this chapter. Delay is a complex measure and is dependent on a number of variables, including the quality of progression, the cycle length, the green ratio, and the v/c ratio for the lane group in question.

LOS A describes operations with very low delay, up to 10 sec per vehicle. This level of service occurs when progression is extremely favorable and most vehicles arrive during the green phase. Most vehicles do not stop at all. Short cycle lengths may also contribute to low delay.

LOS B describes operations with delay greater than 10 and up to 20 sec per vehicle. This level generally occurs with good progression, short cycle lengths, or both. More vehicles stop than with LOS A, causing higher levels of average delay.

Exhibit 16-2. Level-of-Service Criteria for Signalized Intersections

LEVEL OF SERVICE	STOPPED DELAY PER VEHICLE (SEC)
A	≤ 10.0
B	> 10.0 and ≤ 20.0
C	> 20.0 and ≤ 35.0
D	> 35.0 and ≤ 55.0
E	> 55.0 and ≤ 80.0
F	> 80.0

LOS C describes operations with delay greater than 20 and up to 35 sec per vehicle. These higher delays may result from fair progression, longer cycle lengths, or both. Individual cycle failures may begin to appear at this level. The number of vehicles stopping is significant at this level, though many still pass through the intersection without stopping.

LOS D describes operations with delay greater than 35 and up to 55 sec per vehicle. At level D, the influence of congestion becomes more noticeable. Longer delays may result from some combination of unfavorable progression, long cycle lengths, or high v/c ratios. Many vehicles stop, and the proportion of vehicles not stopping declines. Individual cycle failures are noticeable.

LOS E describes operations with delay greater than 55 and up to 80 sec per vehicle. This level is considered by many agencies to be the limit of acceptable delay. These high delay values generally indicate poor progression, long cycle lengths, and high v/c ratios. Individual cycle failures are frequent occurrences.

LOS F describes operations with delay in excess of 80 sec per vehicle. This level, considered to be unacceptable to most drivers, often occurs with oversaturation, that is, when arrival flow rates exceed the capacity of the intersection. It may also occur at high v/c ratios below 1.0 with many individual cycle failures. Poor progression and long cycle lengths may also be major contributing causes to such delay levels.

Source: Highway Capacity Manual, 2000. Transportation Research Board, National Research Council

Level of Service Criteria for Stop Sign Controlled Intersections

The level of service criteria are given in Table 17-2. As used here, control delay is defined as the total elapsed time from the time a vehicle stops at the end of the queue until the vehicle departs from the stop line; this time includes the time required for the vehicle to travel from the last-in-queue position to the first-in-queue position, including deceleration of vehicles from free-flow speed to the speed of vehicles in queue.

The average total delay for any particular minor movement is a function of the service rate or capacity of the approach and the degree of saturation. . . .

Table 17-2. Level of Service Criteria for TWSC Intersections

LEVEL OF SERVICE	AVERAGE CONTROL DELAY (sec/veh)
A	≤ 10
B	$> 10 \text{ and } \leq 15$
C	$> 15 \text{ and } \leq 25$
D	$> 25 \text{ and } \leq 35$
E	$> 35 \text{ and } \leq 50$
F	> 50

Average total delay less than 10 sec/veh is defined as Level of Service (LOS) A. Follow-up times of less than 5 sec have been measured when there is no conflicting traffic for a minor street movement, so control delays of less than 10 sec/veh are appropriate for low flow conditions. To remain consistent with the AWSC intersection analysis procedure described later in this chapter, a total delay of 50 sec/veh is assumed as the break point between LOS E and F.


The proposed level of service criteria for TWSC intersections are somewhat different from the criteria used in Chapter 16 for signalized intersections. The primary reason for this difference is that drivers expect different levels of performance from different kinds of transportation facilities. The expectation is that a signalized intersection is designed to carry higher traffic volumes than an unsignalized intersection. Additionally, several driver behavior considerations combine to make delays at signalized intersections less onerous than at unsignalized intersections. For example, drivers at signalized intersections are able to relax during the red interval, where drivers on the minor approaches to unsignalized intersections must remain attentive to the task of identifying acceptable gaps and vehicle conflicts. Also, there is often much more variability in the amount of delay experienced by individual drivers at unsignalized than signalized intersections. For these reasons, it is considered that the total delay threshold for any given level of service is less for an unsignalized intersection than for a signalized intersection. . . .

LOS F exists when there are insufficient gaps of suitable size to allow a side street demand to cross safely through a major street traffic stream. This level of service is generally evident from extremely long total delays experienced by side street traffic and by queueing on the minor approaches. The method, however, is based on a constant critical gap size - that is, the critical gap remains constant, no matter how long the side street motorist waits. LOS F may also appear in the form of side street vehicles' selecting smaller-than-usual gaps. In such cases, safety may be a problem and some disruption to the major traffic stream may result. It is important to note that LOS F may not always result in long queues but may result in adjustments to normal gap acceptance behavior. The latter is more difficult to observe on the field than queueing, which is more obvious.


Source: Highway Capacity Manual, 2000. Transportation Research Board, National Research Council

APPENDIX C – Traffic Counts

Century Pl Centennial Pkwy



Date: 1/14/2025
Count Period: 7:00 AM to 9:00 AM
Peak Hour: 8:00 AM to 9:00 AM



	HV%	PHF
EB	2%	0.57
WB	1%	0.81
NB	5%	0.63
SB	0%	0.65
TOTAL	2%	0.88

Peak Hour Count Summaries

Peak Hour Interval Start		Centennial Pkwy				Centennial Pkwy				Century Pl				Century Pl				15-min Total	Rolling Hour Total
		Eastbound				Westbound				Northbound				Southbound					
		UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
8:00 AM		0	0	6	0	3	0	27	18	0	1	7	0	0	3	1	1	67	0
8:15 AM		0	0	5	3	5	2	36	22	0	2	2	1	0	2	1	0	81	0
8:30 AM		0	0	17	1	2	1	30	17	0	0	1	1	0	0	1	0	71	0
8:45 AM		0	0	8	1	1	0	26	21	0	3	2	0	0	1	2	1	66	285
P k Hr	All	0	0	36	5	11	3	119	78	0	6	12	2	0	6	5	2	285	
	HV	0	0	1	0	0	0	1	2	0	1	0	0	0	0	0	0	5	
	HV%	-	-	3%	0%	0%	0%	1%	3%	-	17%	0%	0%	-	0%	0%	0%	2%	

Note: For complete count summary (all intervals), see following pages.

** Heavy Vehicle Classifications include FHWA Classes 4-13.

** Count Summaries include heavy vehicles, but exclude bicycles in overall count.

Interval Start	Heavy Vehicle Totals					Bicycles					Pedestrians (Crossing Leg)				
	EB	WB	NB	SB	Total	EB	WB	NB	SB	Total	E	W	N	S	Total
8:00 AM	0	2	0	0	2	0	1	1	0	2	0	1	0	0	1
8:15 AM	1	0	0	0	1	0	0	0	1	1	1	0	0	0	1
8:30 AM	0	0	0	0	0	1	1	0	0	2	0	0	0	0	0
8:45 AM	0	1	1	0	2	0	0	0	0	0	0	0	0	0	0
Peak Hour	1	3	1	0	5	1	2	1	1	5	1	1	0	0	2

Count Summaries - All Vehicles

Interval Start		Centennial Pkwy				Centennial Pkwy				Century PI				Century PI				15-min Total	Rolling Hour Total
		Eastbound				Westbound				Northbound				Southbound					
		UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
7:00 AM		0	0	1	0	0	0	14	3	0	0	1	0	0	1	0	0	20	0
7:15 AM		0	0	1	0	2	0	15	4	0	0	2	0	0	0	0	0	24	0
7:30 AM		0	0	5	0	6	0	10	2	0	0	0	0	0	5	0	0	28	0
7:45 AM		0	0	6	1	5	0	25	14	0	0	2	1	0	1	0	0	55	127
8:00 AM		0	0	6	0	3	0	27	18	0	1	7	0	0	3	1	1	67	174
8:15 AM		0	0	5	3	5	2	36	22	0	2	2	1	0	2	1	0	81	231
8:30 AM		0	0	17	1	2	1	30	17	0	0	1	1	0	0	1	0	71	274
8:45 AM		0	0	8	1	1	0	26	21	0	3	2	0	0	1	2	1	66	285
Count Total		0	0	49	6	24	3	183	101	0	6	17	3	0	13	5	2	412	
Pk Hr	All	0	0	36	5	11	3	119	78	0	6	12	2	0	6	5	2	285	
	HV	0	0	1	0	0	0	1	2	0	1	0	0	0	0	0	0	5	
	HV%	-	-	3%	0%	0%	0%	1%	3%	-	17%	0%	0%	-	0%	0%	0%	2%	

Interval Start	Heavy Vehicle Totals					Bicycles					Pedestrians (Crossing Leg)				
	EB	WB	NB	SB	Total	EB	WB	NB	SB	Total	E	W	N	S	Total
7:00 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
7:15 AM	1	1	0	0	2	0	0	0	0	0	1	0	0	0	1
7:30 AM	1	0	0	2	3	0	0	0	0	0	0	0	0	0	0
7:45 AM	0	1	1	0	2	2	1	0	0	3	0	0	0	0	0
8:00 AM	0	2	0	0	2	0	1	1	0	2	0	1	0	0	1
8:15 AM	1	0	0	0	1	0	0	0	1	1	1	0	0	0	1
8:30 AM	0	0	0	0	0	1	1	0	0	2	0	0	0	0	0
8:45 AM	0	1	1	0	2	0	0	0	0	0	0	0	0	0	0
Count Total	3	5	2	2	12	3	3	1	1	8	2	1	0	0	3
Peak Hour	1	3	1	0	5	1	2	1	1	5	1	1	0	0	2


Count Summaries - Heavy Vehicles

Interval Start	Centennial Pkwy				Centennial Pkwy				Century PI				Century PI				15-min Total	Rolling Hour Total
	Eastbound				Westbound				Northbound				Southbound					
	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
7:00 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
7:15 AM	0	0	1	0	0	0	1	0	0	0	0	0	0	0	0	0	2	0
7:30 AM	0	0	1	0	0	0	0	0	0	0	0	0	0	2	0	0	3	0
7:45 AM	0	0	0	0	0	0	1	0	0	0	1	0	0	0	0	0	2	7
8:00 AM	0	0	0	0	0	0	0	2	0	0	0	0	0	0	0	0	2	9
8:15 AM	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	1	8
8:30 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	5
8:45 AM	0	0	0	0	0	0	1	0	0	0	1	0	0	0	0	0	2	5
Count Total	0	0	3	0	0	0	3	2	0	1	1	0	0	2	0	0	12	
Pk Hr Heavy	0	0	1	0	0	0	1	2	0	1	0	0	0	0	0	0	5	


Count Summaries - Bikes

Interval Start	Centennial Pkwy				Centennial Pkwy				Century PI				Century PI				15-min Total	Rolling Hour Total
	Eastbound				Westbound				Northbound				Southbound					
	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
7:00 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
7:15 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
7:30 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
7:45 AM	0	0	1	1	0	0	0	1	0	0	0	0	0	0	0	0	3	3
8:00 AM	0	0	0	0	0	1	0	0	0	0	0	1	0	0	0	0	2	5
8:15 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	1	6
8:30 AM	0	1	0	0	0	0	1	0	0	0	0	0	0	0	0	0	2	8
8:45 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	5
Count Total	0	1	1	1	0	1	1	1	0	0	1	0	0	0	1	0	8	
Pk Hr Bike	0	1	0	0	0	1	1	0	0	0	1	0	0	0	1	0	5	

Century Pl Centennial Pkwy



	HV%	PHF
EB	1%	0.82
WB	2%	0.72
NB	0%	0.71
SB	1%	0.76
TOTAL	1%	0.78



Peak Hour Count Summaries

Peak Hour Interval Start		Centennial Pkwy				Centennial Pkwy				Century Pl				Century Pl				15-min Total	Rolling Hour Total
		Eastbound				Westbound				Northbound				Southbound					
		UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
4:30 PM		0	0	36	5	3	0	1	2	0	1	0	1	0	16	2	2	69	0
4:45 PM		0	0	36	4	3	2	5	2	0	2	1	1	0	16	3	0	75	0
5:00 PM		0	0	42	3	6	1	7	1	0	1	2	3	0	21	3	1	91	0
5:15 PM		0	1	20	1	5	2	2	1	0	1	2	2	0	8	2	2	49	284
Pk Hr	All	0	1	134	13	17	5	15	6	0	5	5	7	0	61	10	5	284	
	HV	0	0	1	0	0	0	1	0	0	0	0	0	0	0	0	1	3	
	HV%	-	0%	1%	0%	0%	0%	7%	0%	-	0%	0%	0%	-	0%	0%	20%	1%	

Note: For complete count summary (all intervals), see following pages.

** Heavy Vehicle Classifications include FHWA Classes 4-13.

** Count Summaries include heavy vehicles, but exclude bicycles in overall count.

Interval Start	Heavy Vehicle Totals					Bicycles					Pedestrians (Crossing Leg)				
	EB	WB	NB	SB	Total	EB	WB	NB	SB	Total	E	W	N	S	Total
4:30 PM	0	1	0	0	1	0	1	0	0	1	0	0	0	0	0
4:45 PM	1	0	0	0	1	1	0	0	1	2	0	0	1	0	1
5:00 PM	0	0	0	0	0	0	0	1	0	1	1	0	0	0	1
5:15 PM	0	0	0	1	1	0	0	0	0	0	0	2	0	2	4
Peak Hour	1	1	0	1	3	1	1	1	1	4	1	2	1	2	6

Count Summaries - All Vehicles

Interval Start		Centennial Pkwy				Centennial Pkwy				Century PI				Century PI				15-min Total	Rolling Hour Total
		Eastbound				Westbound				Northbound				Southbound					
		UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
4:00 PM		0	1	25	2	0	3	7	3	0	0	1	2	0	8	0	0	52	0
4:15 PM		0	0	16	1	1	0	4	1	0	0	0	2	0	8	1	0	34	0
4:30 PM		0	0	36	5	3	0	1	2	0	1	0	1	0	16	2	2	69	0
4:45 PM		0	0	36	4	3	2	5	2	0	2	1	1	0	16	3	0	75	230
5:00 PM		0	0	42	3	6	1	7	1	0	1	2	3	0	21	3	1	91	269
5:15 PM		0	1	20	1	5	2	2	1	0	1	2	2	0	8	2	2	49	284
5:30 PM		0	0	15	1	0	4	2	1	0	2	2	3	0	10	2	0	42	257
5:45 PM		0	1	15	1	0	2	0	4	0	1	1	1	0	6	1	0	33	215
Count Total		0	3	205	18	18	14	28	15	0	8	9	15	0	93	14	5	445	
Pk Hr	All	0	1	134	13	17	5	15	6	0	5	5	7	0	61	10	5	284	
	HV	0	0	1	0	0	0	1	0	0	0	0	0	0	0	0	1	3	
	HV%	-	0%	1%	0%	0%	0%	7%	0%	-	0%	0%	0%	-	0%	0%	20%	1%	


Interval Start	Heavy Vehicle Totals					Bicycles					Pedestrians (Crossing Leg)				
	EB	WB	NB	SB	Total	EB	WB	NB	SB	Total	E	W	N	S	Total
4:00 PM	1	0	0	0	1	0	0	0	0	0	0	0	0	0	0
4:15 PM	0	0	0	0	0	0	0	0	0	0	0	0	2	0	2
4:30 PM	0	1	0	0	1	0	1	0	0	1	0	0	0	0	0
4:45 PM	1	0	0	0	1	1	0	0	1	2	0	0	1	0	1
5:00 PM	0	0	0	0	0	0	0	1	0	1	1	0	0	0	1
5:15 PM	0	0	0	1	1	0	0	0	0	0	0	2	0	2	4
5:30 PM	0	0	0	0	0	0	0	0	0	0	1	0	0	0	1
5:45 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Count Total	2	1	0	1	4	1	1	1	1	4	2	2	3	2	9
Peak Hour	1	1	0	1	3	1	1	1	1	4	1	2	1	2	6

Count Summaries - Heavy Vehicles

Interval Start	Centennial Pkwy				Centennial Pkwy				Century PI				Century PI				15-min Total	Rolling Hour Total
	Eastbound				Westbound				Northbound				Southbound					
	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
4:00 PM	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0
4:15 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
4:30 PM	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	1	0
4:45 PM	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	1	3
5:00 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	2
5:15 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	3
5:30 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	2
5:45 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
Count Total	0	0	2	0	0	0	1	0	0	0	0	0	0	0	0	1	4	
Pk Hr Heavy	0	0	1	0	0	0	1	0	0	0	0	0	0	0	0	1	3	

Count Summaries - Bikes

Interval Start	Centennial Pkwy				Centennial Pkwy				Century PI				Century PI				15-min Total	Rolling Hour Total
	Eastbound				Westbound				Northbound				Southbound					
	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
4:00 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
4:15 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
4:30 PM	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	1	0
4:45 PM	0	0	1	0	0	0	0	0	0	0	0	0	0	0	1	0	2	3
5:00 PM	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	1	4
5:15 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	4
5:30 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	3
5:45 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
Count Total	0	0	1	0	0	1	0	0	0	0	0	1	0	0	0	1	0	
Pk Hr Bike	0	0	1	0	0	1	0	0	0	0	0	1	0	0	0	1	0	



Count Summaries - All Vehicles

Interval Start		Centennial Pkwy				Centennial Pkwy				Access Rd				Access Rd				15-min Total	Rolling Hour Total
		Eastbound				Westbound				Northbound				Southbound					
		UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
7:00 AM		0	0	1	1	0	0	15	3	0	4	0	0	0	7	0	1	32	0
7:15 AM		0	0	1	0	0	1	13	7	0	1	0	0	0	11	0	4	38	0
7:30 AM		0	1	10	0	0	1	14	8	0	3	2	7	0	12	1	1	60	0
7:45 AM		1	1	9	0	0	1	36	12	0	4	1	4	0	16	1	3	89	219
8:00 AM		1	1	14	0	0	6	42	10	0	2	0	3	0	19	0	4	102	289
8:15 AM		1	0	17	0	0	3	52	7	0	2	1	7	0	3	0	9	102	353
8:30 AM		0	3	14	1	0	3	43	13	0	5	0	4	0	13	0	3	102	395
8:45 AM		0	1	16	1	0	2	40	9	0	1	2	4	0	14	1	6	97	403
Count Total		3	7	82	3	0	17	255	69	0	22	6	29	0	95	3	31	622	
Pk Hr	All	2	5	61	2	0	14	177	39	0	10	3	18	0	49	1	22	403	
	HV	0	0	1	0	0	0	3	0	0	0	0	0	0	1	0	0	5	
	HV%	0%	0%	2%	0%	-	0%	2%	0%	-	0%	0%	0%	-	2%	0%	0%	1%	


Interval Start	Heavy Vehicle Totals					Bicycles					Pedestrians (Crossing Leg)				
	EB	WB	NB	SB	Total	EB	WB	NB	SB	Total	E	W	N	S	Total
7:00 AM	0	1	0	0	1	0	0	0	0	0	0	0	0	0	0
7:15 AM	1	0	0	0	1	0	0	0	0	0	0	0	0	0	0
7:30 AM	3	0	0	0	3	0	0	1	0	1	0	0	0	0	0
7:45 AM	1	1	1	0	3	1	0	0	1	2	0	0	0	0	0
8:00 AM	0	2	0	0	2	0	1	0	0	1	0	0	1	0	1
8:15 AM	1	0	0	0	1	0	0	0	0	0	0	0	1	0	1
8:30 AM	0	0	0	0	0	0	1	0	0	1	0	1	0	0	1
8:45 AM	0	1	0	1	2	0	0	0	0	0	0	0	0	0	0
Count Total	6	5	1	1	13	1	2	1	1	5	0	1	2	0	3
Peak Hour	1	3	0	1	5	0	2	0	0	2	0	1	2	0	3

Count Summaries - Heavy Vehicles

Interval Start	Centennial Pkwy				Centennial Pkwy				Access Rd				Access Rd				15-min Total	Rolling Hour Total
	Eastbound				Westbound				Northbound				Southbound					
	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
7:00 AM	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	1	0
7:15 AM	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0
7:30 AM	0	0	3	0	0	0	0	0	0	0	0	0	0	0	0	0	3	0
7:45 AM	0	0	1	0	0	0	1	0	0	0	0	1	0	0	0	0	3	8
8:00 AM	0	0	0	0	0	0	2	0	0	0	0	0	0	0	0	0	2	9
8:15 AM	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	1	9
8:30 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	6
8:45 AM	0	0	0	0	0	0	1	0	0	0	0	0	0	1	0	0	2	5
Count Total	0	0	6	0	0	0	5	0	0	0	0	1	0	1	0	0	13	
Pk Hr Heavy	0	0	1	0	0	0	3	0	0	0	0	0	0	1	0	0	5	

Count Summaries - Bikes

Interval Start	Centennial Pkwy				Centennial Pkwy				Access Rd				Access Rd				15-min Total	Rolling Hour Total
	Eastbound				Westbound				Northbound				Southbound					
	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
7:00 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
7:15 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
7:30 AM	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	1
7:45 AM	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	2
8:00 AM	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	1
8:15 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
8:30 AM	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	1
8:45 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Count Total	0	1	0	0	0	0	2	0	0	0	1	0	0	0	0	1	5	
Pk Hr Bike	0	0	0	0	0	0	2	0	0	0	0	0	0	0	0	0	2	



Count Summaries - All Vehicles

Interval Start		Centennial Pkwy				Centennial Pkwy				Access Rd				Access Rd				15-min Total	Rolling Hour Total
		Eastbound				Westbound				Northbound				Southbound					
		UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
4:00 PM		0	0	33	2	0	2	8	7	0	2	0	7	0	5	1	3	70	0
4:15 PM		0	2	31	0	2	4	6	9	0	0	0	10	0	5	1	1	71	0
4:30 PM		0	0	48	7	1	8	6	11	0	2	1	4	0	16	0	0	104	0
4:45 PM		0	0	58	3	0	6	6	2	0	1	1	6	0	10	0	2	95	340
5:00 PM		2	1	68	8	2	6	11	1	0	1	0	8	0	4	0	1	113	383
5:15 PM		0	0	40	2	0	2	9	5	0	1	1	5	0	5	0	1	71	383
5:30 PM		1	0	35	1	0	5	3	6	0	1	1	8	0	4	1	1	67	346
5:45 PM		0	0	21	2	0	3	4	3	0	1	0	9	0	3	1	1	48	299
Count Total		3	3	334	25	5	36	53	44	0	9	4	57	0	52	4	10	639	
Pk Hr	All	2	3	205	18	5	24	29	23	0	4	2	28	0	35	1	4	383	
	HV	0	0	1	0	0	0	1	1	0	0	0	0	0	1	0	0	4	
	HV%	0%	0%	0%	0%	0%	0%	3%	4%	-	0%	0%	0%	-	3%	0%	0%	1%	

Interval Start	Heavy Vehicle Totals					Bicycles					Pedestrians (Crossing Leg)				
	EB	WB	NB	SB	Total	EB	WB	NB	SB	Total	E	W	N	S	Total
4:00 PM	1	0	0	0	1	0	0	0	0	0	0	0	0	0	0
4:15 PM	0	0	0	0	0	0	0	0	0	0	0	0	2	0	2
4:30 PM	0	2	0	0	2	0	1	0	0	1	0	0	0	0	0
4:45 PM	1	0	0	1	2	2	0	0	0	2	0	0	0	0	0
5:00 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
5:15 PM	0	0	0	0	0	0	0	0	0	0	1	0	0	2	3
5:30 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
5:45 PM	0	0	1	0	1	0	0	0	0	0	0	0	0	0	0
Count Total	2	2	1	1	6	2	1	0	0	3	1	0	2	2	5
Peak Hour	1	2	0	1	4	2	1	0	0	3	0	0	2	0	2


Count Summaries - Heavy Vehicles

Interval Start	Centennial Pkwy				Centennial Pkwy				Access Rd				Access Rd				15-min Total	Rolling Hour Total
	Eastbound				Westbound				Northbound				Southbound					
	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
4:00 PM	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0
4:15 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
4:30 PM	0	0	0	0	0	0	1	1	0	0	0	0	0	0	0	0	2	0
4:45 PM	0	0	1	0	0	0	0	0	0	0	0	0	0	1	0	0	2	5
5:00 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	4
5:15 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	4
5:30 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	2
5:45 PM	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	1	1
Count Total	0	0	2	0	0	0	1	1	0	0	0	1	0	1	0	0	6	
Pk Hr Heavy	0	0	1	0	0	0	1	1	0	0	0	0	0	1	0	0	4	


Count Summaries - Bikes

Interval Start	Centennial Pkwy				Centennial Pkwy				Access Rd				Access Rd				15-min Total	Rolling Hour Total
	Eastbound				Westbound				Northbound				Southbound					
	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
4:00 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
4:15 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
4:30 PM	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	1	0
4:45 PM	0	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	2	3
5:00 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	3
5:15 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	3
5:30 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	2
5:45 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Count Total	0	1	1	0	0	0	1	0	0	0	0	0	0	0	0	0	3	
Pk Hr Bike	0	1	1	0	0	0	1	0	0	0	0	0	0	0	0	0	3	

McCaslin Blvd Centennial Pkwy



Date: 1/14/2025
Count Period: 7:00 AM to 9:00 AM
Peak Hour: 8:00 AM to 9:00 AM



	HV%	PHF
EB	2%	0.83
WB	2%	0.85
NB	4%	0.94
SB	3%	0.90
TOTAL	3%	0.97

Peak Hour Count Summaries

Peak Hour Interval Start		Centennial Pkwy				W Cherry St				McCaslin Blvd				McCaslin Blvd				15-min Total	Rolling Hour Total
		Eastbound				Westbound				Northbound				Southbound					
		UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
8:00 AM		0	17	9	15	0	75	10	24	0	39	195	18	0	14	144	7	567	0
8:15 AM		0	10	3	13	0	43	9	22	0	46	221	36	0	13	158	9	583	0
8:30 AM		0	12	6	14	0	52	5	39	0	48	207	27	0	15	127	6	558	0
8:45 AM		0	16	7	14	0	65	5	21	0	42	229	33	1	20	132	4	589	2,297
Pk Hr	All	0	55	25	56	0	235	29	106	0	175	852	114	1	62	561	26	2,297	
	HV	0	1	0	2	0	5	0	3	0	3	37	5	0	1	21	0	78	
	HV%	-	2%	0%	4%	-	2%	0%	3%	-	2%	4%	4%	0%	2%	4%	0%	3%	

Note: For complete count summary (all intervals), see following pages.

** Heavy Vehicle Classifications include FHWA Classes 4-13.

** Count Summaries include heavy vehicles, but exclude bicycles in overall count.

Interval Start	Heavy Vehicle Totals					Bicycles					Pedestrians (Crossing Leg)				
	EB	WB	NB	SB	Total	EB	WB	NB	SB	Total	E	W	N	S	Total
8:00 AM	0	2	14	3	19	0	1	0	0	1	0	1	2	0	3
8:15 AM	1	3	9	7	20	0	0	0	0	0	0	0	0	0	0
8:30 AM	0	1	13	6	20	0	0	0	0	0	0	0	1	0	1
8:45 AM	2	2	9	6	19	0	0	0	0	0	0	1	0	0	1
Peak Hour	3	8	45	22	78	0	1	0	0	1	0	2	3	0	5

Count Summaries - All Vehicles

Interval Start		Centennial Pkwy				W Cherry St				McCaslin Blvd				McCaslin Blvd				15-min Total	Rolling Hour Total
		Eastbound				Westbound				Northbound				Southbound					
		UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
7:00 AM		0	2	0	2	0	42	1	17	0	14	88	11	0	5	67	1	250	0
7:15 AM		0	3	1	5	0	50	5	21	0	14	129	25	0	6	91	4	354	0
7:30 AM		0	7	5	14	0	40	6	26	0	13	177	24	0	11	102	4	429	0
7:45 AM		0	10	3	16	0	49	12	25	0	31	211	23	0	3	145	6	534	1,567
8:00 AM		0	17	9	15	0	75	10	24	0	39	195	18	0	14	144	7	567	1,884
8:15 AM		0	10	3	13	0	43	9	22	0	46	221	36	0	13	158	9	583	2,113
8:30 AM		0	12	6	14	0	52	5	39	0	48	207	27	0	15	127	6	558	2,242
8:45 AM		0	16	7	14	0	65	5	21	0	42	229	33	1	20	132	4	589	2,297
Count Total		0	77	34	93	0	416	53	195	0	247	1,457	197	1	87	966	41	3,864	
Pk Hr	All	0	55	25	56	0	235	29	106	0	175	852	114	1	62	561	26	2,297	
	HV	0	1	0	2	0	5	0	3	0	3	37	5	0	1	21	0	78	
	HV%	-	2%	0%	4%	-	2%	0%	3%	-	2%	4%	4%	0%	2%	4%	0%	3%	

Interval Start	Heavy Vehicle Totals					Bicycles					Pedestrians (Crossing Leg)				
	EB	WB	NB	SB	Total	EB	WB	NB	SB	Total	E	W	N	S	Total
7:00 AM	0	1	6	2	9	0	0	0	1	1	0	2	1	0	3
7:15 AM	0	2	4	2	8	0	0	0	0	0	0	0	0	0	0
7:30 AM	4	0	5	4	13	0	0	0	0	0	0	1	2	0	3
7:45 AM	1	1	13	4	19	0	0	0	0	0	2	0	2	0	4
8:00 AM	0	2	14	3	19	0	1	0	0	1	0	1	2	0	3
8:15 AM	1	3	9	7	20	0	0	0	0	0	0	0	0	0	0
8:30 AM	0	1	13	6	20	0	0	0	0	0	0	0	1	0	1
8:45 AM	2	2	9	6	19	0	0	0	0	0	0	1	0	0	1
Count Total	8	12	73	34	127	0	1	0	1	2	2	5	8	0	15
Peak Hour	3	8	45	22	78	0	1	0	0	1	0	2	3	0	5


Count Summaries - Heavy Vehicles

Interval Start	Centennial Pkwy				W Cherry St				McCaslin Blvd				McCaslin Blvd				15-min Total	Rolling Hour Total	
	Eastbound				Westbound				Northbound				Southbound						
	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT			
7:00 AM	0	0	0	0	0	1	0	0	0	0	0	6	0	0	1	1	0	9	0
7:15 AM	0	0	0	0	0	2	0	0	0	0	1	3	0	0	0	2	0	8	0
7:30 AM	0	0	1	3	0	0	0	0	0	0	0	5	0	0	0	4	0	13	0
7:45 AM	0	1	0	0	0	1	0	0	0	0	1	10	2	0	0	4	0	19	49
8:00 AM	0	0	0	0	0	2	0	0	0	0	2	12	0	0	0	3	0	19	59
8:15 AM	0	0	0	1	0	0	0	3	0	0	0	7	2	0	0	7	0	20	71
8:30 AM	0	0	0	0	0	1	0	0	0	0	0	11	2	0	0	6	0	20	78
8:45 AM	0	1	0	1	0	2	0	0	0	0	1	7	1	0	1	5	0	19	78
Count Total	0	2	1	5	0	9	0	3	0	0	5	61	7	0	2	32	0	127	
Pk Hr Heavy	0	1	0	2	0	5	0	3	0	0	3	37	5	0	1	21	0	78	


Count Summaries - Bikes

Interval Start	Centennial Pkwy				W Cherry St				McCaslin Blvd				McCaslin Blvd				15-min Total	Rolling Hour Total	
	Eastbound				Westbound				Northbound				Southbound						
	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT			
7:00 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	1	0
7:15 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
7:30 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
7:45 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
8:00 AM	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	1	1
8:15 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
8:30 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
8:45 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
Count Total	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	1	0	2	
Pk Hr Bike	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	1	

McCaslin Blvd Centennial Pkwy



Date: 1/14/2025
Count Period: 4:00 PM to 6:00 PM
Peak Hour: 4:30 PM to 5:30 PM



	HV%	PHF
EB	1%	0.89
WB	0%	0.93
NB	1%	0.98
SB	1%	0.95
TOTAL	1%	0.97

Peak Hour Count Summaries

Peak Hour Interval Start		Centennial Pkwy				W Cherry St				McCaslin Blvd				McCaslin Blvd				15-min Total	Rolling Hour Total
		Eastbound				Westbound				Northbound				Southbound					
		UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
4:30 PM		0	8	10	49	0	56	2	27	0	11	212	34	0	35	270	11	725	0
4:45 PM		0	16	14	44	0	65	4	27	0	6	198	51	0	25	277	8	735	0
5:00 PM		0	8	8	61	0	62	5	24	0	6	189	43	0	25	266	8	705	0
5:15 PM		0	9	12	36	1	63	5	17	0	5	198	55	0	19	256	6	682	2,847
P k Hr	All	0	41	44	190	1	246	16	95	0	28	797	183	0	104	1,069	33	2,847	
	HV	0	0	0	2	0	0	0	0	0	2	7	1	0	0	9	0	21	
	HV%	-	0%	0%	1%	0%	0%	0%	0%	-	7%	1%	1%	-	0%	1%	0%	1%	

Note: For complete count summary (all intervals), see following pages.

** Heavy Vehicle Classifications include FHWA Classes 4-13.

** Count Summaries include heavy vehicles, but exclude bicycles in overall count.

Interval Start	Heavy Vehicle Totals					Bicycles					Pedestrians (Crossing Leg)				
	EB	WB	NB	SB	Total	EB	WB	NB	SB	Total	E	W	N	S	Total
4:30 PM	0	0	5	5	10	0	0	0	1	1	1	0	0	0	1
4:45 PM	1	0	1	2	4	0	0	1	0	1	0	0	0	0	0
5:00 PM	1	0	3	2	6	0	0	0	0	0	1	2	0	0	3
5:15 PM	0	0	1	0	1	0	0	0	0	0	1	2	0	0	3
Peak Hour	2	0	10	9	21	0	0	1	1	2	3	4	0	0	7


Count Summaries - All Vehicles

Interval Start		Centennial Pkwy				W Cherry St				McCaslin Blvd				McCaslin Blvd				15-min Total	Rolling Hour Total
		Eastbound				Westbound				Northbound				Southbound					
		UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
4:00 PM		0	2	6	32	0	47	4	18	0	8	208	49	0	17	240	5	636	0
4:15 PM		0	10	11	28	0	64	4	22	0	8	184	43	0	20	251	7	652	0
4:30 PM		0	8	10	49	0	56	2	27	0	11	212	34	0	35	270	11	725	0
4:45 PM		0	16	14	44	0	65	4	27	0	6	198	51	0	25	277	8	735	2,748
5:00 PM		0	8	8	61	0	62	5	24	0	6	189	43	0	25	266	8	705	2,817
5:15 PM		0	9	12	36	1	63	5	17	0	5	198	55	0	19	256	6	682	2,847
5:30 PM		0	10	10	28	0	39	2	24	0	3	190	59	0	29	254	10	658	2,780
5:45 PM		0	9	7	22	0	45	2	17	0	4	182	48	0	22	224	4	586	2,631
Count Total		0	72	78	300	1	441	28	176	0	51	1,561	382	0	192	2,038	59	5,379	
Pk Hr	All	0	41	44	190	1	246	16	95	0	28	797	183	0	104	1,069	33	2,847	
	HV	0	0	0	2	0	0	0	0	0	2	7	1	0	0	9	0	21	
	HV%	-	0%	0%	1%	0%	0%	0%	0%	-	7%	1%	1%	-	0%	1%	0%	1%	

Interval Start	Heavy Vehicle Totals					Bicycles					Pedestrians (Crossing Leg)				
	EB	WB	NB	SB	Total	EB	WB	NB	SB	Total	E	W	N	S	Total
4:00 PM	1	0	2	5	8	0	0	0	0	0	0	1	0	0	1
4:15 PM	0	0	0	4	4	0	0	0	0	0	0	0	0	0	0
4:30 PM	0	0	5	5	10	0	0	0	1	1	1	0	0	0	1
4:45 PM	1	0	1	2	4	0	0	1	0	1	0	0	0	0	0
5:00 PM	1	0	3	2	6	0	0	0	0	0	1	2	0	0	3
5:15 PM	0	0	1	0	1	0	0	0	0	0	1	2	0	0	3
5:30 PM	0	0	1	3	4	1	0	0	0	1	1	1	0	0	2
5:45 PM	1	0	0	3	4	0	0	0	0	0	1	0	0	0	1
Count Total	4	0	13	24	41	1	0	1	1	3	5	6	0	0	11
Peak Hour	2	0	10	9	21	0	0	1	1	2	3	4	0	0	7

Count Summaries - Heavy Vehicles																		
Interval Start	Centennial Pkwy				W Cherry St				McCaslin Blvd				McCaslin Blvd				15-min Total	Rolling Hour Total
	Eastbound				Westbound				Northbound				Southbound					
	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
4:00 PM	0	0	0	1	0	0	0	0	0	0	2	0	0	0	5	0	8	0
4:15 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	4	0	4	0
4:30 PM	0	0	0	0	0	0	0	0	0	2	3	0	0	0	5	0	10	0
4:45 PM	0	0	0	1	0	0	0	0	0	0	1	0	0	0	2	0	4	26
5:00 PM	0	0	0	1	0	0	0	0	0	0	2	1	0	0	2	0	6	24
5:15 PM	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	1	21
5:30 PM	0	0	0	0	0	0	0	0	0	0	1	0	0	0	3	0	4	15
5:45 PM	0	0	0	1	0	0	0	0	0	0	0	0	0	0	3	0	4	15
Count Total	0	0	0	4	0	0	0	0	0	2	10	1	0	0	24	0	41	
Pk Hr Heavy	0	0	0	2	0	0	0	0	0	2	7	1	0	0	9	0	21	

Count Summaries - Bikes																		
Interval Start	Centennial Pkwy				W Cherry St				McCaslin Blvd				McCaslin Blvd				15-min Total	Rolling Hour Total
	Eastbound				Westbound				Northbound				Southbound					
	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
4:00 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
4:15 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
4:30 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	0
4:45 PM	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	1	2
5:00 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	2
5:15 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	2
5:30 PM	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	2
5:45 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
Count Total	0	1	0	0	0	0	0	0	0	0	0	1	0	0	0	1	3	
Pk Hr Bike	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	1	2	



Count Summaries - All Vehicles

Interval Start		Access Rd				Access Rd				McCaslin Blvd				McCaslin Blvd				15-min Total	Rolling Hour Total
		Eastbound				Westbound				Northbound				Southbound					
		UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
7:00 AM		0	0	0	1	0	0	0	13	1	7	103	5	0	2	103	1	236	0
7:15 AM		0	0	0	3	0	0	0	11	0	4	156	11	0	6	141	0	332	0
7:30 AM		0	0	0	2	0	0	0	8	2	5	206	5	0	1	151	3	383	0
7:45 AM		0	0	0	7	0	0	0	11	0	10	257	16	0	7	199	0	507	1,458
8:00 AM		0	0	0	5	0	0	0	12	1	6	232	11	0	6	231	8	512	1,734
8:15 AM		0	0	0	2	0	0	0	17	2	14	289	17	0	9	205	3	558	1,960
8:30 AM		0	0	0	7	0	0	0	20	0	4	258	21	0	13	172	5	500	2,077
8:45 AM		0	0	0	5	0	0	0	16	2	6	293	10	0	11	187	9	539	2,109
Count Total		0	0	0	32	0	0	0	108	8	56	1,794	96	0	55	1,389	29	3,567	
Pk Hr	All	0	0	0	19	0	0	0	65	5	30	1,072	59	0	39	795	25	2,109	
	HV	0	0	0	0	0	0	0	0	1	0	44	2	0	0	29	0	76	
	HV%	-	-	-	0%	-	-	-	0%	20%	0%	4%	3%	-	0%	4%	0%	4%	


Interval Start	Heavy Vehicle Totals					Bicycles					Pedestrians (Crossing Leg)				
	EB	WB	NB	SB	Total	EB	WB	NB	SB	Total	E	W	N	S	Total
7:00 AM	0	1	7	2	10	0	0	0	0	0	0	1	0	2	3
7:15 AM	0	0	5	4	9	0	0	1	0	1	0	0	0	0	0
7:30 AM	0	0	7	7	14	0	0	0	0	0	0	1	0	0	1
7:45 AM	0	1	12	4	17	0	0	0	0	0	0	1	0	0	1
8:00 AM	0	0	11	7	18	0	0	0	0	0	0	1	0	0	1
8:15 AM	0	0	13	8	21	0	0	0	0	0	0	0	0	0	0
8:30 AM	0	0	12	8	20	0	0	0	0	0	0	0	0	0	0
8:45 AM	0	0	11	6	17	0	0	0	0	0	0	0	0	0	0
Count Total	0	2	78	46	126	0	0	1	0	1	0	4	0	2	6
Peak Hour	0	0	47	29	76	0	0	0	0	0	0	1	0	0	1

Count Summaries - Heavy Vehicles

Interval Start	Access Rd				Access Rd				McCaslin Blvd				McCaslin Blvd				15-min Total	Rolling Hour Total
	Eastbound				Westbound				Northbound				Southbound					
	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
7:00 AM	0	0	0	0	0	0	0	1	0	0	7	0	0	0	2	0	10	0
7:15 AM	0	0	0	0	0	0	0	0	0	0	3	2	0	0	4	0	9	0
7:30 AM	0	0	0	0	0	0	0	0	1	1	5	0	0	1	6	0	14	0
7:45 AM	0	0	0	0	0	0	0	1	0	0	12	0	0	0	4	0	17	50
8:00 AM	0	0	0	0	0	0	0	0	0	0	11	0	0	0	7	0	18	58
8:15 AM	0	0	0	0	0	0	0	0	0	0	12	1	0	0	8	0	21	70
8:30 AM	0	0	0	0	0	0	0	0	0	0	11	1	0	0	8	0	20	76
8:45 AM	0	0	0	0	0	0	0	0	1	0	10	0	0	0	6	0	17	76
Count Total	0	0	0	0	0	0	0	2	2	1	71	4	0	1	45	0	126	
Pk Hr Heavy	0	0	0	0	0	0	0	0	1	0	44	2	0	0	29	0	76	

Count Summaries - Bikes

Interval Start	Access Rd				Access Rd				McCaslin Blvd				McCaslin Blvd				15-min Total	Rolling Hour Total
	Eastbound				Westbound				Northbound				Southbound					
	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
7:00 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
7:15 AM	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	1	0
7:30 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
7:45 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
8:00 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
8:15 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
8:30 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
8:45 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Count Total	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	1	
Pk Hr Bike	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	



Count Summaries - All Vehicles																			
Interval Start		Access Rd				Access Rd				McCaslin Blvd				McCaslin Blvd				15-min Total	Rolling Hour Total
		Eastbound				Westbound				Northbound				Southbound					
		UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
4:00 PM		0	0	0	13	0	0	0	27	1	2	232	24	0	7	296	12	614	0
4:15 PM		0	0	0	13	0	0	0	24	0	5	210	17	0	14	331	10	624	0
4:30 PM		0	0	0	6	0	0	0	21	0	3	238	23	0	16	358	6	671	0
4:45 PM		0	0	0	10	0	0	0	15	0	5	249	10	0	13	358	11	671	2,580
5:00 PM		0	0	0	11	0	0	0	12	2	4	231	9	0	14	381	6	670	2,636
5:15 PM		0	0	0	8	0	0	0	11	0	3	257	7	1	10	333	5	635	2,647
5:30 PM		0	0	0	10	0	0	0	21	1	2	222	19	0	16	288	9	588	2,564
5:45 PM		0	0	0	19	0	0	0	15	2	4	210	10	0	14	266	6	546	2,439
Count Total		0	0	0	90	0	0	0	146	6	28	1,849	119	1	104	2,611	65	5,019	
Pk Hr	All	0	0	0	35	0	0	0	59	2	15	975	49	1	53	1,430	28	2,647	
	HV	0	0	0	0	0	0	0	0	0	0	11	0	0	0	11	0	22	
	HV%	-	-	-	0%	-	-	-	0%	0%	0%	1%	0%	0%	0%	1%	0%	1%	

Interval Start	Heavy Vehicle Totals					Bicycles					Pedestrians (Crossing Leg)				
	EB	WB	NB	SB	Total	EB	WB	NB	SB	Total	E	W	N	S	Total
4:00 PM	0	0	1	6	7	0	0	0	0	0	0	0	0	0	0
4:15 PM	0	0	0	4	4	0	0	0	0	0	0	0	0	0	0
4:30 PM	0	0	6	5	11	0	0	0	0	0	0	0	0	0	0
4:45 PM	0	0	1	3	4	0	0	1	0	1	0	0	0	0	0
5:00 PM	0	0	3	2	5	0	1	0	0	1	0	1	0	0	1
5:15 PM	0	0	1	1	2	0	0	0	0	0	0	3	0	0	3
5:30 PM	0	0	1	3	4	0	0	0	0	0	0	0	0	0	0
5:45 PM	0	0	0	4	4	0	0	0	0	0	0	0	0	0	0
Count Total	0	0	13	28	41	0	1	1	0	2	0	4	0	0	4
Peak Hour	0	0	11	11	22	0	1	1	0	2	0	4	0	0	4


Count Summaries - Heavy Vehicles

Interval Start	Access Rd				Access Rd				McCaslin Blvd				McCaslin Blvd				15-min Total	Rolling Hour Total
	Eastbound				Westbound				Northbound				Southbound					
	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
4:00 PM	0	0	0	0	0	0	0	0	0	0	1	0	0	0	6	0	7	0
4:15 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	1	3	0	4	0
4:30 PM	0	0	0	0	0	0	0	0	0	0	6	0	0	0	5	0	11	0
4:45 PM	0	0	0	0	0	0	0	0	0	0	1	0	0	0	3	0	4	26
5:00 PM	0	0	0	0	0	0	0	0	0	0	3	0	0	0	2	0	5	24
5:15 PM	0	0	0	0	0	0	0	0	0	0	1	0	0	0	1	0	2	22
5:30 PM	0	0	0	0	0	0	0	0	0	0	1	0	0	0	3	0	4	15
5:45 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	4	0	4	15
Count Total	0	0	0	0	0	0	0	0	0	0	13	0	0	1	27	0	41	
Pk Hr Heavy	0	0	0	0	0	0	0	0	0	0	11	0	0	0	11	0	22	


Count Summaries - Bikes

Interval Start	Access Rd				Access Rd				McCaslin Blvd				McCaslin Blvd				15-min Total	Rolling Hour Total
	Eastbound				Westbound				Northbound				Southbound					
	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
4:00 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
4:15 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
4:30 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
4:45 PM	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	1
5:00 PM	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	2
5:15 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	2
5:30 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	2
5:45 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
Count Total	0	0	0	0	0	0	1	0	0	0	1	0	0	0	0	0	2	
Pk Hr Bike	0	0	0	0	0	0	1	0	0	0	1	0	0	0	0	0	2	

McCaslin Blvd Dillon Rd



Date: 1/14/2025
Count Period: 7:00 AM to 9:00 AM
Peak Hour: 7:45 AM to 8:45 AM



	HV%	PHF
EB	8%	0.69
WB	4%	0.94
NB	3%	0.94
SB	4%	0.85
TOTAL	4%	0.96

Peak Hour Count Summaries

Peak Hour Interval Start		Dillon Rd				Dillon Rd				McCaslin Blvd				McCaslin Blvd				15-min Total	Rolling Hour Total
		Eastbound				Westbound				Northbound				Southbound					
		UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
7:45 AM		0	2	1	13	0	129	11	52	1	27	220	114	0	32	160	9	771	0
8:00 AM		0	3	6	6	0	104	17	47	0	43	219	121	0	52	185	7	810	0
8:15 AM		0	10	4	21	1	110	10	79	2	44	219	92	1	45	157	11	806	0
8:30 AM		0	11	6	14	0	105	18	72	3	36	207	87	0	26	135	7	727	3,114
Pk Hr	All	0	26	17	54	1	448	56	250	6	150	865	414	1	155	637	34	3,114	
	HV	0	1	2	5	0	15	3	11	0	5	37	8	0	3	24	2	116	
	HV%	-	4%	12%	9%	0%	3%	5%	4%	0%	3%	4%	2%	0%	2%	4%	6%	4%	

Note: For complete count summary (all intervals), see following pages.

** Heavy Vehicle Classifications include FHWA Classes 4-13.

** Count Summaries include heavy vehicles, but exclude bicycles in overall count.

Interval Start	Heavy Vehicle Totals					Bicycles					Pedestrians (Crossing Leg)				
	EB	WB	NB	SB	Total	EB	WB	NB	SB	Total	E	W	N	S	Total
7:45 AM	1	10	15	6	32	0	0	0	0	0	1	0	1	1	3
8:00 AM	1	4	14	5	24	0	0	0	0	0	0	3	0	1	4
8:15 AM	3	6	10	12	31	0	0	0	0	0	0	0	0	0	0
8:30 AM	3	9	11	6	29	0	0	0	0	0	0	0	0	0	0
Peak Hour	8	29	50	29	116	0	0	0	0	0	1	3	1	2	7

Count Summaries - All Vehicles

Interval Start		Dillon Rd				Dillon Rd				McCaslin Blvd				McCaslin Blvd				15-min Total	Rolling Hour Total
		Eastbound				Westbound				Northbound				Southbound					
		UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
7:00 AM		0	2	3	5	0	43	3	21	0	8	106	64	0	10	105	7	377	0
7:15 AM		0	3	3	4	0	64	13	28	0	18	125	64	0	12	108	9	451	0
7:30 AM		0	4	2	15	0	91	12	37	0	22	188	79	0	22	137	6	615	0
7:45 AM		0	2	1	13	0	129	11	52	1	27	220	114	0	32	160	9	771	2,214
8:00 AM		0	3	6	6	0	104	17	47	0	43	219	121	0	52	185	7	810	2,647
8:15 AM		0	10	4	21	1	110	10	79	2	44	219	92	1	45	157	11	806	3,002
8:30 AM		0	11	6	14	0	105	18	72	3	36	207	87	0	26	135	7	727	3,114
8:45 AM		0	13	3	22	0	118	10	62	0	24	226	97	0	16	158	10	759	3,102
Count Total		0	48	28	100	1	764	94	398	6	222	1,510	718	1	215	1,145	66	5,316	
Pk Hr	All	0	26	17	54	1	448	56	250	6	150	865	414	1	155	637	34	3,114	
	HV	0	1	2	5	0	15	3	11	0	5	37	8	0	3	24	2	116	
	HV%	-	4%	12%	9%	0%	3%	5%	4%	0%	3%	4%	2%	0%	2%	4%	6%	4%	

Interval Start	Heavy Vehicle Totals					Bicycles					Pedestrians (Crossing Leg)				
	EB	WB	NB	SB	Total	EB	WB	NB	SB	Total	E	W	N	S	Total
7:00 AM	0	1	8	1	10	0	0	0	0	0	0	0	0	0	0
7:15 AM	0	5	7	6	18	0	0	0	0	0	0	0	0	0	0
7:30 AM	0	2	6	6	14	0	0	0	0	0	1	1	0	0	2
7:45 AM	1	10	15	6	32	0	0	0	0	0	1	0	1	1	3
8:00 AM	1	4	14	5	24	0	0	0	0	0	0	3	0	1	4
8:15 AM	3	6	10	12	31	0	0	0	0	0	0	0	0	0	0
8:30 AM	3	9	11	6	29	0	0	0	0	0	0	0	0	0	0
8:45 AM	2	4	9	5	20	0	0	0	0	0	0	0	1	0	1
Count Total	10	41	80	47	178	0	0	0	0	0	2	4	2	2	10
Peak Hour	8	29	50	29	116	0	0	0	0	0	1	3	1	2	7


Count Summaries - Heavy Vehicles

Interval Start	Dillon Rd				Dillon Rd				McCaslin Blvd				McCaslin Blvd				15-min Total	Rolling Hour Total
	Eastbound				Westbound				Northbound				Southbound					
	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
7:00 AM	0	0	0	0	0	0	0	1	0	0	6	2	0	0	1	0	10	0
7:15 AM	0	0	0	0	0	3	1	1	0	1	4	2	0	1	5	0	18	0
7:30 AM	0	0	0	0	0	0	1	1	0	0	5	1	0	0	6	0	14	0
7:45 AM	0	0	0	1	0	6	0	4	0	2	9	4	0	0	6	0	32	74
8:00 AM	0	0	1	0	0	2	1	1	0	1	10	3	0	2	3	0	24	88
8:15 AM	0	0	0	3	0	2	1	3	0	1	9	0	0	1	9	2	31	101
8:30 AM	0	1	1	1	0	5	1	3	0	1	9	1	0	0	6	0	29	116
8:45 AM	0	1	0	1	0	3	0	1	0	0	8	1	0	2	3	0	20	104
Count Total	0	2	2	6	0	21	5	15	0	6	60	14	0	6	39	2	178	
Pk Hr Heavy	0	1	2	5	0	15	3	11	0	5	37	8	0	3	24	2	116	


Count Summaries - Bikes

Interval Start	Dillon Rd				Dillon Rd				McCaslin Blvd				McCaslin Blvd				15-min Total	Rolling Hour Total
	Eastbound				Westbound				Northbound				Southbound					
	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
7:00 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
7:15 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
7:30 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
7:45 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
8:00 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
8:15 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
8:30 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
8:45 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Count Total	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
Pk Hr Bike	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	

McCaslin Blvd Dillon Rd



Date: 1/14/2025
Count Period: 4:00 PM to 6:00 PM
Peak Hour: 4:30 PM to 5:30 PM



	HV%	PHF
EB	1%	0.81
WB	1%	0.98
NB	1%	0.98
SB	1%	0.96
TOTAL	1%	0.98

Peak Hour Count Summaries

Peak Hour Interval Start		Dillon Rd				Dillon Rd				McCaslin Blvd				McCaslin Blvd				15-min Total	Rolling Hour Total
		Eastbound				Westbound				Northbound				Southbound					
		UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
4:30 PM		0	14	12	31	0	143	13	30	0	25	216	123	0	56	285	15	963	0
4:45 PM		0	9	24	38	0	124	17	34	0	23	232	106	0	50	329	5	991	0
5:00 PM		0	21	26	42	0	144	21	21	2	33	188	117	0	66	304	13	998	0
5:15 PM		0	16	12	43	0	137	13	37	0	31	230	104	0	42	286	18	969	3,921
Pk Hr	All	0	60	74	154	0	548	64	122	2	112	866	450	0	214	1,204	51	3,921	
	HV	0	0	2	0	0	4	0	4	0	0	5	4	0	0	9	1	29	
	HV%	-	0%	3%	0%	-	1%	0%	3%	0%	0%	1%	1%	-	0%	1%	2%	1%	

Note: For complete count summary (all intervals), see following pages.

** Heavy Vehicle Classifications include FHWA Classes 4-13.

** Count Summaries include heavy vehicles, but exclude bicycles in overall count.

Interval Start	Heavy Vehicle Totals					Bicycles					Pedestrians (Crossing Leg)				
	EB	WB	NB	SB	Total	EB	WB	NB	SB	Total	E	W	N	S	Total
4:30 PM	0	4	5	5	14	0	0	0	0	0	1	0	0	2	3
4:45 PM	1	0	1	3	5	1	0	0	0	1	1	0	0	1	2
5:00 PM	1	3	3	2	9	0	0	0	0	0	0	1	1	1	3
5:15 PM	0	1	0	0	1	0	0	0	0	0	2	4	1	3	10
Peak Hour	2	8	9	10	29	1	0	0	0	1	4	5	2	7	18

Count Summaries - All Vehicles																			
Interval Start		Dillon Rd				Dillon Rd				McCaslin Blvd				McCaslin Blvd				15-min Total	Rolling Hour Total
		Eastbound				Westbound				Northbound				Southbound					
		UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
4:00 PM		0	18	24	38	1	145	16	53	2	25	172	128	0	63	237	10	932	0
4:15 PM		1	8	9	28	0	113	17	30	2	16	217	107	0	38	291	14	891	0
4:30 PM		0	14	12	31	0	143	13	30	0	25	216	123	0	56	285	15	963	0
4:45 PM		0	9	24	38	0	124	17	34	0	23	232	106	0	50	329	5	991	3,777
5:00 PM		0	21	26	42	0	144	21	21	2	33	188	117	0	66	304	13	998	3,843
5:15 PM		0	16	12	43	0	137	13	37	0	31	230	104	0	42	286	18	969	3,921
5:30 PM		0	15	18	30	0	128	9	31	1	24	183	127	0	54	226	11	857	3,815
5:45 PM		0	9	6	36	0	121	13	23	0	29	198	88	0	40	232	24	819	3,643
Count Total		1	110	131	286	1	1,055	119	259	7	206	1,636	900	0	409	2,190	110	7,420	
Pk Hr	All	0	60	74	154	0	548	64	122	2	112	866	450	0	214	1,204	51	3,921	
	HV	0	0	2	0	0	4	0	4	0	0	5	4	0	0	9	1	29	
	HV%	-	0%	3%	0%	-	1%	0%	3%	0%	0%	1%	1%	-	0%	1%	2%	1%	


Interval Start	Heavy Vehicle Totals					Bicycles					Pedestrians (Crossing Leg)				
	EB	WB	NB	SB	Total	EB	WB	NB	SB	Total	E	W	N	S	Total
4:00 PM	1	3	4	6	14	0	0	0	0	0	0	1	0	0	1
4:15 PM	0	2	2	3	7	0	0	0	0	0	2	0	1	2	5
4:30 PM	0	4	5	5	14	0	0	0	0	0	1	0	0	2	3
4:45 PM	1	0	1	3	5	1	0	0	0	1	1	0	0	1	2
5:00 PM	1	3	3	2	9	0	0	0	0	0	0	1	1	1	3
5:15 PM	0	1	0	0	1	0	0	0	0	0	2	4	1	3	10
5:30 PM	0	1	3	2	6	0	0	0	1	1	0	1	3	1	5
5:45 PM	0	0	2	6	8	0	0	0	0	0	0	0	0	1	1
Count Total	3	14	20	27	64	1	0	0	1	2	6	7	6	11	30
Peak Hour	2	8	9	10	29	1	0	0	0	1	4	5	2	7	18

Count Summaries - Heavy Vehicles

Interval Start	Dillon Rd				Dillon Rd				McCaslin Blvd				McCaslin Blvd				15-min Total	Rolling Hour Total
	Eastbound				Westbound				Northbound				Southbound					
	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
4:00 PM	0	0	0	1	0	2	0	1	0	0	0	4	0	0	6	0	14	0
4:15 PM	0	0	0	0	0	2	0	0	0	0	1	1	0	0	3	0	7	0
4:30 PM	0	0	0	0	0	1	0	3	0	0	2	3	0	0	4	1	14	0
4:45 PM	0	0	1	0	0	0	0	0	0	0	1	0	0	0	3	0	5	40
5:00 PM	0	0	1	0	0	2	0	1	0	0	2	1	0	0	2	0	9	35
5:15 PM	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	1	29
5:30 PM	0	0	0	0	0	0	1	0	0	0	2	1	0	0	2	0	6	21
5:45 PM	0	0	0	0	0	0	0	0	0	0	0	2	0	0	6	0	8	24
Count Total	0	0	2	1	0	8	1	5	0	0	8	12	0	0	26	1	64	
Pk Hr Heavy	0	0	2	0	0	4	0	4	0	0	5	4	0	0	9	1	29	

Count Summaries - Bikes

Interval Start	Dillon Rd				Dillon Rd				McCaslin Blvd				McCaslin Blvd				15-min Total	Rolling Hour Total
	Eastbound				Westbound				Northbound				Southbound					
	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
4:00 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
4:15 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
4:30 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
4:45 PM	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1
5:00 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
5:15 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
5:30 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	2
5:45 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
Count Total	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	1	2	
Pk Hr Bike	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	



Count Summaries - All Vehicles																			
Interval Start		Dillon Rd				Dillon Rd				Access Rd				Access Rd				15-min Total	Rolling Hour Total
		Eastbound				Westbound				Northbound				Southbound					
		UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
7:00 AM		0	0	9	0	0	1	18	2	0	0	0	1	0	0	0	0	31	0
7:15 AM		0	0	9	0	1	6	28	2	0	0	0	0	0	0	0	0	46	0
7:30 AM		0	0	15	0	1	1	27	2	0	0	0	1	0	5	0	0	52	0
7:45 AM		0	0	12	0	2	5	36	1	0	0	0	1	0	3	1	2	63	192
8:00 AM		0	0	15	1	0	7	56	8	0	0	0	0	0	3	0	0	90	251
8:15 AM		0	0	18	1	2	7	48	7	0	0	0	6	0	7	1	0	97	302
8:30 AM		0	0	25	1	0	8	44	3	0	0	0	4	0	1	0	0	86	336
8:45 AM		0	0	30	0	1	7	43	3	0	0	0	4	0	1	0	0	89	362
Count Total		0	0	133	3	7	42	300	28	0	0	0	17	0	20	2	2	554	
Pk Hr	All	0	0	88	3	3	29	191	21	0	0	0	14	0	12	1	0	362	
	HV	0	0	6	0	1	2	6	0	0	0	0	2	0	0	0	0	17	
	HV%	-	-	7%	0%	33%	7%	3%	0%	-	-	-	14%	-	0%	0%	-	5%	


Interval Start	Heavy Vehicle Totals					Bicycles					Pedestrians (Crossing Leg)				
	EB	WB	NB	SB	Total	EB	WB	NB	SB	Total	E	W	N	S	Total
7:00 AM	0	0	0	0	0	0	1	0	0	1	0	0	0	0	0
7:15 AM	0	1	0	0	1	0	0	0	0	0	0	0	0	0	0
7:30 AM	0	2	0	0	2	0	0	1	0	1	0	0	0	0	0
7:45 AM	1	2	0	0	3	2	0	0	0	2	0	0	0	0	0
8:00 AM	1	3	0	0	4	0	0	0	0	0	0	0	0	0	0
8:15 AM	1	4	1	0	6	0	0	0	0	0	0	0	0	0	0
8:30 AM	2	2	1	0	5	0	0	0	0	0	0	0	0	0	0
8:45 AM	2	0	0	0	2	0	0	0	0	0	0	0	0	0	0
Count Total	7	14	2	0	23	2	1	1	0	4	0	0	0	0	0
Peak Hour	6	9	2	0	17	0	0	0	0	0	0	0	0	0	0

Count Summaries - Heavy Vehicles

Interval Start	Dillon Rd				Dillon Rd				Access Rd				Access Rd				15-min Total	Rolling Hour Total
	Eastbound				Westbound				Northbound				Southbound					
	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
7:00 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
7:15 AM	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	1	0
7:30 AM	0	0	0	0	0	0	2	0	0	0	0	0	0	0	0	0	2	0
7:45 AM	0	0	1	0	0	0	2	0	0	0	0	0	0	0	0	0	3	6
8:00 AM	0	0	1	0	0	1	2	0	0	0	0	0	0	0	0	0	4	10
8:15 AM	0	0	1	0	1	1	2	0	0	0	0	1	0	0	0	0	6	15
8:30 AM	0	0	2	0	0	0	2	0	0	0	0	1	0	0	0	0	5	18
8:45 AM	0	0	2	0	0	0	0	0	0	0	0	0	0	0	0	0	2	17
Count Total	0	0	7	0	1	2	11	0	0	0	0	2	0	0	0	0	23	
Pk Hr Heavy	0	0	6	0	1	2	6	0	0	0	0	2	0	0	0	0	17	

Count Summaries - Bikes

Interval Start	Dillon Rd				Dillon Rd				Access Rd				Access Rd				15-min Total	Rolling Hour Total
	Eastbound				Westbound				Northbound				Southbound					
	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
7:00 AM	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	1	0
7:15 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
7:30 AM	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	1	0
7:45 AM	0	0	0	2	0	0	0	0	0	0	0	0	0	0	0	0	2	4
8:00 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	3
8:15 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	3
8:30 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	2
8:45 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Count Total	0	0	0	2	0	0	1	0	0	0	1	0	0	0	0	0	4	
Pk Hr Bike	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	



Count Summaries - All Vehicles

Interval Start		Dillon Rd				Dillon Rd				Access Rd				Access Rd				15-min Total	Rolling Hour Total
		Eastbound				Westbound				Northbound				Southbound					
		UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
4:00 PM		0	0	59	1	3	14	20	2	0	0	0	16	0	2	0	0	117	0
4:15 PM		0	0	26	3	3	23	25	1	0	1	3	14	0	2	0	0	101	0
4:30 PM		0	0	41	2	0	19	15	1	0	0	0	16	0	0	0	1	95	0
4:45 PM		0	1	48	2	4	18	17	6	0	0	1	17	0	3	0	1	118	431
5:00 PM		0	2	54	1	1	26	20	5	0	1	0	32	0	4	0	0	146	460
5:15 PM		0	1	38	4	3	29	16	7	0	1	0	25	0	3	0	0	127	486
5:30 PM		0	0	33	1	0	31	12	0	0	0	0	25	0	7	0	1	110	501
5:45 PM		0	0	34	2	0	31	17	6	0	1	0	12	0	1	0	0	104	487
Count Total		0	4	333	16	14	191	142	28	0	4	4	157	0	22	0	3	918	
Pk Hr	All	0	4	173	8	8	104	65	18	0	2	1	99	0	17	0	2	501	
	HV	0	0	1	0	0	0	1	0	0	0	0	1	0	0	0	0	3	
	HV%	-	0%	1%	0%	0%	0%	2%	0%	-	0%	0%	1%	-	0%	-	0%	1%	


Interval Start	Heavy Vehicle Totals					Bicycles					Pedestrians (Crossing Leg)				
	EB	WB	NB	SB	Total	EB	WB	NB	SB	Total	E	W	N	S	Total
4:00 PM	1	0	0	0	1	0	0	0	0	0	0	0	0	0	0
4:15 PM	0	1	0	0	1	1	0	0	0	1	0	0	0	0	0
4:30 PM	0	1	0	0	1	0	0	1	0	1	0	0	0	0	0
4:45 PM	1	0	0	0	1	0	0	0	0	0	0	0	0	0	0
5:00 PM	0	0	1	0	1	0	0	0	1	1	0	0	0	0	0
5:15 PM	0	1	0	0	1	0	0	0	0	0	0	0	0	0	0
5:30 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
5:45 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Count Total	2	3	1	0	6	1	0	1	1	3	0	0	0	0	0
Peak Hour	1	1	1	0	3	0	0	0	1	1	0	0	0	0	0

Count Summaries - Heavy Vehicles

Interval Start	Dillon Rd				Dillon Rd				Access Rd				Access Rd				15-min Total	Rolling Hour Total
	Eastbound				Westbound				Northbound				Southbound					
	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
4:00 PM	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0
4:15 PM	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	1	0
4:30 PM	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	1	0
4:45 PM	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	1	4
5:00 PM	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	1	4
5:15 PM	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	1	4
5:30 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	3
5:45 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	2
Count Total	0	0	2	0	0	0	3	0	0	0	0	1	0	0	0	0	6	
Pk Hr Heavy	0	0	1	0	0	0	1	0	0	0	0	1	0	0	0	0	3	

Count Summaries - Bikes

Interval Start	Dillon Rd				Dillon Rd				Access Rd				Access Rd				15-min Total	Rolling Hour Total
	Eastbound				Westbound				Northbound				Southbound					
	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
4:00 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
4:15 PM	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0
4:30 PM	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	1	0
4:45 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	2
5:00 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	3
5:15 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	2
5:30 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
5:45 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
Count Total	0	0	1	0	0	0	0	0	0	0	0	1	0	0	0	1	3	
Pk Hr Bike	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	



Count Summaries - All Vehicles																			
Interval Start		Dillon Rd				Dillon Rd				Access Rd				Century Pl				15-min Total	Rolling Hour Total
		Eastbound				Westbound				Northbound				Southbound					
		UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
7:00 AM		0	0	4	0	0	4	11	1	0	0	0	3	0	0	0	0	23	0
7:15 AM		0	0	2	0	0	4	17	2	0	0	1	5	0	0	0	0	31	0
7:30 AM		0	0	4	0	0	8	18	1	0	0	0	9	0	0	1	0	41	0
7:45 AM		0	0	7	0	0	8	24	2	0	0	1	7	0	1	1	0	51	146
8:00 AM		0	0	4	0	0	13	31	10	0	0	1	9	0	1	0	0	69	192
8:15 AM		0	2	5	0	0	8	36	5	0	0	0	12	0	2	2	1	73	234
8:30 AM		0	0	7	0	0	6	31	2	0	0	0	12	0	1	2	0	61	254
8:45 AM		0	0	8	0	0	12	23	5	0	0	1	22	0	2	1	1	75	278
Count Total		0	2	41	0	0	63	191	28	0	0	4	79	0	7	7	2	424	
Pk Hr	All	0	2	24	0	0	39	121	22	0	0	2	55	0	6	5	2	278	
	HV	0	0	1	0	0	0	5	0	0	0	1	3	0	0	0	0	10	
	HV%	-	0%	4%	-	-	0%	4%	0%	-	-	50%	5%	-	0%	0%	0%	4%	


Interval Start	Heavy Vehicle Totals					Bicycles					Pedestrians (Crossing Leg)				
	EB	WB	NB	SB	Total	EB	WB	NB	SB	Total	E	W	N	S	Total
7:00 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
7:15 AM	0	1	0	0	1	0	0	0	0	0	1	0	0	0	1
7:30 AM	0	1	0	0	1	0	0	0	0	0	0	0	0	0	0
7:45 AM	0	2	1	0	3	0	0	0	1	1	0	0	0	0	0
8:00 AM	1	1	0	0	2	0	0	1	1	2	0	0	1	0	1
8:15 AM	0	2	0	0	2	0	0	0	1	1	2	0	1	0	3
8:30 AM	0	2	1	0	3	0	0	0	0	0	0	0	0	0	0
8:45 AM	0	0	3	0	3	0	0	0	0	0	0	0	0	0	0
Count Total	1	9	5	0	15	0	0	1	3	4	3	0	2	0	5
Peak Hour	1	5	4	0	10	0	0	1	2	3	2	0	2	0	4

Count Summaries - Heavy Vehicles

Interval Start	Dillon Rd				Dillon Rd				Access Rd				Century Pl				15-min Total	Rolling Hour Total
	Eastbound				Westbound				Northbound				Southbound					
	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
7:00 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
7:15 AM	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	1	0
7:30 AM	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	1	0
7:45 AM	0	0	0	0	0	0	2	0	0	0	0	1	0	0	0	0	3	5
8:00 AM	0	0	1	0	0	0	1	0	0	0	0	0	0	0	0	0	2	7
8:15 AM	0	0	0	0	0	0	2	0	0	0	0	0	0	0	0	0	2	8
8:30 AM	0	0	0	0	0	0	2	0	0	0	0	1	0	0	0	0	3	10
8:45 AM	0	0	0	0	0	0	0	0	0	0	1	2	0	0	0	0	3	10
Count Total	0	0	1	0	0	1	8	0	0	0	1	4	0	0	0	0	15	
Pk Hr Heavy	0	0	1	0	0	0	5	0	0	0	1	3	0	0	0	0	10	

Count Summaries - Bikes

Interval Start	Dillon Rd				Dillon Rd				Access Rd				Century Pl				15-min Total	Rolling Hour Total
	Eastbound				Westbound				Northbound				Southbound					
	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
7:00 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
7:15 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
7:30 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
7:45 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	1	1
8:00 AM	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	2	3
8:15 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	4
8:30 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	4
8:45 AM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	3
Count Total	0	0	0	0	0	0	0	0	0	0	0	1	0	0	1	0	2	
Pk Hr Bike	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	2	



Count Summaries - All Vehicles																			
Interval Start		Dillon Rd				Dillon Rd				Access Rd				Century Pl				15-min Total	Rolling Hour Total
		Eastbound				Westbound				Northbound				Southbound					
		UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
4:00 PM		0	0	35	0	0	7	12	0	0	0	3	17	0	5	2	1	82	0
4:15 PM		0	0	14	0	0	9	13	0	0	0	2	10	0	2	1	0	51	0
4:30 PM		0	0	19	0	0	6	5	1	0	0	1	12	0	7	0	0	51	0
4:45 PM		0	0	22	0	0	8	7	1	0	0	3	13	0	7	3	0	64	248
5:00 PM		0	0	19	0	0	6	11	4	0	0	2	11	0	12	2	0	67	233
5:15 PM		0	0	20	0	0	9	4	2	0	1	3	9	0	5	2	0	55	237
5:30 PM		0	0	16	0	0	5	6	3	0	1	2	5	0	1	5	1	45	231
5:45 PM		0	0	7	0	0	9	5	0	0	0	3	16	0	4	1	0	45	212
Count Total		0	0	152	0	0	59	63	11	0	2	19	93	0	43	16	2	460	
Pk Hr	All	0	0	90	0	0	30	37	2	0	0	9	52	0	21	6	1	248	
	HV	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	1	
	HV%	-	-	1%	-	-	0%	0%	0%	-	-	0%	0%	-	0%	0%	0%	0%	

Interval Start	Heavy Vehicle Totals					Bicycles					Pedestrians (Crossing Leg)				
	EB	WB	NB	SB	Total	EB	WB	NB	SB	Total	E	W	N	S	Total
4:00 PM	1	0	0	0	1	0	0	0	0	0	0	0	0	0	0
4:15 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
4:30 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
4:45 PM	0	0	0	0	0	1	0	0	2	3	0	0	0	0	0
5:00 PM	0	0	0	0	0	0	2	1	0	3	0	0	0	0	0
5:15 PM	1	0	0	0	1	0	0	0	0	0	1	0	0	0	1
5:30 PM	0	0	0	0	0	1	0	0	0	1	3	0	0	0	3
5:45 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Count Total	2	0	0	0	2	2	2	1	2	7	4	0	0	0	4
Peak Hour	1	0	0	0	1	1	0	0	2	3	0	0	0	0	0

Count Summaries - Heavy Vehicles

Interval Start	Dillon Rd				Dillon Rd				Access Rd				Century Pl				15-min Total	Rolling Hour Total
	Eastbound				Westbound				Northbound				Southbound					
	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
4:00 PM	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0
4:15 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
4:30 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
4:45 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
5:00 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
5:15 PM	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1
5:30 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
5:45 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
Count Total	0	0	2	0	0	0	0	0	0	0	0	0	0	0	0	0	2	
Pk Hr Heavy	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	1	

Count Summaries - Bikes

Interval Start	Dillon Rd				Dillon Rd				Access Rd				Century Pl				15-min Total	Rolling Hour Total
	Eastbound				Westbound				Northbound				Southbound					
	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT	UT	LT	TH	RT		
4:00 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
4:15 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
4:30 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
4:45 PM	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	2	3	3
5:00 PM	0	0	0	0	0	1	0	1	0	0	1	0	0	0	0	0	3	6
5:15 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	6
5:30 PM	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	7
5:45 PM	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	4
Count Total	0	1	1	0	0	1	0	1	0	0	1	0	0	0	0	2	7	
Pk Hr Bike	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	2	3	

APPENDIX D – Existing Synchro Outputs

HCM 7th TWSC
1: Century PI & Centennial Pkwy

02/05/2025

Intersection													
Int Delay, s/veh	1.2												
Movement	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations													
Traffic Vol, veh/h	0	36	5	11	3	119	78	6	12	2	6	5	2
Future Vol, veh/h	0	36	5	11	3	119	78	6	12	2	6	5	2
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	-	None	-	-	None	-	-	None
Storage Length	100	-	-	-	100	-	-	-	-	-	100	-	-
Veh in Median Storage, #	-	0	-	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	85	85	85	92	85	85	85	85	85	85	85	85	85
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	42	6	12	4	140	92	7	14	2	7	6	2
Major/Minor	Major1			Major2			Minor1			Minor2			
Conflicting Flow All	232	0	0	-	48	0	0	195	308	45	242	265	186
Stage 1	-	-	-	-	-	-	-	45	45	-	193	217	-
Stage 2	-	-	-	-	-	-	-	150	263	-	49	48	-
Critical Hdwy	4.12	-	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1336	-	-	-	1559	-	-	764	606	1024	712	640	856
Stage 1	-	-	-	-	-	-	-	969	857	-	809	723	-
Stage 2	-	-	-	-	-	-	-	853	691	-	964	855	-
Platoon blocked, %		-	-			-	-						
Mov Cap-1 Maneuver	1336	-	-	~ -1	~ -1	-	-	755	606	1024	693	640	856
Mov Cap-2 Maneuver	-	-	-	-	-	-	-	755	606	-	693	640	-
Stage 1	-	-	-	-	-	-	-	969	857	-	809	723	-
Stage 2	-	-	-	-	-	-	-	843	691	-	946	855	-
Approach	EB			WB			NB			SB			
HCM Control Delay, s/v	0						10.54			10.26			
HCM LOS							B			B			
Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1	SBLn2				
Capacity (veh/h)	673	1336	-	-	-	-	-	693	690				
HCM Lane V/C Ratio	0.035	-	-	-	-	-	-	0.01	0.012				
HCM Control Delay (s/veh)	10.5	0	-	-	-	-	-	10.2	10.3				
HCM Lane LOS	B	A	-	-	-	-	-	B	B				
HCM 95th %tile Q(veh)	0.1	0	-	-	-	-	-	0	0				
Notes													
~: Volume exceeds capacity		\$: Delay exceeds 300s			+: Computation Not Defined				*: All major volume in platoon				

Intersection												
Int Delay, s/veh	3.3											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	7	67	2	14	177	39	10	3	18	51	1	24
Future Vol, veh/h	7	67	2	14	177	39	10	3	18	51	1	24
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	80	-	-	100	-	50	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	85	85	85	85	85	85
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	8	73	2	15	192	42	12	4	21	60	1	28
Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	235	0	0	75	0	0	313	354	74	313	313	192
Stage 1	-	-	-	-	-	-	89	89	-	223	223	-
Stage 2	-	-	-	-	-	-	223	265	-	90	90	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1333	-	-	1524	-	-	640	571	988	640	602	849
Stage 1	-	-	-	-	-	-	918	821	-	780	719	-
Stage 2	-	-	-	-	-	-	779	689	-	918	820	-
Platoon blocked, %		-	-		-	-						
Mov Cap-1 Maneuver	1333	-	-	1524	-	-	608	562	988	613	593	849
Mov Cap-2 Maneuver	-	-	-	-	-	-	608	562	-	613	593	-
Stage 1	-	-	-	-	-	-	913	816	-	772	712	-
Stage 2	-	-	-	-	-	-	744	682	-	889	815	-
Approach	EB			WB			NB			SB		
HCM Control Delay, s/v	0.71			0.45			9.88			11.18		
HCM LOS							A			B		
Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1				
Capacity (veh/h)	775	1333	-	-	1524	-	-	671				
HCM Lane V/C Ratio	0.047	0.006	-	-	0.01	-	-	0.133				
HCM Control Delay (s/veh)	9.9	7.7	-	-	7.4	-	-	11.2				
HCM Lane LOS	A	A	-	-	A	-	-	B				
HCM 95th %tile Q(veh)	0.1	0	-	-	0	-	-	0.5				

Queues

3: McCaslin Blvd & Centennial Pkwy

02/05/2025

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Group Flow (vph)	65	29	66	276	34	125	190	926	124	70	631	29
v/c Ratio	0.39	0.09	0.04	0.62	0.14	0.08	0.38	0.46	0.08	0.20	0.34	0.02
Control Delay (s/veh)	57.7	49.4	0.1	55.3	46.0	0.1	4.9	8.8	0.1	11.8	20.1	0.0
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	57.7	49.4	0.1	55.3	46.0	0.1	4.9	8.8	0.1	11.8	20.1	0.0
Queue Length 50th (ft)	49	11	0	106	24	0	14	49	0	19	149	0
Queue Length 95th (ft)	87	24	0	135	50	0	26	377	0	45	245	0
Internal Link Dist (ft)	360			352			447			338		
Turn Bay Length (ft)	100		100	150			325		125	315		50
Base Capacity (vph)	383	766	1583	743	403	1583	600	2007	1583	384	1834	1583
Starvation Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.17	0.04	0.04	0.37	0.08	0.08	0.32	0.46	0.08	0.18	0.34	0.02
Intersection Summary												

HCM 7th Signalized Intersection Summary

3: McCaslin Blvd & Centennial Pkwy

02/05/2025

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	55	25	56	235	29	106	175	852	114	63	568	26
Future Volume (veh/h)	55	25	56	235	29	106	175	852	114	63	568	26
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Lane Width Adj.	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	65	29	0	276	34	0	190	926	0	70	631	0
Peak Hour Factor	0.85	0.85	0.85	0.85	0.85	0.85	0.92	0.92	0.92	0.90	0.90	0.90
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	142	283		361	195		538	2055		459	1952	
Arrive On Green	0.08	0.08	0.00	0.10	0.10	0.00	0.13	1.00	0.00	0.04	0.55	0.00
Sat Flow, veh/h	1781	3554	1585	3456	1870	1585	1781	3554	1585	1781	3554	1585
Grp Volume(v), veh/h	65	29	0	276	34	0	190	926	0	70	631	0
Grp Sat Flow(s),veh/h/ln	1781	1777	1585	1728	1870	1585	1781	1777	1585	1781	1777	1585
Q Serve(g_s), s	4.2	0.9	0.0	9.3	2.0	0.0	5.8	0.0	0.0	2.0	11.7	0.0
Cycle Q Clear(g_c), s	4.2	0.9	0.0	9.3	2.0	0.0	5.8	0.0	0.0	2.0	11.7	0.0
Prop In Lane	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	142	283		361	195		538	2055		459	1952	
V/C Ratio(X)	0.46	0.10		0.77	0.17		0.35	0.45		0.15	0.32	
Avail Cap(c_a), veh/h	386	770		749	405		717	2055		525	1952	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	2.00	2.00	2.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	52.7	51.2	0.0	52.3	49.0	0.0	9.9	0.0	0.0	10.7	14.8	0.0
Incr Delay (d2), s/veh	2.8	0.2	0.0	4.1	0.5	0.0	0.1	0.7	0.0	0.1	0.4	0.0
Initial Q Delay(d3), s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	2.0	0.4	0.0	4.2	1.0	0.0	1.9	0.2	0.0	0.8	4.6	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d), s/veh	55.5	51.4	0.0	56.4	49.5	0.0	10.1	0.7	0.0	10.7	15.3	0.0
LnGrp LOS	E	D		E	D		B	A		B	B	
Approach Vol, veh/h	94			310			1116			701		
Approach Delay, s/veh	54.2			55.6			2.3			14.8		
Approach LOS	D			E			A			B		
Timer - Assigned Phs	1	2		4	5	6		8				
Phs Duration (G+Y+Rc), s	10.5	75.4		15.6	14.0	71.9		18.5				
Change Period (Y+Rc), s	6.0	6.0		6.0	6.0	6.0		6.0				
Max Green Setting (Gmax), s	9.0	35.0		26.0	20.0	24.0		26.0				
Max Q Clear Time (g_c+I1), s	4.0	2.0		6.2	7.8	13.7		11.3				
Green Ext Time (p_c), s	0.0	10.7		0.3	0.2	3.8		1.2				

Intersection Summary

HCM 7th Control Delay, s/veh	15.9
HCM 7th LOS	B

Notes

User approved pedestrian interval to be less than phase max green.

Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.

Intersection												
Int Delay, s/veh	0.9											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations			↱			↱	↱↑↑↑			↱↑↑↑		
Traffic Vol, veh/h	0	0	31	0	0	69	35	1072	59	39	795	25
Future Vol, veh/h	0	0	31	0	0	69	35	1072	59	39	795	25
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	Stop	-	-	Stop	-	-	None	-	-	None
Storage Length	-	-	0	-	-	0	150	-	-	250	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	85	85	85	85	85	85	91	91	91	88	88	88
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	0	36	0	0	81	38	1178	65	44	903	28

Major/Minor	Minor2		Minor1		Major1		Major2					
Conflicting Flow All	-	-	466	-	-	621	932	0	0	1243	0	0
Stage 1	-	-	-	-	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-	-	-	-	-
Critical Hdwy	-	-	7.14	-	-	7.14	5.34	-	-	5.34	-	-
Critical Hdwy Stg 1	-	-	-	-	-	-	-	-	-	-	-	-
Critical Hdwy Stg 2	-	-	-	-	-	-	-	-	-	-	-	-
Follow-up Hdwy	-	-	3.92	-	-	3.92	3.12	-	-	3.12	-	-
Pot Cap-1 Maneuver	0	0	*796	0	0	*752	666	-	-	542	-	-
Stage 1	0	0	-	0	0	-	-	-	-	-	-	-
Stage 2	0	0	-	0	0	-	-	-	-	-	-	-
Platoon blocked, %			0			0	0	-	-	0	-	-
Mov Cap-1 Maneuver	-	-	*796	-	-	*752	666	-	-	542	-	-
Mov Cap-2 Maneuver	-	-	-	-	-	-	-	-	-	-	-	-
Stage 1	-	-	-	-	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-	-	-	-	-

Approach	EB		WB		NB		SB	
HCM Control Delay, s/v	9.74		10.37		0.32		0.56	
HCM LOS	A		B					

Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1	WBLn1	SBL	SBT	SBR
Capacity (veh/h)	666	-	-	796	752	542	-	-
HCM Lane V/C Ratio	0.058	-	-	0.046	0.108	0.082	-	-
HCM Control Delay (s/veh)	10.7	-	-	9.7	10.4	12.2	-	-
HCM Lane LOS	B	-	-	A	B	B	-	-
HCM 95th %tile Q(veh)	0.2	-	-	0.1	0.4	0.3	-	-

Notes			
~: Volume exceeds capacity	\$: Delay exceeds 300s	+: Computation Not Defined	*: All major volume in platoon

Queues

5: McCaslin Blvd & Dillon Rd

02/05/2025

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Group Flow (vph)	31	32	75	488	61	272	170	967	450	182	749	40
v/c Ratio	0.18	0.21	0.05	0.86	0.18	0.17	0.75	0.53	0.28	0.63	0.27	0.03
Control Delay (s/veh)	56.5	54.9	0.1	64.0	41.8	0.2	75.2	22.2	0.5	63.4	20.7	0.0
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	56.5	54.9	0.1	64.0	41.8	0.2	75.2	22.2	0.5	63.4	20.7	0.0
Queue Length 50th (ft)	12	24	0	189	39	0	68	292	0	76	96	0
Queue Length 95th (ft)	26	53	0	#263	79	0	#119	360	0	110	176	0
Internal Link Dist (ft)		457			420			285			453	
Turn Bay Length (ft)	130		150	280		250	450		150	250		100
Base Capacity (vph)	314	465	1583	600	621	1583	228	1837	1583	314	2732	1583
Starvation Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.10	0.07	0.05	0.81	0.10	0.17	0.75	0.53	0.28	0.58	0.27	0.03

Intersection Summary

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

HCM 7th Signalized Intersection Summary

5: McCaslin Blvd & Dillon Rd

02/05/2025

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	26	27	64	449	56	250	156	890	414	155	637	34
Future Volume (veh/h)	26	27	64	449	56	250	156	890	414	155	637	34
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Lane Width Adj.	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	31	32	0	488	61	0	170	967	0	182	749	0
Peak Hour Factor	0.85	0.85	0.85	0.92	0.92	0.92	0.92	0.92	0.92	0.85	0.85	0.85
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	93	153		547	399		224	1746		236	2527	
Arrive On Green	0.03	0.08	0.00	0.16	0.21	0.00	0.06	0.49	0.00	0.14	0.99	0.00
Sat Flow, veh/h	3456	1870	1585	3456	1870	1585	3456	3554	1585	3456	5106	1585
Grp Volume(v), veh/h	31	32	0	488	61	0	170	967	0	182	749	0
Grp Sat Flow(s),veh/h/ln	1728	1870	1585	1728	1870	1585	1728	1777	1585	1728	1702	1585
Q Serve(g_s), s	1.1	1.9	0.0	16.6	3.2	0.0	5.8	22.8	0.0	6.1	0.3	0.0
Cycle Q Clear(g_c), s	1.1	1.9	0.0	16.6	3.2	0.0	5.8	22.8	0.0	6.1	0.3	0.0
Prop In Lane	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	93	153		547	399		224	1746		236	2527	
V/C Ratio(X)	0.33	0.21		0.89	0.15		0.76	0.55		0.77	0.30	
Avail Cap(c_a), veh/h	317	468		605	623		230	1746		317	2527	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	2.00	2.00	2.00
Upstream Filter(I)	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	57.3	51.4	0.0	49.5	38.4	0.0	55.2	21.3	0.0	50.9	0.3	0.0
Incr Delay (d2), s/veh	1.6	0.7	0.0	14.2	0.2	0.0	12.6	1.3	0.0	6.9	0.3	0.0
Initial Q Delay(d3), s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	0.5	0.9	0.0	8.1	1.5	0.0	2.9	9.5	0.0	2.7	0.1	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d), s/veh	58.9	52.1	0.0	63.7	38.5	0.0	67.8	22.6	0.0	57.8	0.6	0.0
LnGrp LOS	E	D		E	D		E	C		E	A	
Approach Vol, veh/h	63			549			1137			931		
Approach Delay, s/veh	55.4			60.9			29.4			11.8		
Approach LOS	E			E			C			B		
Timer - Assigned Phs	1	2	3	4	5	6	7	8				
Phs Duration (G+Y+Rc), s	14.2	65.0	25.0	15.8	13.8	65.4	9.2	31.6				
Change Period (Y+Rc), s	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0				
Max Green Setting (Gmax), s	11.0	34.0	21.0	30.0	8.0	37.0	11.0	40.0				
Max Q Clear Time (g_c+l1), s	8.1	24.8	18.6	3.9	7.8	2.3	3.1	5.2				
Green Ext Time (p_c), s	0.1	6.2	0.4	0.1	0.0	10.9	0.0	0.3				

Intersection Summary

HCM 7th Control Delay, s/veh	30.3
HCM 7th LOS	C

Notes

Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.

Intersection												
Int Delay, s/veh	1.5											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↔↔		↗	↗↗			↔			↔	
Traffic Vol, veh/h	0	88	3	32	191	21	0	0	16	13	1	0
Future Vol, veh/h	0	88	3	32	191	21	0	0	16	13	1	0
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	175	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	85	85	85	86	86	86	85	85	85	85	85	85
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	104	4	37	222	24	0	0	19	15	1	0

Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	247	0	0	107	0	0	291	426	54	360	416	123
Stage 1	-	-	-	-	-	-	105	105	-	309	309	-
Stage 2	-	-	-	-	-	-	186	321	-	52	107	-
Critical Hdwy	4.14	-	-	4.14	-	-	7.54	6.54	6.94	7.54	6.54	6.94
Critical Hdwy Stg 1	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Follow-up Hdwy	2.22	-	-	2.22	-	-	3.52	4.02	3.32	3.52	4.02	3.32
Pot Cap-1 Maneuver	1317	-	-	1482	-	-	638	519	1002	570	526	905
Stage 1	-	-	-	-	-	-	889	807	-	676	658	-
Stage 2	-	-	-	-	-	-	798	650	-	955	806	-
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-
Mov Cap-1 Maneuver	1317	-	-	1482	-	-	621	506	1002	546	513	905
Mov Cap-2 Maneuver	-	-	-	-	-	-	621	506	-	546	513	-
Stage 1	-	-	-	-	-	-	889	807	-	659	642	-
Stage 2	-	-	-	-	-	-	776	634	-	937	806	-

Approach	EB			WB			NB			SB		
HCM Control Delay, s/v	0			0.98			8.66			11.84		
HCM LOS							A			B		

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1
Capacity (veh/h)	1002	1317	-	-	1482	-	-	543
HCM Lane V/C Ratio	0.019	-	-	-	0.025	-	-	0.03
HCM Control Delay (s/veh)	8.7	0	-	-	7.5	-	-	11.8
HCM Lane LOS	A	A	-	-	A	-	-	B
HCM 95th %tile Q(veh)	0.1	0	-	-	0.1	-	-	0.1

Intersection

Int Delay, s/veh 3.4

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↔↔			↔↔			↔			↔	
Traffic Vol, veh/h	2	24	0	39	121	22	0	2	55	6	5	2
Future Vol, veh/h	2	24	0	39	121	22	0	2	55	6	5	2
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	85	85	85	85	85	85	85	85	85	85	85	85
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	2	28	0	46	142	26	0	2	65	7	6	2

Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	168	0	0	28	0	0	199	293	14	267	280	84
Stage 1	-	-	-	-	-	-	33	33	-	247	247	-
Stage 2	-	-	-	-	-	-	166	260	-	20	33	-
Critical Hdwy	4.14	-	-	4.14	-	-	7.54	6.54	6.94	7.54	6.54	6.94
Critical Hdwy Stg 1	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Follow-up Hdwy	2.22	-	-	2.22	-	-	3.52	4.02	3.32	3.52	4.02	3.32
Pot Cap-1 Maneuver	1407	-	-	1584	-	-	742	617	1062	664	627	958
Stage 1	-	-	-	-	-	-	979	867	-	735	701	-
Stage 2	-	-	-	-	-	-	820	692	-	996	867	-
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-
Mov Cap-1 Maneuver	1407	-	-	1584	-	-	710	597	1062	601	607	958
Mov Cap-2 Maneuver	-	-	-	-	-	-	710	597	-	601	607	-
Stage 1	-	-	-	-	-	-	977	866	-	713	679	-
Stage 2	-	-	-	-	-	-	786	671	-	931	866	-

Approach	EB			WB			NB			SB		
HCM Control Delay, s/v	0.59			1.66			8.72			10.76		
HCM LOS							A			B		

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1
Capacity (veh/h)	1034	277	-	-	635	-	-	640
HCM Lane V/C Ratio	0.065	0.002	-	-	0.029	-	-	0.024
HCM Control Delay (s/veh)	8.7	7.6	0	-	7.3	0.1	-	10.8
HCM Lane LOS	A	A	A	-	A	A	-	B
HCM 95th %tile Q(veh)	0.2	0	-	-	0.1	-	-	0.1

HCM 7th TWSC
1: Century PI & Centennial Pkwy

02/05/2025

Intersection													
Int Delay, s/veh	3.4												
Movement	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations													
Traffic Vol, veh/h	1	134	13	17	5	15	6	5	5	7	61	10	5
Future Vol, veh/h	1	134	13	17	5	15	6	5	5	7	61	10	5
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	-	None	-	-	None	-	-	None
Storage Length	100	-	-	-	100	-	-	-	-	-	100	-	-
Veh in Median Storage, #	-	0	-	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	85	85	85	92	85	85	85	85	85	85	85	85	85
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	1	158	15	18	6	18	7	6	6	8	72	12	6

Major/Minor	Major1			Major2			Minor1			Minor2			
Conflicting Flow All	25	0	0	-	173	0	0	203	241	165	196	245	21
Stage 1	-	-	-	-	-	-	-	168	168	-	33	70	-
Stage 2	-	-	-	-	-	-	-	35	73	-	163	175	-
Critical Hdwy	4.12	-	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1590	-	-	-	1404	-	-	755	660	879	763	657	1056
Stage 1	-	-	-	-	-	-	-	834	760	-	983	837	-
Stage 2	-	-	-	-	-	-	-	980	834	-	839	754	-
Platoon blocked, %		-	-			-	-						
Mov Cap-1 Maneuver	1590	-	-	~-1	~-1	-	-	737	660	879	749	656	1056
Mov Cap-2 Maneuver	-	-	-	-	-	-	-	737	660	-	749	656	-
Stage 1	-	-	-	-	-	-	-	834	759	-	983	837	-
Stage 2	-	-	-	-	-	-	-	961	834	-	824	753	-

Approach	EB	WB	NB	SB
HCM Control Delay, s/v 0.05			9.85	10.24
HCM LOS			A	B

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1	SBLn2
Capacity (veh/h)	762	1590	-	-	-	-	-	749	751
HCM Lane V/C Ratio	0.026	0.001	-	-	-	-	-	0.096	0.023
HCM Control Delay (s/veh)	9.9	7.3	-	-	-	-	-	10.3	9.9
HCM Lane LOS	A	A	-	-	-	-	-	B	A
HCM 95th %tile Q(veh)	0.1	0	-	-	-	-	-	0.3	0.1

Notes			
~: Volume exceeds capacity	\$: Delay exceeds 300s	+: Computation Not Defined	*: All major volume in platoon

Intersection												
Int Delay, s/veh	2.6											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	3	217	20	25	32	20	5	3	23	35	0	6
Future Vol, veh/h	3	217	20	25	32	20	5	3	23	35	0	6
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	80	-	-	100	-	50	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	85	85	85	85	85	85	86	86	86	85	85	85
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	4	255	24	29	38	24	6	3	27	41	0	7

Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	61	0	0	279	0	0	371	394	267	361	382	38
Stage 1	-	-	-	-	-	-	274	274	-	96	96	-
Stage 2	-	-	-	-	-	-	96	120	-	264	286	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1542	-	-	1284	-	-	586	542	772	595	551	1034
Stage 1	-	-	-	-	-	-	732	683	-	910	815	-
Stage 2	-	-	-	-	-	-	910	796	-	741	675	-
Platoon blocked, %		-	-		-	-						
Mov Cap-1 Maneuver	1542	-	-	1284	-	-	567	529	772	556	537	1034
Mov Cap-2 Maneuver	-	-	-	-	-	-	567	529	-	556	537	-
Stage 1	-	-	-	-	-	-	730	682	-	889	796	-
Stage 2	-	-	-	-	-	-	883	778	-	710	674	-

Approach	EB	WB	NB	SB
HCM Control Delay, s/v	0.09	2.56	10.42	11.56
HCM LOS			B	B

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1
Capacity (veh/h)	700	1542	-	-	1284	-	-	597
HCM Lane V/C Ratio	0.052	0.002	-	-	0.023	-	-	0.081
HCM Control Delay (s/veh)	10.4	7.3	-	-	7.9	-	-	11.6
HCM Lane LOS	B	A	-	-	A	-	-	B
HCM 95th %tile Q(veh)	0.2	0	-	-	0.1	-	-	0.3

Queues

3: McCaslin Blvd & Centennial Pkwy

02/05/2025

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Group Flow (vph)	46	49	213	268	17	103	30	887	207	113	1168	36
v/c Ratio	0.30	0.16	0.13	0.62	0.07	0.07	0.11	0.46	0.13	0.30	0.55	0.02
Control Delay (s/veh)	56.7	51.9	0.2	55.9	45.3	0.1	4.9	6.4	0.2	11.1	17.9	0.0
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	56.7	51.9	0.2	55.9	45.3	0.1	4.9	6.4	0.2	11.1	17.9	0.0
Queue Length 50th (ft)	35	18	0	103	12	0	3	55	0	31	307	0
Queue Length 95th (ft)	69	37	0	142	33	0	m6	70	0	63	432	0
Internal Link Dist (ft)	360			352			447			338		
Turn Bay Length (ft)	100		100	150			325		125	315		50
Base Capacity (vph)	383	766	1583	743	403	1583	288	1938	1583	400	2138	1583
Starvation Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.12	0.06	0.13	0.36	0.04	0.07	0.10	0.46	0.13	0.28	0.55	0.02

Intersection Summary

m Volume for 95th percentile queue is metered by upstream signal.

HCM 7th Signalized Intersection Summary

3: McCaslin Blvd & Centennial Pkwy

02/05/2025

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	41	44	190	247	16	95	28	816	190	104	1075	33
Future Volume (veh/h)	41	44	190	247	16	95	28	816	190	104	1075	33
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Lane Width Adj.	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	46	49	0	268	17	0	30	887	0	113	1168	0
Peak Hour Factor	0.89	0.89	0.89	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	142	284		350	189		296	2051		442	2106	
Arrive On Green	0.08	0.08	0.00	0.10	0.10	0.00	0.04	0.77	0.00	0.04	0.59	0.00
Sat Flow, veh/h	1781	3554	1585	3456	1870	1585	1781	3554	1585	1781	3554	1585
Grp Volume(v), veh/h	46	49	0	268	17	0	30	887	0	113	1168	0
Grp Sat Flow(s),veh/h/ln	1781	1777	1585	1728	1870	1585	1781	1777	1585	1781	1777	1585
Q Serve(g_s), s	2.9	1.5	0.0	9.1	1.0	0.0	0.8	10.4	0.0	3.1	23.9	0.0
Cycle Q Clear(g_c), s	2.9	1.5	0.0	9.1	1.0	0.0	0.8	10.4	0.0	3.1	23.9	0.0
Prop In Lane	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	142	284		350	189		296	2051		442	2106	
V/C Ratio(X)	0.32	0.17		0.77	0.09		0.10	0.43		0.26	0.55	
Avail Cap(c_a), veh/h	386	770		749	405		353	2051		516	2106	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.33	1.33	1.33	1.00	1.00	1.00
Upstream Filter(I)	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	52.2	51.5	0.0	52.6	48.9	0.0	11.7	7.1	0.0	9.8	14.8	0.0
Incr Delay (d2), s/veh	1.6	0.3	0.0	4.2	0.2	0.0	0.1	0.7	0.0	0.1	1.1	0.0
Initial Q Delay(d3), s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	1.4	0.7	0.0	4.1	0.5	0.0	0.3	3.3	0.0	1.1	9.2	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d), s/veh	53.7	51.9	0.0	56.8	49.2	0.0	11.7	7.8	0.0	10.0	15.9	0.0
LnGrp LOS	D	D		E	D		B	A		A	B	
Approach Vol, veh/h	95			285			917			1281		
Approach Delay, s/veh	52.8			56.3			7.9			15.4		
Approach LOS	D			E			A			B		
Timer - Assigned Phs	1	2		4	5	6		8				
Phs Duration (G+Y+Rc), s	11.0	75.3		15.6	9.2	77.1		18.1				
Change Period (Y+Rc), s	6.0	6.0		6.0	6.0	6.0		6.0				
Max Green Setting (Gmax), s	10.0	34.0		26.0	7.0	37.0		26.0				
Max Q Clear Time (g_c+l1), s	5.1	12.4		4.9	2.8	25.9		11.1				
Green Ext Time (p_c), s	0.1	8.5		0.4	0.0	7.1		1.1				

Intersection Summary

HCM 7th Control Delay, s/veh	18.6
HCM 7th LOS	B

Notes

User approved pedestrian interval to be less than phase max green.

Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.

Intersection												
Int Delay, s/veh	0.7											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations			↱			↱	↱↑↑↑			↱↑↑↑		
Traffic Vol, veh/h	0	0	39	0	0	59	19	975	54	54	1430	28
Future Vol, veh/h	0	0	39	0	0	59	19	975	54	54	1430	28
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	Stop	-	-	Stop	-	-	None	-	-	None
Storage Length	-	-	0	-	-	0	150	-	-	250	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	85	85	85	85	85	85	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	0	46	0	0	69	21	1060	59	59	1554	30

Major/Minor	Minor2		Minor1		Major1		Major2					
Conflicting Flow All	-	-	792	-	-	559	1585	0	0	1118	0	0
Stage 1	-	-	-	-	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-	-	-	-	-
Critical Hdwy	-	-	7.14	-	-	7.14	5.34	-	-	5.34	-	-
Critical Hdwy Stg 1	-	-	-	-	-	-	-	-	-	-	-	-
Critical Hdwy Stg 2	-	-	-	-	-	-	-	-	-	-	-	-
Follow-up Hdwy	-	-	3.92	-	-	3.92	3.12	-	-	3.12	-	-
Pot Cap-1 Maneuver	0	0	*692	0	0	*766	442	-	-	598	-	-
Stage 1	0	0	-	0	0	-	-	-	-	-	-	-
Stage 2	0	0	-	0	0	-	-	-	-	-	-	-
Platoon blocked, %			0			0	0	-	-	0	-	-
Mov Cap-1 Maneuver	-	-	*692	-	-	*766	442	-	-	598	-	-
Mov Cap-2 Maneuver	-	-	-	-	-	-	-	-	-	-	-	-
Stage 1	-	-	-	-	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-	-	-	-	-

Approach	EB	WB	NB	SB
HCM Control Delay, s/v10.57		10.16	0.25	0.42
HCM LOS	B	B		

Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1WBLn1	SBL	SBT	SBR
Capacity (veh/h)	442	-	-	692	766	598	-
HCM Lane V/C Ratio	0.047	-	-	0.066	0.091	0.098	-
HCM Control Delay (s/veh)	13.5	-	-	10.6	10.2	11.7	-
HCM Lane LOS	B	-	-	B	B	B	-
HCM 95th %tile Q(veh)	0.1	-	-	0.2	0.3	0.3	-

Notes			
~: Volume exceeds capacity	\$: Delay exceeds 300s	+: Computation Not Defined	*: All major volume in platoon

Queues

5: McCaslin Blvd & Dillon Rd

02/05/2025

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Group Flow (vph)	71	88	181	596	70	133	124	941	489	233	1309	55
v/c Ratio	0.35	0.48	0.11	0.92	0.17	0.08	0.48	0.56	0.31	1.02	0.55	0.03
Control Delay (s/veh)	58.9	59.8	0.1	69.1	38.0	0.1	59.3	25.7	0.5	125.1	23.9	0.0
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	58.9	59.8	0.1	69.1	38.0	0.1	59.3	25.7	0.5	125.1	23.9	0.0
Queue Length 50th (ft)	27	66	0	235	44	0	48	281	0	~101	204	0
Queue Length 95th (ft)	49	110	0	#336	82	0	79	372	0	#189	319	m0
Internal Link Dist (ft)		457			420			285			453	
Turn Bay Length (ft)	130		150	280		250	450		150	250		100
Base Capacity (vph)	228	465	1583	657	698	1583	314	1675	1583	228	2364	1583
Starvation Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.31	0.19	0.11	0.91	0.10	0.08	0.39	0.56	0.31	1.02	0.55	0.03

Intersection Summary

~ Volume exceeds capacity, queue is theoretically infinite.

Queue shown is maximum after two cycles.

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

m Volume for 95th percentile queue is metered by upstream signal.

HCM 7th Signalized Intersection Summary

5: McCaslin Blvd & Dillon Rd

02/05/2025

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	60	75	154	548	64	122	114	866	450	214	1204	51
Future Volume (veh/h)	60	75	154	548	64	122	114	866	450	214	1204	51
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Lane Width Adj.	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	71	88	0	596	70	0	124	941	0	233	1309	0
Peak Hour Factor	0.85	0.85	0.85	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	130	156		647	436		180	1644		230	2438	
Arrive On Green	0.04	0.08	0.00	0.19	0.23	0.00	0.05	0.46	0.00	0.04	0.32	0.00
Sat Flow, veh/h	3456	1870	1585	3456	1870	1585	3456	3554	1585	3456	5106	1585
Grp Volume(v), veh/h	71	88	0	596	70	0	124	941	0	233	1309	0
Grp Sat Flow(s),veh/h/ln	1728	1870	1585	1728	1870	1585	1728	1777	1585	1728	1702	1585
Q Serve(g_s), s	2.4	5.4	0.0	20.3	3.6	0.0	4.2	23.2	0.0	8.0	25.3	0.0
Cycle Q Clear(g_c), s	2.4	5.4	0.0	20.3	3.6	0.0	4.2	23.2	0.0	8.0	25.3	0.0
Prop In Lane	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	130	156		647	436		180	1644		230	2438	
V/C Ratio(X)	0.54	0.56		0.92	0.16		0.69	0.57		1.01	0.54	
Avail Cap(c_a), veh/h	230	468		662	701		317	1644		230	2438	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.67	0.67	0.67
Upstream Filter(I)	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	56.7	52.9	0.0	47.9	36.7	0.0	55.9	23.6	0.0	57.3	29.9	0.0
Incr Delay (d2), s/veh	2.6	3.2	0.0	17.9	0.2	0.0	3.5	1.5	0.0	62.2	0.9	0.0
Initial Q Delay(d3), s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	1.1	2.7	0.0	10.2	1.6	0.0	1.9	9.8	0.0	5.5	11.0	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d), s/veh	59.3	56.1	0.0	65.7	36.9	0.0	59.4	25.0	0.0	119.6	30.8	0.0
LnGrp LOS	E	E		E	D		E	C		F	C	
Approach Vol, veh/h	159			666			1065			1542		
Approach Delay, s/veh	57.5			62.7			29.0			44.2		
Approach LOS	E			E			C			D		
Timer - Assigned Phs	1	2	3	4	5	6	7	8				
Phs Duration (G+Y+Rc), s	14.0	61.5	28.5	16.0	12.2	63.3	10.5	33.9				
Change Period (Y+Rc), s	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0				
Max Green Setting (Gmax), s	8.0	35.0	23.0	30.0	11.0	32.0	8.0	45.0				
Max Q Clear Time (g_c+I1), s	10.0	25.2	22.3	7.4	6.2	27.3	4.4	5.6				
Green Ext Time (p_c), s	0.0	6.4	0.2	0.4	0.1	4.0	0.0	0.3				

Intersection Summary

HCM 7th Control Delay, s/veh	43.7
HCM 7th LOS	D

Notes

Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.

Intersection												
Int Delay, s/veh	4											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	4	181	9	100	68	19	2	1	96	12	0	2
Future Vol, veh/h	4	181	9	100	68	19	2	1	96	12	0	2
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	175	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	85	85	85	85	85	85	85	85	85	85	85	85
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	5	213	11	118	80	22	2	1	113	14	0	2
Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	102	0	0	224	0	0	503	565	112	443	559	51
Stage 1	-	-	-	-	-	-	228	228	-	326	326	-
Stage 2	-	-	-	-	-	-	275	338	-	116	233	-
Critical Hdwy	4.14	-	-	4.14	-	-	7.54	6.54	6.94	7.54	6.54	6.94
Critical Hdwy Stg 1	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Follow-up Hdwy	2.22	-	-	2.22	-	-	3.52	4.02	3.32	3.52	4.02	3.32
Pot Cap-1 Maneuver	1488	-	-	1342	-	-	452	432	920	498	436	1006
Stage 1	-	-	-	-	-	-	754	714	-	660	647	-
Stage 2	-	-	-	-	-	-	707	639	-	876	711	-
Platoon blocked, %		-	-		-	-						
Mov Cap-1 Maneuver	1488	-	-	1342	-	-	410	393	920	396	396	1006
Mov Cap-2 Maneuver	-	-	-	-	-	-	410	393	-	396	396	-
Stage 1	-	-	-	-	-	-	752	712	-	602	590	-
Stage 2	-	-	-	-	-	-	644	583	-	764	708	-
Approach	EB			WB			NB			SB		
HCM Control Delay, s/v	0.18			4.25			9.68			13.62		
HCM LOS							A			B		
Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1				
Capacity (veh/h)	886	70	-	-	1342	-	-	434				
HCM Lane V/C Ratio	0.131	0.003	-	-	0.088	-	-	0.038				
HCM Control Delay (s/veh)	9.7	7.4	0	-	7.9	-	-	13.6				
HCM Lane LOS	A	A	A	-	A	-	-	B				
HCM 95th %tile Q(veh)	0.5	0	-	-	0.3	-	-	0.1				

Intersection												
Int Delay, s/veh	4.8											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↔↔			↔↔			↔			↔	
Traffic Vol, veh/h	0	80	0	29	27	8	1	9	45	31	7	0
Future Vol, veh/h	0	80	0	29	27	8	1	9	45	31	7	0
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	91	91	91	85	85	85	86	86	86	85	85	85
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	88	0	34	32	9	1	10	52	36	8	0
Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	41	0	0	88	0	0	176	197	44	154	193	21
Stage 1	-	-	-	-	-	-	88	88	-	105	105	-
Stage 2	-	-	-	-	-	-	88	109	-	49	88	-
Critical Hdwy	4.14	-	-	4.14	-	-	7.54	6.54	6.94	7.54	6.54	6.94
Critical Hdwy Stg 1	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Follow-up Hdwy	2.22	-	-	2.22	-	-	3.52	4.02	3.32	3.52	4.02	3.32
Pot Cap-1 Maneuver	1566	-	-	1506	-	-	770	697	1017	798	701	1052
Stage 1	-	-	-	-	-	-	910	821	-	890	808	-
Stage 2	-	-	-	-	-	-	909	804	-	958	821	-
Platoon blocked, %		-	-		-	-						
Mov Cap-1 Maneuver	1566	-	-	1506	-	-	743	681	1017	729	685	1052
Mov Cap-2 Maneuver	-	-	-	-	-	-	743	681	-	729	685	-
Stage 1	-	-	-	-	-	-	910	821	-	869	789	-
Stage 2	-	-	-	-	-	-	879	785	-	897	821	-
Approach	EB			WB			NB			SB		
HCM Control Delay, s/v	0			3.4			9.13			10.33		
HCM LOS							A			B		
Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1				
Capacity (veh/h)	935	1566	-	-	1236	-	-	720				
HCM Lane V/C Ratio	0.068	-	-	-	0.023	-	-	0.062				
HCM Control Delay (s/veh)	9.1	0	-	-	7.4	0.1	-	10.3				
HCM Lane LOS	A	A	-	-	A	A	-	B				
HCM 95th %tile Q(veh)	0.2	0	-	-	0.1	-	-	0.2				

APPENDIX E – Background (without site development) Synchro Outputs

HCM 7th TWSC
1: Century PI & Centennial Pkwy

02/05/2025

Intersection													
Int Delay, s/veh	1.2												
Movement	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations													
Traffic Vol, veh/h	0	39	5	11	3	124	78	6	12	2	6	5	2
Future Vol, veh/h	0	39	5	11	3	124	78	6	12	2	6	5	2
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	-	None	-	-	None	-	-	None
Storage Length	100	-	-	-	100	-	-	-	-	-	100	-	-
Veh in Median Storage, #	-	0	-	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	42	5	12	3	135	85	7	13	2	7	5	2
Major/Minor	Major1			Major2			Minor1			Minor2			
Conflicting Flow All	220	0	0	-	48	0	0	189	295	45	233	255	177
Stage 1	-	-	-	-	-	-	-	45	45	-	184	208	-
Stage 2	-	-	-	-	-	-	-	144	250	-	49	48	-
Critical Hdwy	4.12	-	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1350	-	-	-	1559	-	-	771	616	1025	722	648	866
Stage 1	-	-	-	-	-	-	-	969	857	-	818	730	-
Stage 2	-	-	-	-	-	-	-	859	700	-	964	855	-
Platoon blocked, %		-	-			-	-						
Mov Cap-1 Maneuver	1350	-	-	~ -1	~ -1	-	-	763	616	1025	705	648	866
Mov Cap-2 Maneuver	-	-	-	-	-	-	-	763	616	-	705	648	-
Stage 1	-	-	-	-	-	-	-	969	857	-	818	730	-
Stage 2	-	-	-	-	-	-	-	850	700	-	948	855	-
Approach	EB			WB			NB			SB			
HCM Control Delay, s/v	0						10.45			10.18			
HCM LOS							B			B			
Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1	SBLn2				
Capacity (veh/h)	683	1350	-	-	-	-	-	705	698				
HCM Lane V/C Ratio	0.032	-	-	-	-	-	-	0.009	0.011				
HCM Control Delay (s/veh)	10.4	0	-	-	-	-	-	10.2	10.2				
HCM Lane LOS	B	A	-	-	-	-	-	B	B				
HCM 95th %tile Q(veh)	0.1	0	-	-	-	-	-	0	0				
Notes													
~: Volume exceeds capacity		\$: Delay exceeds 300s			+: Computation Not Defined				*: All major volume in platoon				

Intersection

Int Delay, s/veh 3.1

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	7	70	2	14	182	39	10	3	18	51	1	24
Future Vol, veh/h	7	70	2	14	182	39	10	3	18	51	1	24
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	80	-	-	100	-	50	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	8	76	2	15	198	42	11	3	20	55	1	26

Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	240	0	0	78	0	0	321	363	77	321	322	198
Stage 1	-	-	-	-	-	-	92	92	-	228	228	-
Stage 2	-	-	-	-	-	-	229	271	-	93	93	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1326	-	-	1520	-	-	632	565	984	632	595	843
Stage 1	-	-	-	-	-	-	915	818	-	774	715	-
Stage 2	-	-	-	-	-	-	774	685	-	914	818	-
Platoon blocked, %		-	-		-	-						
Mov Cap-1 Maneuver	1326	-	-	1520	-	-	601	556	984	606	586	843
Mov Cap-2 Maneuver	-	-	-	-	-	-	601	556	-	606	586	-
Stage 1	-	-	-	-	-	-	909	814	-	767	708	-
Stage 2	-	-	-	-	-	-	741	679	-	887	813	-

Approach	EB			WB			NB			SB		
HCM Control Delay, s/v	0.68			0.44			9.9			11.18		
HCM LOS							A			B		

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1
Capacity (veh/h)	769	1326	-	-	1520	-	-	665
HCM Lane V/C Ratio	0.044	0.006	-	-	0.01	-	-	0.124
HCM Control Delay (s/veh)	9.9	7.7	-	-	7.4	-	-	11.2
HCM Lane LOS	A	A	-	-	A	-	-	B
HCM 95th %tile Q(veh)	0.1	0	-	-	0	-	-	0.4

Queues

3: McCaslin Blvd & Centennial Pkwy

02/05/2025

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Group Flow (vph)	61	28	62	260	33	117	193	945	126	70	629	29
v/c Ratio	0.38	0.09	0.04	0.61	0.14	0.07	0.38	0.46	0.08	0.20	0.34	0.02
Control Delay (s/veh)	57.3	49.8	0.1	55.9	47.0	0.1	4.7	8.0	0.1	11.3	19.4	0.0
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	57.3	49.8	0.1	55.9	47.0	0.1	4.7	8.0	0.1	11.3	19.4	0.0
Queue Length 50th (ft)	45	10	0	100	23	0	13	47	0	19	146	0
Queue Length 95th (ft)	88	25	0	139	53	0	24	350	0	44	238	0
Internal Link Dist (ft)		360			352			447			338	
Turn Bay Length (ft)	100		100	150			325		125	315		50
Base Capacity (vph)	383	766	1583	743	403	1583	607	2034	1583	383	1860	1583
Starvation Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.16	0.04	0.04	0.35	0.08	0.07	0.32	0.46	0.08	0.18	0.34	0.02
Intersection Summary												

HCM 7th Signalized Intersection Summary

3: McCaslin Blvd & Centennial Pkwy

02/05/2025

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	56	26	57	239	30	108	178	869	116	64	579	27
Future Volume (veh/h)	56	26	57	239	30	108	178	869	116	64	579	27
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Lane Width Adj.	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	61	28	0	260	33	0	193	945	0	70	629	0
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	141	281		343	186		545	2075		456	1971	
Arrive On Green	0.08	0.08	0.00	0.10	0.10	0.00	0.13	1.00	0.00	0.04	0.55	0.00
Sat Flow, veh/h	1781	3554	1585	3456	1870	1585	1781	3554	1585	1781	3554	1585
Grp Volume(v), veh/h	61	28	0	260	33	0	193	945	0	70	629	0
Grp Sat Flow(s),veh/h/ln	1781	1777	1585	1728	1870	1585	1781	1777	1585	1781	1777	1585
Q Serve(g_s), s	3.9	0.9	0.0	8.8	1.9	0.0	5.8	0.0	0.0	2.0	11.5	0.0
Cycle Q Clear(g_c), s	3.9	0.9	0.0	8.8	1.9	0.0	5.8	0.0	0.0	2.0	11.5	0.0
Prop In Lane	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	141	281		343	186		545	2075		456	1971	
V/C Ratio(X)	0.43	0.10		0.76	0.18		0.35	0.46		0.15	0.32	
Avail Cap(c_a), veh/h	386	770		749	405		723	2075		523	1971	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	2.00	2.00	2.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	52.7	51.3	0.0	52.6	49.5	0.0	9.7	0.0	0.0	10.4	14.5	0.0
Incr Delay (d2), s/veh	2.5	0.2	0.0	4.1	0.5	0.0	0.1	0.7	0.0	0.1	0.4	0.0
Initial Q Delay(d3), s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	1.8	0.4	0.0	4.0	0.9	0.0	1.9	0.2	0.0	0.8	4.5	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d), s/veh	55.2	51.5	0.0	56.7	50.1	0.0	9.8	0.7	0.0	10.4	14.9	0.0
LnGrp LOS	E	D		E	D		A	A		B	B	
Approach Vol, veh/h	89			293			1138			699		
Approach Delay, s/veh	54.0			56.0			2.3			14.4		
Approach LOS	D			E			A			B		
Timer - Assigned Phs	1	2		4	5	6		8				
Phs Duration (G+Y+Rc), s	10.5	76.1		15.5	14.0	72.6		17.9				
Change Period (Y+Rc), s	6.0	6.0		6.0	6.0	6.0		6.0				
Max Green Setting (Gmax), s	9.0	35.0		26.0	20.0	24.0		26.0				
Max Q Clear Time (g_c+I1), s	4.0	2.0		5.9	7.8	13.5		10.8				
Green Ext Time (p_c), s	0.0	11.0		0.3	0.2	3.8		1.1				

Intersection Summary

HCM 7th Control Delay, s/veh	15.3
HCM 7th LOS	B

Notes

User approved pedestrian interval to be less than phase max green.

Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.

Intersection												
Int Delay, s/veh	0.9											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations			↱			↱	↱↑↑↑			↱↑↑↑		
Traffic Vol, veh/h	0	0	31	0	0	69	35	1094	59	39	811	25
Future Vol, veh/h	0	0	31	0	0	69	35	1094	59	39	811	25
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	Stop	-	-	Stop	-	-	None	-	-	None
Storage Length	-	-	0	-	-	0	150	-	-	250	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	0	34	0	0	75	38	1189	64	42	882	27
Major/Minor	Minor2		Minor1		Major1		Major2					
Conflicting Flow All	-	-	454	-	-	627	909	0	0	1253	0	0
Stage 1	-	-	-	-	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-	-	-	-	-
Critical Hdwy	-	-	7.14	-	-	7.14	5.34	-	-	5.34	-	-
Critical Hdwy Stg 1	-	-	-	-	-	-	-	-	-	-	-	-
Critical Hdwy Stg 2	-	-	-	-	-	-	-	-	-	-	-	-
Follow-up Hdwy	-	-	3.92	-	-	3.92	3.12	-	-	3.12	-	-
Pot Cap-1 Maneuver	0	0	*796	0	0	*752	685	-	-	535	-	-
Stage 1	0	0	-	0	0	-	-	-	-	-	-	-
Stage 2	0	0	-	0	0	-	-	-	-	-	-	-
Platoon blocked, %			0			0	0	-	-	0	-	-
Mov Cap-1 Maneuver	-	-	*796	-	-	*752	685	-	-	535	-	-
Mov Cap-2 Maneuver	-	-	-	-	-	-	-	-	-	-	-	-
Stage 1	-	-	-	-	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-	-	-	-	-
Approach	EB		WB		NB		SB					
HCM Control Delay, s/v	9.72		10.32		0.31		0.55					
HCM LOS	A		B									
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1	WBLn1	SBL	SBT	SBR				
Capacity (veh/h)	685	-	-	796	752	535	-	-				
HCM Lane V/C Ratio	0.056	-	-	0.042	0.1	0.079	-	-				
HCM Control Delay (s/veh)	10.6	-	-	9.7	10.3	12.3	-	-				
HCM Lane LOS	B	-	-	A	B	B	-	-				
HCM 95th %tile Q(veh)	0.2	-	-	0.1	0.3	0.3	-	-				
Notes												
~: Volume exceeds capacity \$: Delay exceeds 300s +: Computation Not Defined *: All major volume in platoon												

Queues

5: McCaslin Blvd & Dillon Rd

02/05/2025

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Group Flow (vph)	28	30	71	498	62	277	173	986	459	172	705	38
v/c Ratio	0.16	0.19	0.04	0.87	0.18	0.17	0.76	0.54	0.29	0.60	0.26	0.02
Control Delay (s/veh)	56.4	54.5	0.0	64.9	41.6	0.2	76.2	22.4	0.5	62.6	20.7	0.0
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	56.4	54.5	0.0	64.9	41.6	0.2	76.2	22.4	0.5	62.6	20.7	0.0
Queue Length 50th (ft)	10	22	0	193	40	0	69	298	0	72	85	0
Queue Length 95th (ft)	26	53	0	#273	80	0	#123	370	0	111	180	0
Internal Link Dist (ft)		457			420			285			453	
Turn Bay Length (ft)	130		150	280		250	450		150	250		100
Base Capacity (vph)	314	465	1583	600	621	1583	228	1837	1583	314	2724	1583
Starvation Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.09	0.06	0.04	0.83	0.10	0.17	0.76	0.54	0.29	0.55	0.26	0.02

Intersection Summary

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

HCM 7th Signalized Intersection Summary

5: McCaslin Blvd & Dillon Rd

02/05/2025

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	26	28	65	458	57	255	159	907	422	158	649	35
Future Volume (veh/h)	26	28	65	458	57	255	159	907	422	158	649	35
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Lane Width Adj.	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	28	30	0	498	62	0	173	986	0	172	705	0
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	87	153		556	407		227	1748		226	2510	
Arrive On Green	0.03	0.08	0.00	0.16	0.22	0.00	0.07	0.49	0.00	0.13	0.98	0.00
Sat Flow, veh/h	3456	1870	1585	3456	1870	1585	3456	3554	1585	3456	5106	1585
Grp Volume(v), veh/h	28	30	0	498	62	0	173	986	0	172	705	0
Grp Sat Flow(s),veh/h/ln	1728	1870	1585	1728	1870	1585	1728	1777	1585	1728	1702	1585
Q Serve(g_s), s	1.0	1.8	0.0	17.0	3.2	0.0	5.9	23.4	0.0	5.8	0.4	0.0
Cycle Q Clear(g_c), s	1.0	1.8	0.0	17.0	3.2	0.0	5.9	23.4	0.0	5.8	0.4	0.0
Prop In Lane	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	87	153		556	407		227	1748		226	2510	
V/C Ratio(X)	0.32	0.20		0.90	0.15		0.76	0.56		0.76	0.28	
Avail Cap(c_a), veh/h	317	468		605	623		230	1748		317	2510	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	2.00	2.00	2.00
Upstream Filter(I)	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	57.5	51.4	0.0	49.4	38.0	0.0	55.1	21.4	0.0	51.2	0.5	0.0
Incr Delay (d2), s/veh	1.5	0.6	0.0	14.9	0.2	0.0	13.1	1.3	0.0	5.6	0.3	0.0
Initial Q Delay(d3), s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	0.4	0.9	0.0	8.3	1.5	0.0	3.0	9.8	0.0	2.5	0.2	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d), s/veh	59.0	52.0	0.0	64.3	38.2	0.0	68.3	22.8	0.0	56.8	0.8	0.0
LnGrp LOS	E	D		E	D		E	C		E	A	
Approach Vol, veh/h	58			560			1159			877		
Approach Delay, s/veh	55.4			61.4			29.6			11.8		
Approach LOS	E			E			C			B		
Timer - Assigned Phs	1	2	3	4	5	6	7	8				
Phs Duration (G+Y+Rc), s	13.9	65.0	25.3	15.8	13.9	65.0	9.0	32.1				
Change Period (Y+Rc), s	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0				
Max Green Setting (Gmax), s	11.0	34.0	21.0	30.0	8.0	37.0	11.0	40.0				
Max Q Clear Time (g_c+I1), s	7.8	25.4	19.0	3.8	7.9	2.4	3.0	5.2				
Green Ext Time (p_c), s	0.1	5.9	0.3	0.1	0.0	10.1	0.0	0.3				

Intersection Summary

HCM 7th Control Delay, s/veh	31.0
HCM 7th LOS	C

Notes

Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.

Intersection												
Int Delay, s/veh	1.5											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↔↔		↗	↗↗			↔			↔	
Traffic Vol, veh/h	0	90	3	32	196	21	0	0	16	13	1	0
Future Vol, veh/h	0	90	3	32	196	21	0	0	16	13	1	0
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	175	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	98	3	35	213	23	0	0	17	14	1	0

Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	236	0	0	101	0	0	276	405	51	343	395	118
Stage 1	-	-	-	-	-	-	99	99	-	294	294	-
Stage 2	-	-	-	-	-	-	177	305	-	49	101	-
Critical Hdwy	4.14	-	-	4.14	-	-	7.54	6.54	6.94	7.54	6.54	6.94
Critical Hdwy Stg 1	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Follow-up Hdwy	2.22	-	-	2.22	-	-	3.52	4.02	3.32	3.52	4.02	3.32
Pot Cap-1 Maneuver	1328	-	-	1489	-	-	655	533	1007	587	540	912
Stage 1	-	-	-	-	-	-	896	812	-	690	668	-
Stage 2	-	-	-	-	-	-	808	661	-	958	811	-
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-
Mov Cap-1 Maneuver	1328	-	-	1489	-	-	638	521	1007	563	528	912
Mov Cap-2 Maneuver	-	-	-	-	-	-	638	521	-	563	528	-
Stage 1	-	-	-	-	-	-	896	812	-	674	653	-
Stage 2	-	-	-	-	-	-	788	645	-	942	811	-

Approach	EB	WB	NB	SB
HCM Control Delay, s/v	0	0.96	8.64	11.6
HCM LOS			A	B

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1
Capacity (veh/h)	1007	1328	-	-	1489	-	-	561
HCM Lane V/C Ratio	0.017	-	-	-	0.023	-	-	0.027
HCM Control Delay (s/veh)	8.6	0	-	-	7.5	-	-	11.6
HCM Lane LOS	A	A	-	-	A	-	-	B
HCM 95th %tile Q(veh)	0.1	0	-	-	0.1	-	-	0.1

Intersection												
Int Delay, s/veh	3.3											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	2	26	0	39	126	22	0	2	55	6	5	2
Future Vol, veh/h	2	26	0	39	126	22	0	2	55	6	5	2
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	2	28	0	42	137	24	0	2	60	7	5	2
Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	161	0	0	28	0	0	189	278	14	253	266	80
Stage 1	-	-	-	-	-	-	33	33	-	234	234	-
Stage 2	-	-	-	-	-	-	156	246	-	20	33	-
Critical Hdwy	4.14	-	-	4.14	-	-	7.54	6.54	6.94	7.54	6.54	6.94
Critical Hdwy Stg 1	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Follow-up Hdwy	2.22	-	-	2.22	-	-	3.52	4.02	3.32	3.52	4.02	3.32
Pot Cap-1 Maneuver	1416	-	-	1583	-	-	754	628	1062	679	638	963
Stage 1	-	-	-	-	-	-	979	867	-	748	710	-
Stage 2	-	-	-	-	-	-	831	702	-	996	867	-
Platoon blocked, %		-	-		-	-						
Mov Cap-1 Maneuver	1416	-	-	1583	-	-	724	610	1062	620	619	963
Mov Cap-2 Maneuver	-	-	-	-	-	-	724	610	-	620	619	-
Stage 1	-	-	-	-	-	-	978	866	-	727	690	-
Stage 2	-	-	-	-	-	-	799	682	-	937	866	-
Approach	EB			WB			NB			SB		
HCM Control Delay, s/v	0.55			1.62			8.7			10.61		
HCM LOS							A			B		
Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1				
Capacity (veh/h)	1035	257	-	-	621	-	-	656				
HCM Lane V/C Ratio	0.06	0.002	-	-	0.027	-	-	0.022				
HCM Control Delay (s/veh)	8.7	7.5	0	-	7.3	0.1	-	10.6				
HCM Lane LOS	A	A	A	-	A	A	-	B				
HCM 95th %tile Q(veh)	0.2	0	-	-	0.1	-	-	0.1				

HCM 7th TWSC
1: Century PI & Centennial Pkwy

02/05/2025

Intersection													
Int Delay, s/veh	3.2												
Movement	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations													
Traffic Vol, veh/h	1	139	13	17	5	17	6	5	5	7	61	10	5
Future Vol, veh/h	1	139	13	17	5	17	6	5	5	7	61	10	5
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	-	None	-	-	None	-	-	None
Storage Length	100	-	-	-	100	-	-	-	-	-	100	-	-
Veh in Median Storage, #	-	0	-	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	1	151	14	18	5	18	7	5	5	8	66	11	5

Major/Minor	Major1			Major2			Minor1			Minor2			
Conflicting Flow All	25	0	0	-	165	0	0	195	233	158	189	237	22
Stage 1	-	-	-	-	-	-	-	160	160	-	33	70	-
Stage 2	-	-	-	-	-	-	-	35	73	-	156	167	-
Critical Hdwy	4.12	-	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1589	-	-	-	1413	-	-	764	667	887	772	664	1055
Stage 1	-	-	-	-	-	-	-	842	765	-	984	837	-
Stage 2	-	-	-	-	-	-	-	981	834	-	846	760	-
Platoon blocked, %		-	-			-	-						
Mov Cap-1 Maneuver	1589	-	-	~-1	~-1	-	-	747	667	887	758	663	1055
Mov Cap-2 Maneuver	-	-	-	-	-	-	-	747	667	-	758	663	-
Stage 1	-	-	-	-	-	-	-	841	765	-	984	837	-
Stage 2	-	-	-	-	-	-	-	963	834	-	833	759	-

Approach	EB	WB	NB	SB
HCM Control Delay, s/v 0.05			9.79	10.13
HCM LOS			A	B

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1	SBLn2
Capacity (veh/h)	770	1589	-	-	-	-	-	758	757
HCM Lane V/C Ratio	0.024	0.001	-	-	-	-	-	0.087	0.022
HCM Control Delay (s/veh)	9.8	7.3	-	-	-	-	-	10.2	9.9
HCM Lane LOS	A	A	-	-	-	-	-	B	A
HCM 95th %tile Q(veh)	0.1	0	-	-	-	-	-	0.3	0.1

Notes			
~: Volume exceeds capacity	\$: Delay exceeds 300s	+: Computation Not Defined	*: All major volume in platoon

Intersection												
Int Delay, s/veh	2.5											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	3	222	20	25	34	20	5	3	23	35	0	6
Future Vol, veh/h	3	222	20	25	34	20	5	3	23	35	0	6
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	80	-	-	100	-	50	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	3	241	22	27	37	22	5	3	25	38	0	7

Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	59	0	0	263	0	0	350	372	252	341	361	37
Stage 1	-	-	-	-	-	-	259	259	-	91	91	-
Stage 2	-	-	-	-	-	-	91	113	-	249	270	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1545	-	-	1301	-	-	605	558	786	613	566	1035
Stage 1	-	-	-	-	-	-	746	694	-	916	819	-
Stage 2	-	-	-	-	-	-	916	802	-	755	686	-
Platoon blocked, %		-	-		-	-						
Mov Cap-1 Maneuver	1545	-	-	1301	-	-	587	546	786	577	553	1035
Mov Cap-2 Maneuver	-	-	-	-	-	-	587	546	-	577	553	-
Stage 1	-	-	-	-	-	-	744	692	-	897	802	-
Stage 2	-	-	-	-	-	-	891	785	-	726	685	-

Approach	EB	WB	NB	SB
HCM Control Delay, s/v	0.09	2.48	10.27	11.29
HCM LOS			B	B

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1
Capacity (veh/h)	717	1545	-	-	1301	-	-	617
HCM Lane V/C Ratio	0.047	0.002	-	-	0.021	-	-	0.072
HCM Control Delay (s/veh)	10.3	7.3	-	-	7.8	-	-	11.3
HCM Lane LOS	B	A	-	-	A	-	-	B
HCM 95th %tile Q(veh)	0.1	0	-	-	0.1	-	-	0.2

Queues

3: McCaslin Blvd & Centennial Pkwy

02/05/2025

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Group Flow (vph)	46	49	210	274	17	105	32	904	210	115	1191	37
v/c Ratio	0.30	0.16	0.13	0.63	0.07	0.07	0.12	0.47	0.13	0.31	0.56	0.02
Control Delay (s/veh)	56.5	51.8	0.2	55.8	45.1	0.1	4.8	6.2	0.2	11.3	18.3	0.0
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	56.5	51.8	0.2	55.8	45.1	0.1	4.8	6.2	0.2	11.3	18.3	0.0
Queue Length 50th (ft)	35	18	0	105	12	0	3	53	0	32	318	0
Queue Length 95th (ft)	72	38	0	145	33	0	m6	68	0	65	447	0
Internal Link Dist (ft)	360			352			447			338		
Turn Bay Length (ft)	100		100	150			325		125	315		50
Base Capacity (vph)	383	766	1583	743	403	1583	279	1931	1583	392	2132	1583
Starvation Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.12	0.06	0.13	0.37	0.04	0.07	0.11	0.47	0.13	0.29	0.56	0.02

Intersection Summary

m Volume for 95th percentile queue is metered by upstream signal.

HCM 7th Signalized Intersection Summary

3: McCaslin Blvd & Centennial Pkwy

02/05/2025

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	42	45	193	252	16	97	29	832	193	106	1096	34
Future Volume (veh/h)	42	45	193	252	16	97	29	832	193	106	1096	34
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Lane Width Adj.	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	46	49	0	274	17	0	32	904	0	115	1191	0
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	142	284		356	193		289	2042		434	2096	
Arrive On Green	0.08	0.08	0.00	0.10	0.10	0.00	0.04	0.76	0.00	0.04	0.59	0.00
Sat Flow, veh/h	1781	3554	1585	3456	1870	1585	1781	3554	1585	1781	3554	1585
Grp Volume(v), veh/h	46	49	0	274	17	0	32	904	0	115	1191	0
Grp Sat Flow(s),veh/h/ln	1781	1777	1585	1728	1870	1585	1781	1777	1585	1781	1777	1585
Q Serve(g_s), s	2.9	1.5	0.0	9.3	1.0	0.0	0.9	10.9	0.0	3.2	24.8	0.0
Cycle Q Clear(g_c), s	2.9	1.5	0.0	9.3	1.0	0.0	0.9	10.9	0.0	3.2	24.8	0.0
Prop In Lane	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	142	284		356	193		289	2042		434	2096	
V/C Ratio(X)	0.32	0.17		0.77	0.09		0.11	0.44		0.26	0.57	
Avail Cap(c_a), veh/h	386	770		749	405		344	2042		507	2096	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.33	1.33	1.33	1.00	1.00	1.00
Upstream Filter(I)	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	52.2	51.5	0.0	52.4	48.7	0.0	11.9	7.3	0.0	10.0	15.2	0.0
Incr Delay (d2), s/veh	1.6	0.3	0.0	4.2	0.2	0.0	0.1	0.7	0.0	0.1	1.1	0.0
Initial Q Delay(d3), s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	1.4	0.7	0.0	4.2	0.5	0.0	0.3	3.4	0.0	1.2	9.6	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d), s/veh	53.7	51.9	0.0	56.7	49.0	0.0	12.0	8.0	0.0	10.1	16.3	0.0
LnGrp LOS	D	D		E	D		B	A		B	B	
Approach Vol, veh/h	95			291			936			1306		
Approach Delay, s/veh	52.8			56.2			8.1			15.8		
Approach LOS	D			E			A			B		
Timer - Assigned Phs	1	2		4	5	6		8				
Phs Duration (G+Y+Rc), s	11.1	75.0		15.6	9.3	76.8		18.4				
Change Period (Y+Rc), s	6.0	6.0		6.0	6.0	6.0		6.0				
Max Green Setting (Gmax), s	10.0	34.0		26.0	7.0	37.0		26.0				
Max Q Clear Time (g_c+l1), s	5.2	12.9		4.9	2.9	26.8		11.3				
Green Ext Time (p_c), s	0.1	8.6		0.4	0.0	6.7		1.1				

Intersection Summary

HCM 7th Control Delay, s/veh	18.9
HCM 7th LOS	B

Notes

User approved pedestrian interval to be less than phase max green.

Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.

Intersection												
Int Delay, s/veh	0.7											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations			↱			↱	↱ ↱ ↱ ↱			↱ ↱ ↱ ↱		
Traffic Vol, veh/h	0	0	39	0	0	59	19	995	54	54	1459	28
Future Vol, veh/h	0	0	39	0	0	59	19	995	54	54	1459	28
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	Stop	-	-	Stop	-	-	None	-	-	None
Storage Length	-	-	0	-	-	0	150	-	-	250	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	0	42	0	0	64	21	1082	59	59	1586	30

Major/Minor	Minor2		Minor1		Major1		Major2					
Conflicting Flow All	-	-	808	-	-	570	1616	0	0	1140	0	0
Stage 1	-	-	-	-	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-	-	-	-	-
Critical Hdwy	-	-	7.14	-	-	7.14	5.34	-	-	5.34	-	-
Critical Hdwy Stg 1	-	-	-	-	-	-	-	-	-	-	-	-
Critical Hdwy Stg 2	-	-	-	-	-	-	-	-	-	-	-	-
Follow-up Hdwy	-	-	3.92	-	-	3.92	3.12	-	-	3.12	-	-
Pot Cap-1 Maneuver	0	0	*692	0	0	*766	422	-	-	581	-	-
Stage 1	0	0	-	0	0	-	-	-	-	-	-	-
Stage 2	0	0	-	0	0	-	-	-	-	-	-	-
Platoon blocked, %			0			0	0	-	-	0	-	-
Mov Cap-1 Maneuver	-	-	*692	-	-	*766	422	-	-	581	-	-
Mov Cap-2 Maneuver	-	-	-	-	-	-	-	-	-	-	-	-
Stage 1	-	-	-	-	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-	-	-	-	-

Approach	EB	WB	NB	SB
HCM Control Delay, s/v10.54		10.13	0.25	0.42
HCM LOS	B	B		

Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1WBLn1	SBL	SBT	SBR
Capacity (veh/h)	422	-	-	692	766	581	-
HCM Lane V/C Ratio	0.049	-	-	0.061	0.084	0.101	-
HCM Control Delay (s/veh)	14	-	-	10.5	10.1	11.9	-
HCM Lane LOS	B	-	-	B	B	B	-
HCM 95th %tile Q(veh)	0.2	-	-	0.2	0.3	0.3	-

Notes			
~: Volume exceeds capacity	\$: Delay exceeds 300s	+: Computation Not Defined	*: All major volume in platoon

Queues

5: McCaslin Blvd & Dillon Rd

02/05/2025

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Group Flow (vph)	66	84	171	608	71	135	126	960	499	237	1335	57
v/c Ratio	0.33	0.47	0.11	0.94	0.17	0.09	0.48	0.57	0.32	1.04	0.57	0.04
Control Delay (s/veh)	58.5	59.5	0.1	71.0	38.2	0.1	59.3	25.8	0.5	128.5	24.5	0.0
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	58.5	59.5	0.1	71.0	38.2	0.1	59.3	25.8	0.5	128.5	24.5	0.0
Queue Length 50th (ft)	25	63	0	240	45	0	48	287	0	~105	212	0
Queue Length 95th (ft)	49	112	0	#347	83	0	79	380	0	#191	329	m0
Internal Link Dist (ft)		457			420			285			453	
Turn Bay Length (ft)	130		150	280		250	450		150	250		100
Base Capacity (vph)	228	465	1583	657	698	1583	314	1677	1583	228	2362	1583
Starvation Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.29	0.18	0.11	0.93	0.10	0.09	0.40	0.57	0.32	1.04	0.57	0.04

Intersection Summary

~ Volume exceeds capacity, queue is theoretically infinite.

Queue shown is maximum after two cycles.

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

m Volume for 95th percentile queue is metered by upstream signal.

HCM 7th Signalized Intersection Summary

5: McCaslin Blvd & Dillon Rd

02/05/2025

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	61	77	157	559	65	124	116	883	459	218	1228	52
Future Volume (veh/h)	61	77	157	559	65	124	116	883	459	218	1228	52
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Lane Width Adj.	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	66	84	0	608	71	0	126	960	0	237	1335	0
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	128	156		657	442		182	1635		230	2421	
Arrive On Green	0.04	0.08	0.00	0.19	0.24	0.00	0.05	0.46	0.00	0.04	0.32	0.00
Sat Flow, veh/h	3456	1870	1585	3456	1870	1585	3456	3554	1585	3456	5106	1585
Grp Volume(v), veh/h	66	84	0	608	71	0	126	960	0	237	1335	0
Grp Sat Flow(s),veh/h/ln	1728	1870	1585	1728	1870	1585	1728	1777	1585	1728	1702	1585
Q Serve(g_s), s	2.2	5.2	0.0	20.8	3.6	0.0	4.3	24.0	0.0	8.0	26.0	0.0
Cycle Q Clear(g_c), s	2.2	5.2	0.0	20.8	3.6	0.0	4.3	24.0	0.0	8.0	26.0	0.0
Prop In Lane	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	128	156		657	442		182	1635		230	2421	
V/C Ratio(X)	0.52	0.54		0.93	0.16		0.69	0.59		1.03	0.55	
Avail Cap(c_a), veh/h	230	468		662	701		317	1635		230	2421	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.67	0.67	0.67
Upstream Filter(I)	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	56.7	52.8	0.0	47.8	36.4	0.0	55.9	24.0	0.0	57.3	30.4	0.0
Incr Delay (d2), s/veh	2.4	2.9	0.0	18.8	0.2	0.0	3.5	1.6	0.0	67.0	0.9	0.0
Initial Q Delay(d3), s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	1.0	2.6	0.0	10.4	1.7	0.0	1.9	10.2	0.0	5.7	11.4	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d), s/veh	59.1	55.7	0.0	66.6	36.5	0.0	59.4	25.5	0.0	124.3	31.3	0.0
LnGrp LOS	E	E		E	D		E	C		F	C	
Approach Vol, veh/h	150			679			1086			1572		
Approach Delay, s/veh	57.2			63.4			29.5			45.3		
Approach LOS	E			E			C			D		
Timer - Assigned Phs	1	2	3	4	5	6	7	8				
Phs Duration (G+Y+Rc), s	14.0	61.2	28.8	16.0	12.3	62.9	10.4	34.4				
Change Period (Y+Rc), s	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0				
Max Green Setting (Gmax), s	8.0	35.0	23.0	30.0	11.0	32.0	8.0	45.0				
Max Q Clear Time (g_c+I1), s	10.0	26.0	22.8	7.2	6.3	28.0	4.2	5.6				
Green Ext Time (p_c), s	0.0	6.0	0.1	0.4	0.1	3.5	0.0	0.3				

Intersection Summary

HCM 7th Control Delay, s/veh	44.4
HCM 7th LOS	D

Notes

Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.

Intersection												
Int Delay, s/veh	3.9											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	4	187	9	100	72	19	2	1	96	12	0	2
Future Vol, veh/h	4	187	9	100	72	19	2	1	96	12	0	2
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	175	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	4	203	10	109	78	21	2	1	104	13	0	2
Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	99	0	0	213	0	0	473	533	107	417	528	49
Stage 1	-	-	-	-	-	-	217	217	-	306	306	-
Stage 2	-	-	-	-	-	-	257	316	-	111	222	-
Critical Hdwy	4.14	-	-	4.14	-	-	7.54	6.54	6.94	7.54	6.54	6.94
Critical Hdwy Stg 1	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Follow-up Hdwy	2.22	-	-	2.22	-	-	3.52	4.02	3.32	3.52	4.02	3.32
Pot Cap-1 Maneuver	1492	-	-	1354	-	-	474	451	927	520	454	1008
Stage 1	-	-	-	-	-	-	765	722	-	679	660	-
Stage 2	-	-	-	-	-	-	726	653	-	882	719	-
Platoon blocked, %		-	-		-	-						
Mov Cap-1 Maneuver	1492	-	-	1354	-	-	434	414	927	422	417	1008
Mov Cap-2 Maneuver	-	-	-	-	-	-	434	414	-	422	417	-
Stage 1	-	-	-	-	-	-	763	720	-	624	607	-
Stage 2	-	-	-	-	-	-	666	601	-	779	716	-
Approach	EB			WB			NB			SB		
HCM Control Delay, s/v	0.17			4.13			9.57			13.09		
HCM LOS							A			B		
Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1				
Capacity (veh/h)	895	68	-	-	1354	-	-	460				
HCM Lane V/C Ratio	0.12	0.003	-	-	0.08	-	-	0.033				
HCM Control Delay (s/veh)	9.6	7.4	0	-	7.9	-	-	13.1				
HCM Lane LOS	A	A	A	-	A	-	-	B				
HCM 95th %tile Q(veh)	0.4	0	-	-	0.3	-	-	0.1				

Intersection

Int Delay, s/veh 4.5

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↔↔			↔↔			↔			↔	
Traffic Vol, veh/h	0	86	0	29	31	8	1	9	45	31	7	0
Future Vol, veh/h	0	86	0	29	31	8	1	9	45	31	7	0
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	93	0	32	34	9	1	10	49	34	8	0

Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	42	0	0	93	0	0	177	199	47	153	195	21
Stage 1	-	-	-	-	-	-	93	93	-	101	101	-
Stage 2	-	-	-	-	-	-	84	105	-	52	93	-
Critical Hdwy	4.14	-	-	4.14	-	-	7.54	6.54	6.94	7.54	6.54	6.94
Critical Hdwy Stg 1	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Follow-up Hdwy	2.22	-	-	2.22	-	-	3.52	4.02	3.32	3.52	4.02	3.32
Pot Cap-1 Maneuver	1565	-	-	1499	-	-	769	696	1012	800	700	1051
Stage 1	-	-	-	-	-	-	903	817	-	894	811	-
Stage 2	-	-	-	-	-	-	915	807	-	955	817	-
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-
Mov Cap-1 Maneuver	1565	-	-	1499	-	-	744	681	1012	734	685	1051
Mov Cap-2 Maneuver	-	-	-	-	-	-	744	681	-	734	685	-
Stage 1	-	-	-	-	-	-	903	817	-	875	793	-
Stage 2	-	-	-	-	-	-	887	790	-	898	817	-

Approach	EB			WB			NB			SB		
HCM Control Delay, s/v	0			3.2			9.13			10.27		
HCM LOS							A			B		

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1
Capacity (veh/h)	932	1565	-	-	1193	-	-	725
HCM Lane V/C Ratio	0.064	-	-	-	0.021	-	-	0.057
HCM Control Delay (s/veh)	9.1	0	-	-	7.5	0.1	-	10.3
HCM Lane LOS	A	A	-	-	A	A	-	B
HCM 95th %tile Q(veh)	0.2	0	-	-	0.1	-	-	0.2

HCM 7th TWSC
1: Century PI & Centennial Pkwy

02/05/2025

Intersection													
Int Delay, s/veh	1												
Movement	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations													
Traffic Vol, veh/h	0	68	5	11	3	172	78	6	12	2	6	5	2
Future Vol, veh/h	0	68	5	11	3	172	78	6	12	2	6	5	2
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	-	None	-	-	None	-	-	None
Storage Length	100	-	-	-	100	-	-	-	-	-	100	-	-
Veh in Median Storage, #	-	0	-	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	74	5	12	3	187	85	7	13	2	7	5	2
Major/Minor	Major1			Major2			Minor1			Minor2			
Conflicting Flow All	272	0	0	-	79	0	0	273	379	77	316	339	229
Stage 1	-	-	-	-	-	-	-	77	77	-	236	260	-
Stage 2	-	-	-	-	-	-	-	196	302	-	80	79	-
Critical Hdwy	4.12	-	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1292	-	-	-	1519	-	-	680	553	984	636	582	810
Stage 1	-	-	-	-	-	-	-	932	831	-	767	693	-
Stage 2	-	-	-	-	-	-	-	806	664	-	928	829	-
Platoon blocked, %		-	-			-	-						
Mov Cap-1 Maneuver	1292	-	-	~ -1	~ -1	-	-	671	553	984	620	582	810
Mov Cap-2 Maneuver	-	-	-	-	-	-	-	671	553	-	620	582	-
Stage 1	-	-	-	-	-	-	-	932	831	-	767	693	-
Stage 2	-	-	-	-	-	-	-	797	664	-	911	829	-
Approach	EB			WB			NB			SB			
HCM Control Delay, s/v	0						11.09			10.81			
HCM LOS							B			B			
Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1	SBLn2				
Capacity (veh/h)	612	1292	-	-	-	-	-	620	633				
HCM Lane V/C Ratio	0.035	-	-	-	-	-	-	0.011	0.012				
HCM Control Delay (s/veh)	11.1	0	-	-	-	-	-	10.9	10.8				
HCM Lane LOS	B	A	-	-	-	-	-	B	B				
HCM 95th %tile Q(veh)	0.1	0	-	-	-	-	-	0	0				
Notes													
~: Volume exceeds capacity		\$: Delay exceeds 300s		+: Computation Not Defined		*: All major volume in platoon							

Intersection

Int Delay, s/veh 2.8

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	7	99	2	14	230	39	10	3	18	51	1	24
Future Vol, veh/h	7	99	2	14	230	39	10	3	18	51	1	24
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	80	-	-	100	-	50	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	8	108	2	15	250	42	11	3	20	55	1	26

Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	292	0	0	110	0	0	405	447	109	405	405	250
Stage 1	-	-	-	-	-	-	124	124	-	280	280	-
Stage 2	-	-	-	-	-	-	281	323	-	124	125	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1269	-	-	1480	-	-	556	507	945	556	535	789
Stage 1	-	-	-	-	-	-	880	793	-	726	679	-
Stage 2	-	-	-	-	-	-	726	650	-	880	792	-
Platoon blocked, %		-	-		-	-						
Mov Cap-1 Maneuver	1269	-	-	1480	-	-	528	498	945	533	526	789
Mov Cap-2 Maneuver	-	-	-	-	-	-	528	498	-	533	526	-
Stage 1	-	-	-	-	-	-	875	789	-	719	672	-
Stage 2	-	-	-	-	-	-	693	644	-	853	788	-

Approach	EB			WB			NB			SB		
HCM Control Delay, s/v	0.51			0.37			10.37			12.05		
HCM LOS							B			B		

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1
Capacity (veh/h)	705	1269	-	-	1480	-	-	593
HCM Lane V/C Ratio	0.048	0.006	-	-	0.01	-	-	0.139
HCM Control Delay (s/veh)	10.4	7.9	-	-	7.5	-	-	12
HCM Lane LOS	B	A	-	-	A	-	-	B
HCM 95th %tile Q(veh)	0.2	0	-	-	0	-	-	0.5

Queues

3: McCaslin Blvd & Centennial Pkwy

02/05/2025

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Group Flow (vph)	74	34	75	314	39	142	234	1141	153	85	761	35
v/c Ratio	0.43	0.10	0.05	0.65	0.15	0.09	0.53	0.59	0.10	0.32	0.44	0.02
Control Delay (s/veh)	58.6	49.3	0.1	55.0	45.0	0.1	9.6	10.9	0.1	15.1	24.3	0.0
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	58.6	49.3	0.1	55.0	45.0	0.1	9.6	10.9	0.1	15.1	24.3	0.0
Queue Length 50th (ft)	55	13	0	120	27	0	21	110	0	24	201	0
Queue Length 95th (ft)	103	m28	0	160	58	0	36	517	m0	56	333	0
Internal Link Dist (ft)	360			352			447			338		
Turn Bay Length (ft)	100		100	150			325		125	315		50
Base Capacity (vph)	383	766	1583	743	403	1583	522	1946	1583	295	1719	1583
Starvation Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.19	0.04	0.05	0.42	0.10	0.09	0.45	0.59	0.10	0.29	0.44	0.02

Intersection Summary

m Volume for 95th percentile queue is metered by upstream signal.

HCM 7th Signalized Intersection Summary

3: McCaslin Blvd & Centennial Pkwy

02/05/2025

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	68	31	69	289	36	131	215	1050	141	78	700	32
Future Volume (veh/h)	68	31	69	289	36	131	215	1050	141	78	700	32
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Lane Width Adj.	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	74	34	0	314	39	0	234	1141	0	85	761	0
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	144	288		401	217		481	2003		387	1852	
Arrive On Green	0.08	0.08	0.00	0.12	0.12	0.00	0.16	1.00	0.00	0.04	0.52	0.00
Sat Flow, veh/h	1781	3554	1585	3456	1870	1585	1781	3554	1585	1781	3554	1585
Grp Volume(v), veh/h	74	34	0	314	39	0	234	1141	0	85	761	0
Grp Sat Flow(s),veh/h/ln	1781	1777	1585	1728	1870	1585	1781	1777	1585	1781	1777	1585
Q Serve(g_s), s	4.8	1.1	0.0	10.6	2.3	0.0	7.6	0.0	0.0	2.6	15.7	0.0
Cycle Q Clear(g_c), s	4.8	1.1	0.0	10.6	2.3	0.0	7.6	0.0	0.0	2.6	15.7	0.0
Prop In Lane	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	144	288		401	217		481	2003		387	1852	
V/C Ratio(X)	0.51	0.12		0.78	0.18		0.49	0.57		0.22	0.41	
Avail Cap(c_a), veh/h	386	770		749	405		632	2003		451	1852	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	2.00	2.00	2.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	52.9	51.2	0.0	51.6	47.9	0.0	11.1	0.0	0.0	12.2	17.5	0.0
Incr Delay (d2), s/veh	3.4	0.2	0.0	4.0	0.5	0.0	0.3	1.2	0.0	0.1	0.7	0.0
Initial Q Delay(d3), s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	2.3	0.5	0.0	4.8	1.1	0.0	2.4	0.3	0.0	1.0	6.3	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d), s/veh	56.2	51.4	0.0	55.6	48.3	0.0	11.4	1.2	0.0	12.3	18.2	0.0
LnGrp LOS	E	D		E	D		B	A		B	B	
Approach Vol, veh/h	108			353			1375			846		
Approach Delay, s/veh	54.7			54.8			2.9			17.6		
Approach LOS	D			D			A			B		
Timer - Assigned Phs	1	2		4	5	6		8				
Phs Duration (G+Y+Rc), s	10.7	73.6		15.7	15.8	68.5		19.9				
Change Period (Y+Rc), s	6.0	6.0		6.0	6.0	6.0		6.0				
Max Green Setting (Gmax), s	9.0	35.0		26.0	20.0	24.0		26.0				
Max Q Clear Time (g_c+I1), s	4.6	2.0		6.8	9.6	17.7		12.6				
Green Ext Time (p_c), s	0.0	14.0		0.4	0.2	3.2		1.3				

Intersection Summary

HCM 7th Control Delay, s/veh	16.5
HCM 7th LOS	B

Notes

User approved pedestrian interval to be less than phase max green.

Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.

Intersection												
Int Delay, s/veh	0.8											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations			↱			↱	↱↑↑↑			↱↑↑↑		
Traffic Vol, veh/h	0	0	31	0	0	69	35	1337	59	39	994	25
Future Vol, veh/h	0	0	31	0	0	69	35	1337	59	39	994	25
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	Stop	-	-	Stop	-	-	None	-	-	None
Storage Length	-	-	0	-	-	0	150	-	-	250	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	0	34	0	0	75	38	1453	64	42	1080	27

Major/Minor	Minor2		Minor1		Major1		Major2	
Conflicting Flow All	-	-	554	-	-	759	1108	0
Stage 1	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-
Critical Hdwy	-	-	7.14	-	-	7.14	5.34	-
Critical Hdwy Stg 1	-	-	-	-	-	-	-	-
Critical Hdwy Stg 2	-	-	-	-	-	-	-	-
Follow-up Hdwy	-	-	3.92	-	-	3.92	3.12	-
Pot Cap-1 Maneuver	0	0	*766	0	0	*707	606	-
Stage 1	0	0	-	0	0	-	-	-
Stage 2	0	0	-	0	0	-	-	-
Platoon blocked, %			0			0	0	-
Mov Cap-1 Maneuver	-	-	*766	-	-	*707	606	-
Mov Cap-2 Maneuver	-	-	-	-	-	-	-	-
Stage 1	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-

Approach	EB	WB	NB	SB
HCM Control Delay, s/v	9.91	10.69	0.28	0.51
HCM LOS	A	B		

Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1WBLn1	SBL	SBT	SBR
Capacity (veh/h)	606	-	-	766	707	455	-
HCM Lane V/C Ratio	0.063	-	-	0.044	0.106	0.093	-
HCM Control Delay (s/veh)	11.3	-	-	9.9	10.7	13.7	-
HCM Lane LOS	B	-	-	A	B	B	-
HCM 95th %tile Q(veh)	0.2	-	-	0.1	0.4	0.3	-

Notes			
~: Volume exceeds capacity	\$: Delay exceeds 300s	+: Computation Not Defined	*: All major volume in platoon

Queues

5: McCaslin Blvd & Dillon Rd

02/05/2025

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Group Flow (vph)	37	37	97	601	75	333	214	1186	554	209	859	47
v/c Ratio	0.21	0.24	0.06	1.00	0.21	0.21	0.94	0.66	0.35	0.70	0.32	0.03
Control Delay (s/veh)	56.8	55.4	0.1	86.8	42.2	0.3	101.6	25.8	0.6	62.8	24.6	0.0
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	56.8	55.4	0.1	86.8	42.2	0.3	101.6	25.8	0.6	62.8	24.6	0.0
Queue Length 50th (ft)	14	27	0	~242	48	0	86	391	0	88	147	0
Queue Length 95th (ft)	32	63	0	#365	93	0	#163	481	0	130	216	0
Internal Link Dist (ft)		457			420			285			453	
Turn Bay Length (ft)	130		150	280		250	450		150	250		100
Base Capacity (vph)	314	465	1583	600	621	1583	228	1794	1583	314	2682	1583
Starvation Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.12	0.08	0.06	1.00	0.12	0.21	0.94	0.66	0.35	0.67	0.32	0.03

Intersection Summary

~ Volume exceeds capacity, queue is theoretically infinite.

Queue shown is maximum after two cycles.

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

HCM 7th Signalized Intersection Summary

5: McCaslin Blvd & Dillon Rd

02/05/2025

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	34	34	89	553	69	306	197	1091	510	192	790	43
Future Volume (veh/h)	34	34	89	553	69	306	197	1091	510	192	790	43
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Lane Width Adj.	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	37	37	0	601	75	0	214	1186	0	209	859	0
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	102	155		605	427		230	1658		262	2428	
Arrive On Green	0.03	0.08	0.00	0.17	0.23	0.00	0.07	0.47	0.00	0.15	0.95	0.00
Sat Flow, veh/h	3456	1870	1585	3456	1870	1585	3456	3554	1585	3456	5106	1585
Grp Volume(v), veh/h	37	37	0	601	75	0	214	1186	0	209	859	0
Grp Sat Flow(s),veh/h/ln	1728	1870	1585	1728	1870	1585	1728	1777	1585	1728	1702	1585
Q Serve(g_s), s	1.3	2.2	0.0	20.8	3.9	0.0	7.4	32.1	0.0	7.0	1.5	0.0
Cycle Q Clear(g_c), s	1.3	2.2	0.0	20.8	3.9	0.0	7.4	32.1	0.0	7.0	1.5	0.0
Prop In Lane	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	102	155		605	427		230	1658		262	2428	
V/C Ratio(X)	0.36	0.24		0.99	0.18		0.93	0.72		0.80	0.35	
Avail Cap(c_a), veh/h	317	468		605	623		230	1658		317	2428	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	2.00	2.00	2.00
Upstream Filter(I)	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	57.1	51.5	0.0	49.4	37.2	0.0	55.7	25.6	0.0	50.0	1.6	0.0
Incr Delay (d2), s/veh	1.6	0.8	0.0	34.9	0.2	0.0	40.0	2.7	0.0	10.4	0.4	0.0
Initial Q Delay(d3), s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	0.6	1.1	0.0	11.7	1.8	0.0	4.5	13.7	0.0	3.2	0.5	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d), s/veh	58.7	52.3	0.0	84.4	37.4	0.0	95.7	28.3	0.0	60.4	2.0	0.0
LnGrp LOS	E	D		F	D		F	C		E	A	
Approach Vol, veh/h	74			676			1400			1068		
Approach Delay, s/veh	55.5			79.2			38.6			13.4		
Approach LOS	E			E			D			B		
Timer - Assigned Phs	1	2	3	4	5	6	7	8				
Phs Duration (G+Y+Rc), s	15.1	62.0	27.0	15.9	14.0	63.1	9.5	33.4				
Change Period (Y+Rc), s	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0				
Max Green Setting (Gmax), s	11.0	34.0	21.0	30.0	8.0	37.0	11.0	40.0				
Max Q Clear Time (g_c+I1), s	9.0	34.1	22.8	4.2	9.4	3.5	3.3	5.9				
Green Ext Time (p_c), s	0.1	0.0	0.0	0.1	0.0	12.6	0.0	0.3				

Intersection Summary

HCM 7th Control Delay, s/veh	39.2
HCM 7th LOS	D

Notes

Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.

Intersection												
Int Delay, s/veh	1.5											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕↕		↗	↕↕			↕			↕	
Traffic Vol, veh/h	0	115	3	38	248	21	0	0	29	13	1	0
Future Vol, veh/h	0	115	3	38	248	21	0	0	29	13	1	0
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	175	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	125	3	41	270	23	0	0	32	14	1	0
Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	292	0	0	128	0	0	345	502	64	426	492	146
Stage 1	-	-	-	-	-	-	127	127	-	364	364	-
Stage 2	-	-	-	-	-	-	218	375	-	63	128	-
Critical Hdwy	4.14	-	-	4.14	-	-	7.54	6.54	6.94	7.54	6.54	6.94
Critical Hdwy Stg 1	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Follow-up Hdwy	2.22	-	-	2.22	-	-	3.52	4.02	3.32	3.52	4.02	3.32
Pot Cap-1 Maneuver	1266	-	-	1455	-	-	585	470	987	512	476	874
Stage 1	-	-	-	-	-	-	864	790	-	628	623	-
Stage 2	-	-	-	-	-	-	764	615	-	941	789	-
Platoon blocked, %		-	-		-	-						
Mov Cap-1 Maneuver	1266	-	-	1455	-	-	567	457	987	482	463	874
Mov Cap-2 Maneuver	-	-	-	-	-	-	567	457	-	482	463	-
Stage 1	-	-	-	-	-	-	864	790	-	610	605	-
Stage 2	-	-	-	-	-	-	741	598	-	911	789	-
Approach	EB			WB			NB			SB		
HCM Control Delay, s/v	0			0.93			8.77			12.74		
HCM LOS							A			B		
Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1				
Capacity (veh/h)	987	1266	-	-	1455	-	-	480				
HCM Lane V/C Ratio	0.032	-	-	-	0.028	-	-	0.032				
HCM Control Delay (s/veh)	8.8	0	-	-	7.5	-	-	12.7				
HCM Lane LOS	A	A	-	-	A	-	-	B				
HCM 95th %tile Q(veh)	0.1	0	-	-	0.1	-	-	0.1				

Intersection

Int Delay, s/veh 2.7

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↔↔			↔↔			↔			↔	
Traffic Vol, veh/h	2	51	0	39	178	22	0	2	55	6	5	2
Future Vol, veh/h	2	51	0	39	178	22	0	2	55	6	5	2
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	2	55	0	42	193	24	0	2	60	7	5	2

Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	217	0	0	55	0	0	244	362	28	323	350	109
Stage 1	-	-	-	-	-	-	60	60	-	290	290	-
Stage 2	-	-	-	-	-	-	184	302	-	33	60	-
Critical Hdwy	4.14	-	-	4.14	-	-	7.54	6.54	6.94	7.54	6.54	6.94
Critical Hdwy Stg 1	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Follow-up Hdwy	2.22	-	-	2.22	-	-	3.52	4.02	3.32	3.52	4.02	3.32
Pot Cap-1 Maneuver	1349	-	-	1548	-	-	690	564	1041	606	573	924
Stage 1	-	-	-	-	-	-	945	844	-	693	671	-
Stage 2	-	-	-	-	-	-	800	663	-	979	844	-
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-
Mov Cap-1 Maneuver	1349	-	-	1548	-	-	660	547	1041	551	555	924
Mov Cap-2 Maneuver	-	-	-	-	-	-	660	547	-	551	555	-
Stage 1	-	-	-	-	-	-	943	843	-	673	651	-
Stage 2	-	-	-	-	-	-	768	643	-	919	843	-

Approach	EB			WB			NB			SB		
HCM Control Delay, s/v	0.3			1.32			8.8			11.26		
HCM LOS							A			B		

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1
Capacity (veh/h)	1009	136	-	-	509	-	-	590
HCM Lane V/C Ratio	0.061	0.002	-	-	0.027	-	-	0.024
HCM Control Delay (s/veh)	8.8	7.7	0	-	7.4	0.2	-	11.3
HCM Lane LOS	A	A	A	-	A	A	-	B
HCM 95th %tile Q(veh)	0.2	0	-	-	0.1	-	-	0.1

HCM 7th TWSC
1: Century PI & Centennial Pkwy

02/05/2025

Intersection													
Int Delay, s/veh	2.7												
Movement	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations													
Traffic Vol, veh/h	1	198	13	17	5	33	6	5	5	7	61	10	5
Future Vol, veh/h	1	198	13	17	5	33	6	5	5	7	61	10	5
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	-	None	-	-	None	-	-	None
Storage Length	100	-	-	-	100	-	-	-	-	-	100	-	-
Veh in Median Storage, #	-	0	-	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	1	215	14	18	5	36	7	5	5	8	66	11	5

Major/Minor	Major1			Major2			Minor1			Minor2			
Conflicting Flow All	42	0	0	-	229	0	0	277	315	222	270	318	39
Stage 1	-	-	-	-	-	-	-	224	224	-	50	87	-
Stage 2	-	-	-	-	-	-	-	52	90	-	220	232	-
Critical Hdwy	4.12	-	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1567	-	-	-	1339	-	-	676	601	817	682	598	1032
Stage 1	-	-	-	-	-	-	-	778	718	-	963	823	-
Stage 2	-	-	-	-	-	-	-	961	820	-	782	713	-
Platoon blocked, %		-	-			-	-						
Mov Cap-1 Maneuver	1567	-	-	~-1	~-1	-	-	660	601	817	669	598	1032
Mov Cap-2 Maneuver	-	-	-	-	-	-	-	660	601	-	669	598	-
Stage 1	-	-	-	-	-	-	-	778	717	-	963	823	-
Stage 2	-	-	-	-	-	-	-	943	820	-	769	712	-

Approach	EB	WB	NB	SB
HCM Control Delay, s/v 0.03			10.32	10.84
HCM LOS			B	B

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1	SBLn2
Capacity (veh/h)	695	1567	-	-	-	-	-	669	695
HCM Lane V/C Ratio	0.027	0.001	-	-	-	-	-	0.099	0.023
HCM Control Delay (s/veh)	10.3	7.3	-	-	-	-	-	11	10.3
HCM Lane LOS	B	A	-	-	-	-	-	B	B
HCM 95th %tile Q(veh)	0.1	0	-	-	-	-	-	0.3	0.1

Notes			
~: Volume exceeds capacity	\$: Delay exceeds 300s	+: Computation Not Defined	*: All major volume in platoon

Intersection

Int Delay, s/veh 2.2

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	3	281	20	25	50	20	5	3	23	35	0	6
Future Vol, veh/h	3	281	20	25	50	20	5	3	23	35	0	6
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	80	-	-	100	-	50	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	3	305	22	27	54	22	5	3	25	38	0	7

Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	76	0	0	327	0	0	432	453	316	422	442	54
Stage 1	-	-	-	-	-	-	323	323	-	109	109	-
Stage 2	-	-	-	-	-	-	109	130	-	314	334	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1523	-	-	1232	-	-	534	502	724	542	509	1013
Stage 1	-	-	-	-	-	-	689	650	-	897	805	-
Stage 2	-	-	-	-	-	-	897	788	-	697	643	-
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-
Mov Cap-1 Maneuver	1523	-	-	1232	-	-	518	490	724	507	497	1013
Mov Cap-2 Maneuver	-	-	-	-	-	-	518	490	-	507	497	-
Stage 1	-	-	-	-	-	-	688	649	-	877	788	-
Stage 2	-	-	-	-	-	-	871	771	-	668	642	-

Approach	EB	WB	NB	SB
HCM Control Delay, s/v 0.07		2.1	10.82	12.16
HCM LOS			B	B

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1
Capacity (veh/h)	652	1523	-	-	1232	-	-	547
HCM Lane V/C Ratio	0.052	0.002	-	-	0.022	-	-	0.081
HCM Control Delay (s/veh)	10.8	7.4	-	-	8	-	-	12.2
HCM Lane LOS	B	A	-	-	A	-	-	B
HCM 95th %tile Q(veh)	0.2	0	-	-	0.1	-	-	0.3

Queues

3: McCaslin Blvd & Centennial Pkwy

02/05/2025

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Group Flow (vph)	55	59	254	332	22	127	37	1093	255	139	1441	45
v/c Ratio	0.35	0.19	0.16	0.67	0.08	0.08	0.21	0.59	0.16	0.48	0.70	0.03
Control Delay (s/veh)	57.6	51.8	0.2	54.9	43.1	0.1	6.3	7.2	0.2	16.1	23.6	0.0
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	57.6	51.8	0.2	54.9	43.1	0.1	6.3	7.2	0.2	16.1	23.6	0.0
Queue Length 50th (ft)	41	22	0	127	15	0	4	66	0	41	450	0
Queue Length 95th (ft)	82	44	0	168	38	0	m6	83	m0	83	#670	0
Internal Link Dist (ft)	360			352			447			338		
Turn Bay Length (ft)	100		100	150			325		125	315		50
Base Capacity (vph)	383	766	1583	743	403	1583	198	1840	1583	307	2054	1583
Starvation Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.14	0.08	0.16	0.45	0.05	0.08	0.19	0.59	0.16	0.45	0.70	0.03

Intersection Summary

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

m Volume for 95th percentile queue is metered by upstream signal.

HCM 7th Signalized Intersection Summary

3: McCaslin Blvd & Centennial Pkwy

02/05/2025

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	51	54	234	305	20	117	34	1006	235	128	1326	41
Future Volume (veh/h)	51	54	234	305	20	117	34	1006	235	128	1326	41
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Lane Width Adj.	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	55	59	0	332	22	0	37	1093	0	139	1441	0
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	145	290		418	226		214	1944		433	2019	
Arrive On Green	0.08	0.08	0.00	0.12	0.12	0.00	0.06	1.00	0.00	0.05	0.57	0.00
Sat Flow, veh/h	1781	3554	1585	3456	1870	1585	1781	3554	1585	1781	3554	1585
Grp Volume(v), veh/h	55	59	0	332	22	0	37	1093	0	139	1441	0
Grp Sat Flow(s),veh/h/ln	1781	1777	1585	1728	1870	1585	1781	1777	1585	1781	1777	1585
Q Serve(g_s), s	3.5	1.9	0.0	11.2	1.3	0.0	1.1	0.0	0.0	4.1	35.3	0.0
Cycle Q Clear(g_c), s	3.5	1.9	0.0	11.2	1.3	0.0	1.1	0.0	0.0	4.1	35.3	0.0
Prop In Lane	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	145	290		418	226		214	1944		433	2019	
V/C Ratio(X)	0.38	0.20		0.79	0.10		0.17	0.56		0.32	0.71	
Avail Cap(c_a), veh/h	386	770		749	405		265	1944		491	2019	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	2.00	2.00	2.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	52.2	51.5	0.0	51.3	46.9	0.0	15.5	0.0	0.0	10.5	18.8	0.0
Incr Delay (d2), s/veh	2.0	0.4	0.0	4.2	0.2	0.0	0.1	1.2	0.0	0.2	2.2	0.0
Initial Q Delay(d3), s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	1.6	0.8	0.0	5.1	0.6	0.0	0.4	0.3	0.0	1.5	14.0	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d), s/veh	54.2	51.9	0.0	55.5	47.1	0.0	15.6	1.2	0.0	10.7	21.0	0.0
LnGrp LOS	D	D		E	D		B	A		B	C	
Approach Vol, veh/h	114			354			1130			1580		
Approach Delay, s/veh	53.0			54.9			1.7			20.1		
Approach LOS	D			D			A			C		
Timer - Assigned Phs	1	2		4	5	6		8				
Phs Duration (G+Y+Rc), s	12.1	71.6		15.8	9.5	74.2		20.5				
Change Period (Y+Rc), s	6.0	6.0		6.0	6.0	6.0		6.0				
Max Green Setting (Gmax), s	10.0	34.0		26.0	7.0	37.0		26.0				
Max Q Clear Time (g_c+I1), s	6.1	2.0		5.5	3.1	37.3		13.2				
Green Ext Time (p_c), s	0.1	13.1		0.5	0.0	0.0		1.3				

Intersection Summary

HCM 7th Control Delay, s/veh	18.6
HCM 7th LOS	B

Notes

User approved pedestrian interval to be less than phase max green.

Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.

Intersection												
Int Delay, s/veh	0.6											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations			↱			↱	↱↑↑↑			↱↑↑↑		
Traffic Vol, veh/h	0	0	39	0	0	59	19	1216	54	54	1783	28
Future Vol, veh/h	0	0	39	0	0	59	19	1216	54	54	1783	28
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	Stop	-	-	Stop	-	-	None	-	-	None
Storage Length	-	-	0	-	-	0	150	-	-	250	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	0	42	0	0	64	21	1322	59	59	1938	30

Major/Minor	Minor2		Minor1		Major1		Major2					
Conflicting Flow All	-	-	984	-	-	690	1968	0	0	1380	0	0
Stage 1	-	-	-	-	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-	-	-	-	-
Critical Hdwy	-	-	7.14	-	-	7.14	5.34	-	-	5.34	-	-
Critical Hdwy Stg 1	-	-	-	-	-	-	-	-	-	-	-	-
Critical Hdwy Stg 2	-	-	-	-	-	-	-	-	-	-	-	-
Follow-up Hdwy	-	-	3.92	-	-	3.92	3.12	-	-	3.12	-	-
Pot Cap-1 Maneuver	0	0	*633	0	0	*722	327	-	-	514	-	-
Stage 1	0	0	-	0	0	-	-	-	-	-	-	-
Stage 2	0	0	-	0	0	-	-	-	-	-	-	-
Platoon blocked, %			0			0	0	-	-	0	-	-
Mov Cap-1 Maneuver	-	-	*633	-	-	*722	327	-	-	514	-	-
Mov Cap-2 Maneuver	-	-	-	-	-	-	-	-	-	-	-	-
Stage 1	-	-	-	-	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-	-	-	-	-

Approach	EB		WB		NB		SB	
HCM Control Delay, s/v	11.1		10.47		0.25		0.37	
HCM LOS	B		B					

Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1WBLn1	SBL	SBT	SBR
Capacity (veh/h)	327	-	-	633	722	514	-
HCM Lane V/C Ratio	0.063	-	-	0.067	0.089	0.114	-
HCM Control Delay (s/veh)	16.8	-	-	11.1	10.5	12.9	-
HCM Lane LOS	C	-	-	B	B	B	-
HCM 95th %tile Q(veh)	0.2	-	-	0.2	0.3	0.4	-

Notes			
~: Volume exceeds capacity	\$: Delay exceeds 300s	+: Computation Not Defined	*: All major volume in platoon

Queues

5: McCaslin Blvd & Dillon Rd

02/05/2025

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Group Flow (vph)	82	101	216	734	87	163	168	1157	603	289	1620	72
v/c Ratio	0.40	0.53	0.14	1.12	0.18	0.10	0.59	0.75	0.38	1.27	0.75	0.05
Control Delay (s/veh)	59.8	60.5	0.2	116.4	37.2	0.1	61.8	32.3	0.7	194.1	34.1	0.0
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	59.8	60.5	0.2	116.4	37.2	0.1	61.8	32.3	0.7	194.1	34.1	0.0
Queue Length 50th (ft)	31	76	0	~336	55	0	65	382	0	~148	316	0
Queue Length 95th (ft)	58	129	0	#457	96	0	102	501	0	#244	443	m0
Internal Link Dist (ft)		457			420			285			453	
Turn Bay Length (ft)	130		150	280		250	450		150	250		100
Base Capacity (vph)	228	465	1583	657	698	1583	314	1551	1583	228	2146	1583
Starvation Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.36	0.22	0.14	1.12	0.12	0.10	0.54	0.75	0.38	1.27	0.75	0.05

Intersection Summary

~ Volume exceeds capacity, queue is theoretically infinite.

Queue shown is maximum after two cycles.

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

m Volume for 95th percentile queue is metered by upstream signal.

HCM 7th Signalized Intersection Summary

5: McCaslin Blvd & Dillon Rd

02/05/2025

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	75	93	199	675	80	150	155	1064	555	266	1490	66
Future Volume (veh/h)	75	93	199	675	80	150	155	1064	555	266	1490	66
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Lane Width Adj.	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	82	101	0	734	87	0	168	1157	0	289	1620	0
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	135	156		662	441		225	1629		230	2348	
Arrive On Green	0.04	0.08	0.00	0.19	0.24	0.00	0.07	0.46	0.00	0.02	0.15	0.00
Sat Flow, veh/h	3456	1870	1585	3456	1870	1585	3456	3554	1585	3456	5106	1585
Grp Volume(v), veh/h	82	101	0	734	87	0	168	1157	0	289	1620	0
Grp Sat Flow(s),veh/h/ln	1728	1870	1585	1728	1870	1585	1728	1777	1585	1728	1702	1585
Q Serve(g_s), s	2.8	6.3	0.0	23.0	4.5	0.0	5.7	31.4	0.0	8.0	36.1	0.0
Cycle Q Clear(g_c), s	2.8	6.3	0.0	23.0	4.5	0.0	5.7	31.4	0.0	8.0	36.1	0.0
Prop In Lane	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	135	156		662	441		225	1629		230	2348	
V/C Ratio(X)	0.61	0.65		1.11	0.20		0.75	0.71		1.25	0.69	
Avail Cap(c_a), veh/h	230	468		662	701		317	1629		230	2348	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.33	0.33	0.33
Upstream Filter(I)	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	56.8	53.3	0.0	48.5	36.7	0.0	55.1	26.1	0.0	58.7	42.8	0.0
Incr Delay (d2), s/veh	3.3	4.5	0.0	68.5	0.2	0.0	4.8	2.7	0.0	144.9	1.7	0.0
Initial Q Delay(d3), s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	1.3	3.1	0.0	16.0	2.0	0.0	2.6	13.4	0.0	8.3	16.8	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d), s/veh	60.0	57.8	0.0	117.0	36.9	0.0	59.9	28.8	0.0	203.6	44.5	0.0
LnGrp LOS	E	E		F	D		E	C		F	D	
Approach Vol, veh/h	183			821			1325			1909		
Approach Delay, s/veh	58.8			108.5			32.7			68.6		
Approach LOS	E			F			C			E		
Timer - Assigned Phs	1	2	3	4	5	6	7	8				
Phs Duration (G+Y+Rc), s	14.0	61.0	29.0	16.0	13.8	61.2	10.7	34.3				
Change Period (Y+Rc), s	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0				
Max Green Setting (Gmax), s	8.0	35.0	23.0	30.0	11.0	32.0	8.0	45.0				
Max Q Clear Time (g_c+I1), s	10.0	33.4	25.0	8.3	7.7	38.1	4.8	6.5				
Green Ext Time (p_c), s	0.0	1.4	0.0	0.4	0.1	0.0	0.0	0.4				
Intersection Summary												
HCM 7th Control Delay, s/veh	64.7											
HCM 7th LOS	E											
Notes												
Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.												

Intersection												
Int Delay, s/veh	3.6											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↔↔		↗	↗↗			↔			↔	
Traffic Vol, veh/h	4	247	9	119	121	19	2	1	108	12	0	2
Future Vol, veh/h	4	247	9	119	121	19	2	1	108	12	0	2
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	175	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	4	268	10	129	132	21	2	1	117	13	0	2

Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	152	0	0	278	0	0	607	693	139	544	688	76
Stage 1	-	-	-	-	-	-	282	282	-	401	401	-
Stage 2	-	-	-	-	-	-	324	411	-	143	287	-
Critical Hdwy	4.14	-	-	4.14	-	-	7.54	6.54	6.94	7.54	6.54	6.94
Critical Hdwy Stg 1	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Follow-up Hdwy	2.22	-	-	2.22	-	-	3.52	4.02	3.32	3.52	4.02	3.32
Pot Cap-1 Maneuver	1426	-	-	1281	-	-	381	365	884	422	368	970
Stage 1	-	-	-	-	-	-	701	676	-	597	600	-
Stage 2	-	-	-	-	-	-	662	593	-	845	673	-
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-
Mov Cap-1 Maneuver	1426	-	-	1281	-	-	340	327	884	327	330	970
Mov Cap-2 Maneuver	-	-	-	-	-	-	340	327	-	327	330	-
Stage 1	-	-	-	-	-	-	699	674	-	537	539	-
Stage 2	-	-	-	-	-	-	594	533	-	729	671	-

Approach	EB			WB			NB			SB		
HCM Control Delay, s/v	0.14			3.73			9.96			15.41		
HCM LOS							A			C		

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1
Capacity (veh/h)	846	53	-	-	1281	-	-	361
HCM Lane V/C Ratio	0.143	0.003	-	-	0.101	-	-	0.042
HCM Control Delay (s/veh)	10	7.5	0	-	8.1	-	-	15.4
HCM Lane LOS	A	A	A	-	A	-	-	C
HCM 95th %tile Q(veh)	0.5	0	-	-	0.3	-	-	0.1

Intersection

Int Delay, s/veh 3.3

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↔			↔			↔			↔	
Traffic Vol, veh/h	0	146	0	29	80	8	1	9	45	31	7	0
Future Vol, veh/h	0	146	0	29	80	8	1	9	45	31	7	0
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	159	0	32	87	9	1	10	49	34	8	0

Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	96	0	0	159	0	0	269	317	79	239	313	48
Stage 1	-	-	-	-	-	-	159	159	-	154	154	-
Stage 2	-	-	-	-	-	-	110	159	-	84	159	-
Critical Hdwy	4.14	-	-	4.14	-	-	7.54	6.54	6.94	7.54	6.54	6.94
Critical Hdwy Stg 1	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Follow-up Hdwy	2.22	-	-	2.22	-	-	3.52	4.02	3.32	3.52	4.02	3.32
Pot Cap-1 Maneuver	1496	-	-	1418	-	-	662	598	965	696	601	1011
Stage 1	-	-	-	-	-	-	828	765	-	832	769	-
Stage 2	-	-	-	-	-	-	883	765	-	914	765	-
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-
Mov Cap-1 Maneuver	1496	-	-	1418	-	-	639	584	965	635	587	1011
Mov Cap-2 Maneuver	-	-	-	-	-	-	639	584	-	635	587	-
Stage 1	-	-	-	-	-	-	828	765	-	813	751	-
Stage 2	-	-	-	-	-	-	854	748	-	857	765	-

Approach	EB			WB			NB			SB		
HCM Control Delay, s/v	0			1.95			9.47			11.16		
HCM LOS							A			B		

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1
Capacity (veh/h)	865	1496	-	-	792	-	-	625
HCM Lane V/C Ratio	0.069	-	-	-	0.022	-	-	0.066
HCM Control Delay (s/veh)	9.5	0	-	-	7.6	0.1	-	11.2
HCM Lane LOS	A	A	-	-	A	A	-	B
HCM 95th %tile Q(veh)	0.2	0	-	-	0.1	-	-	0.2

APPENDIX F – Future (with site development) Synchro Outputs

HCM 7th TWSC
1: Century PI & Centennial Pkwy

02/05/2025

Intersection													
Int Delay, s/veh	1.4												
Movement	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations													
Traffic Vol, veh/h	0	45	11	11	15	128	78	10	12	11	6	5	2
Future Vol, veh/h	0	45	11	11	15	128	78	10	12	11	6	5	2
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	-	None	-	-	None	-	-	None
Storage Length	100	-	-	-	100	-	-	-	-	-	100	-	-
Veh in Median Storage, #	-	0	-	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	49	12	12	16	139	85	11	13	12	7	5	2
Major/Minor	Major1			Major2			Minor1			Minor2			
Conflicting Flow All	224	0	0	-	61	0	0	229	335	55	270	299	182
Stage 1	-	-	-	-	-	-	-	55	55	-	214	238	-
Stage 2	-	-	-	-	-	-	-	174	280	-	55	61	-
Critical Hdwy	4.12	-	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1345	-	-	-	1542	-	-	726	585	1012	683	613	861
Stage 1	-	-	-	-	-	-	-	957	849	-	788	708	-
Stage 2	-	-	-	-	-	-	-	827	679	-	957	844	-
Platoon blocked, %		-	-			-	-						
Mov Cap-1 Maneuver	1345	-	-	~ -2	~ -2	-	-	717	585	1012	660	613	861
Mov Cap-2 Maneuver	-	-	-	-	-	-	-	717	585	-	660	613	-
Stage 1	-	-	-	-	-	-	-	957	849	-	788	708	-
Stage 2	-	-	-	-	-	-	-	819	679	-	931	844	-
Approach	EB			WB			NB			SB			
HCM Control Delay, s/v	0						10.2			10.48			
HCM LOS							B			B			
Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1	SBLn2				
Capacity (veh/h)	728	1345	-	-	~	-	-	660	668				
HCM Lane V/C Ratio	0.049	-	-	-	-	-	-	0.01	0.011				
HCM Control Delay (s/veh)	10.2	0	-	-	-	-	-	10.5	10.4				
HCM Lane LOS	B	A	-	-	-	-	-	B	B				
HCM 95th %tile Q(veh)	0.2	0	-	-	-	-	-	0	0				
Notes													
~: Volume exceeds capacity		\$: Delay exceeds 300s			+: Computation Not Defined				*: All major volume in platoon				

Intersection												
Int Delay, s/veh	4.5											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	7	79	8	57	194	39	14	3	89	51	1	24
Future Vol, veh/h	7	79	8	57	194	39	14	3	89	51	1	24
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	80	-	-	100	-	50	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	8	86	9	62	211	42	15	3	97	55	1	26
Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	253	0	0	95	0	0	441	483	90	437	445	211
Stage 1	-	-	-	-	-	-	105	105	-	335	335	-
Stage 2	-	-	-	-	-	-	335	377	-	103	110	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1312	-	-	1499	-	-	527	484	968	529	508	829
Stage 1	-	-	-	-	-	-	900	808	-	679	643	-
Stage 2	-	-	-	-	-	-	679	616	-	903	804	-
Platoon blocked, %		-	-		-	-						
Mov Cap-1 Maneuver	1312	-	-	1499	-	-	485	461	968	451	484	829
Mov Cap-2 Maneuver	-	-	-	-	-	-	485	461	-	451	484	-
Stage 1	-	-	-	-	-	-	895	803	-	651	616	-
Stage 2	-	-	-	-	-	-	629	590	-	805	800	-
Approach	EB			WB			NB			SB		
HCM Control Delay, s/v	0.58			1.47			10.02			13.09		
HCM LOS							B			B		
Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1				
Capacity (veh/h)	832	1312	-	-	1499	-	-	527				
HCM Lane V/C Ratio	0.138	0.006	-	-	0.041	-	-	0.157				
HCM Control Delay (s/veh)	10	7.8	-	-	7.5	-	-	13.1				
HCM Lane LOS	B	A	-	-	A	-	-	B				
HCM 95th %tile Q(veh)	0.5	0	-	-	0.1	-	-	0.6				

Queues

3: McCaslin Blvd & Centennial Pkwy

02/05/2025

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Group Flow (vph)	129	47	62	273	46	117	193	923	126	70	646	76
v/c Ratio	0.60	0.11	0.04	0.62	0.19	0.07	0.43	0.51	0.08	0.23	0.40	0.05
Control Delay (s/veh)	60.5	45.5	0.1	55.4	47.2	0.1	6.4	10.6	0.1	14.4	24.6	0.1
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	60.5	45.5	0.1	55.4	47.2	0.1	6.4	10.6	0.1	14.4	24.6	0.1
Queue Length 50th (ft)	96	17	0	104	32	0	16	131	0	21	167	0
Queue Length 95th (ft)	154	34	0	143	66	0	29	407	0	51	278	0
Internal Link Dist (ft)	360			352			447			338		
Turn Bay Length (ft)	100		100	150			325		125	315		50
Base Capacity (vph)	383	766	1583	743	403	1583	543	1811	1583	343	1617	1583
Starvation Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.34	0.06	0.04	0.37	0.11	0.07	0.36	0.51	0.08	0.20	0.40	0.05
Intersection Summary												

HCM 7th Signalized Intersection Summary

3: McCaslin Blvd & Centennial Pkwy

02/05/2025

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	119	43	57	251	42	108	178	849	116	64	594	70
Future Volume (veh/h)	119	43	57	251	42	108	178	849	116	64	594	70
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Lane Width Adj.	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	129	47	0	273	46	0	193	923	0	70	646	0
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	165	328		359	194		521	2011		451	1900	
Arrive On Green	0.09	0.09	0.00	0.10	0.10	0.00	0.14	1.00	0.00	0.04	0.53	0.00
Sat Flow, veh/h	1781	3554	1585	3456	1870	1585	1781	3554	1585	1781	3554	1585
Grp Volume(v), veh/h	129	47	0	273	46	0	193	923	0	70	646	0
Grp Sat Flow(s),veh/h/ln	1781	1777	1585	1728	1870	1585	1781	1777	1585	1781	1777	1585
Q Serve(g_s), s	8.5	1.5	0.0	9.2	2.7	0.0	6.1	0.0	0.0	2.1	12.4	0.0
Cycle Q Clear(g_c), s	8.5	1.5	0.0	9.2	2.7	0.0	6.1	0.0	0.0	2.1	12.4	0.0
Prop In Lane	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	165	328		359	194		521	2011		451	1900	
V/C Ratio(X)	0.78	0.14		0.76	0.24		0.37	0.46		0.16	0.34	
Avail Cap(c_a), veh/h	386	770		749	405		695	2011		517	1900	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	2.00	2.00	2.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	53.3	50.1	0.0	52.3	49.4	0.0	10.6	0.0	0.0	11.4	15.9	0.0
Incr Delay (d2), s/veh	9.4	0.2	0.0	4.0	0.7	0.0	0.2	0.8	0.0	0.1	0.5	0.0
Initial Q Delay(d3), s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	4.2	0.7	0.0	4.2	1.3	0.0	2.0	0.2	0.0	0.8	4.9	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d), s/veh	62.7	50.3	0.0	56.3	50.1	0.0	10.8	0.8	0.0	11.5	16.4	0.0
LnGrp LOS	E	D		E	D		B	A		B	B	
Approach Vol, veh/h	176			319			1116			716		
Approach Delay, s/veh	59.4			55.4			2.5			15.9		
Approach LOS	E			E			A			B		
Timer - Assigned Phs	1	2		4	5	6		8				
Phs Duration (G+Y+Rc), s	10.5	73.9		17.1	14.3	70.2		18.5				
Change Period (Y+Rc), s	6.0	6.0		6.0	6.0	6.0		6.0				
Max Green Setting (Gmax), s	9.0	35.0		26.0	20.0	24.0		26.0				
Max Q Clear Time (g_c+I1), s	4.1	2.0		10.5	8.1	14.4		11.2				
Green Ext Time (p_c), s	0.0	10.6		0.6	0.2	3.7		1.3				

Intersection Summary

HCM 7th Control Delay, s/veh	18.2
HCM 7th LOS	B

Notes

User approved pedestrian interval to be less than phase max green.

Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.

Intersection												
Int Delay, s/veh	1.5											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations			↱			↱	↱↑↑↑			↱↑↑↑		
Traffic Vol, veh/h	0	0	98	0	0	69	112	1074	59	39	795	68
Future Vol, veh/h	0	0	98	0	0	69	112	1074	59	39	795	68
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	Stop	-	-	Stop	-	-	None	-	-	None
Storage Length	-	-	0	-	-	0	150	-	-	250	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	0	107	0	0	75	122	1167	64	42	864	74

Major/Minor	Minor2		Minor1		Major1		Major2					
Conflicting Flow All	-	-	469	-	-	616	938	0	0	1232	0	0
Stage 1	-	-	-	-	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-	-	-	-	-
Critical Hdwy	-	-	7.14	-	-	7.14	5.34	-	-	5.34	-	-
Critical Hdwy Stg 1	-	-	-	-	-	-	-	-	-	-	-	-
Critical Hdwy Stg 2	-	-	-	-	-	-	-	-	-	-	-	-
Follow-up Hdwy	-	-	3.92	-	-	3.92	3.12	-	-	3.12	-	-
Pot Cap-1 Maneuver	0	0	*796	0	0	*752	660	-	-	551	-	-
Stage 1	0	0	-	0	0	-	-	-	-	-	-	-
Stage 2	0	0	-	0	0	-	-	-	-	-	-	-
Platoon blocked, %			0			0	0	-	-	0	-	-
Mov Cap-1 Maneuver	-	-	*796	-	-	*752	660	-	-	551	-	-
Mov Cap-2 Maneuver	-	-	-	-	-	-	-	-	-	-	-	-
Stage 1	-	-	-	-	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-	-	-	-	-

Approach	EB	WB	NB	SB
HCM Control Delay, s/v10.22		10.32	1.05	0.52
HCM LOS	B	B		

Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1WBLn1	SBL	SBT	SBR
Capacity (veh/h)	660	-	-	796	752	551	-
HCM Lane V/C Ratio	0.184	-	-	0.134	0.1	0.077	-
HCM Control Delay (s/veh)	11.7	-	-	10.2	10.3	12.1	-
HCM Lane LOS	B	-	-	B	B	B	-
HCM 95th %tile Q(veh)	0.7	-	-	0.5	0.3	0.2	-

Notes			
~: Volume exceeds capacity	\$: Delay exceeds 300s	+: Computation Not Defined	*: All major volume in platoon

Queues

5: McCaslin Blvd & Dillon Rd

02/05/2025

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Group Flow (vph)	33	49	107	498	87	302	240	1018	459	190	742	38
v/c Ratio	0.19	0.31	0.07	0.87	0.22	0.19	1.05	0.59	0.29	0.65	0.29	0.02
Control Delay (s/veh)	56.6	56.7	0.1	64.9	40.5	0.3	127.6	25.4	0.5	61.6	24.6	0.0
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	56.6	56.7	0.1	64.9	40.5	0.3	127.6	25.4	0.5	61.6	24.6	0.0
Queue Length 50th (ft)	12	36	0	193	56	0	~104	313	0	79	128	0
Queue Length 95th (ft)	29	76	0	#273	104	0	#189	396	0	120	186	0
Internal Link Dist (ft)		457			420			285			453	
Turn Bay Length (ft)	130		150	280		250	450		150	250		100
Base Capacity (vph)	314	465	1583	600	621	1583	228	1725	1583	314	2574	1583
Starvation Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.11	0.11	0.07	0.83	0.14	0.19	1.05	0.59	0.29	0.61	0.29	0.02

Intersection Summary

~ Volume exceeds capacity, queue is theoretically infinite.

Queue shown is maximum after two cycles.

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

HCM 7th Signalized Intersection Summary

5: McCaslin Blvd & Dillon Rd

02/05/2025

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	30	45	98	458	80	278	221	937	422	175	683	35
Future Volume (veh/h)	30	45	98	458	80	278	221	937	422	175	683	35
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Lane Width Adj.	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	33	49	0	498	87	0	240	1018	0	190	742	0
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	96	155		556	404		230	1726		244	2499	
Arrive On Green	0.03	0.08	0.00	0.16	0.22	0.00	0.07	0.49	0.00	0.14	0.98	0.00
Sat Flow, veh/h	3456	1870	1585	3456	1870	1585	3456	3554	1585	3456	5106	1585
Grp Volume(v), veh/h	33	49	0	498	87	0	240	1018	0	190	742	0
Grp Sat Flow(s),veh/h/ln	1728	1870	1585	1728	1870	1585	1728	1777	1585	1728	1702	1585
Q Serve(g_s), s	1.1	3.0	0.0	17.0	4.6	0.0	8.0	24.8	0.0	6.4	0.5	0.0
Cycle Q Clear(g_c), s	1.1	3.0	0.0	17.0	4.6	0.0	8.0	24.8	0.0	6.4	0.5	0.0
Prop In Lane	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	96	155		556	404		230	1726		244	2499	
V/C Ratio(X)	0.34	0.32		0.90	0.22		1.04	0.59		0.78	0.30	
Avail Cap(c_a), veh/h	317	468		605	623		230	1726		317	2499	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	2.00	2.00	2.00
Upstream Filter(I)	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	57.3	51.8	0.0	49.4	38.7	0.0	56.0	22.3	0.0	50.6	0.7	0.0
Incr Delay (d2), s/veh	1.6	1.1	0.0	14.9	0.3	0.0	70.6	1.5	0.0	7.9	0.3	0.0
Initial Q Delay(d3), s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	0.5	1.4	0.0	8.3	2.1	0.0	5.7	10.4	0.0	2.8	0.2	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d), s/veh	58.8	53.0	0.0	64.3	38.9	0.0	126.6	23.7	0.0	58.5	1.0	0.0
LnGrp LOS	E	D		E	D		F	C		E	A	
Approach Vol, veh/h	82			585			1258			932		
Approach Delay, s/veh	55.3			60.5			43.4			12.7		
Approach LOS	E			E			D			B		
Timer - Assigned Phs	1	2	3	4	5	6	7	8				
Phs Duration (G+Y+Rc), s	14.5	64.3	25.3	16.0	14.0	64.7	9.3	31.9				
Change Period (Y+Rc), s	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0				
Max Green Setting (Gmax), s	11.0	34.0	21.0	30.0	8.0	37.0	11.0	40.0				
Max Q Clear Time (g_c+l1), s	8.4	26.8	19.0	5.0	10.0	2.5	3.1	6.6				
Green Ext Time (p_c), s	0.1	5.2	0.3	0.2	0.0	10.7	0.0	0.4				
Intersection Summary												
HCM 7th Control Delay, s/veh				37.2								
HCM 7th LOS				D								
Notes												
Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.												

Intersection

Int Delay, s/veh 2.3

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↔↔		↗	↗↗			↔			↔	
Traffic Vol, veh/h	0	98	3	32	208	94	0	0	16	59	1	0
Future Vol, veh/h	0	98	3	32	208	94	0	0	16	59	1	0
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	175	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	107	3	35	226	102	0	0	17	64	1	0

Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	328	0	0	110	0	0	291	506	55	400	457	164
Stage 1	-	-	-	-	-	-	108	108	-	347	347	-
Stage 2	-	-	-	-	-	-	183	398	-	53	110	-
Critical Hdwy	4.14	-	-	4.14	-	-	7.54	6.54	6.94	7.54	6.54	6.94
Critical Hdwy Stg 1	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Follow-up Hdwy	2.22	-	-	2.22	-	-	3.52	4.02	3.32	3.52	4.02	3.32
Pot Cap-1 Maneuver	1228	-	-	1478	-	-	639	468	1000	535	499	852
Stage 1	-	-	-	-	-	-	886	805	-	642	633	-
Stage 2	-	-	-	-	-	-	801	601	-	953	804	-
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-
Mov Cap-1 Maneuver	1228	-	-	1478	-	-	622	457	1000	513	487	852
Mov Cap-2 Maneuver	-	-	-	-	-	-	622	457	-	513	487	-
Stage 1	-	-	-	-	-	-	886	805	-	627	619	-
Stage 2	-	-	-	-	-	-	781	587	-	936	804	-

Approach	EB	WB	NB	SB
HCM Control Delay, s/v	0	0.72	8.66	13.05
HCM LOS			A	B

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1
Capacity (veh/h)	1000	1228	-	-	1478	-	-	513
HCM Lane V/C Ratio	0.017	-	-	-	0.024	-	-	0.127
HCM Control Delay (s/veh)	8.7	0	-	-	7.5	-	-	13
HCM Lane LOS	A	A	-	-	A	-	-	B
HCM 95th %tile Q(veh)	0.1	0	-	-	0.1	-	-	0.4

Intersection

Int Delay, s/veh 3.4

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↔↔			↔↔			↔			↔	
Traffic Vol, veh/h	2	26	0	39	126	34	0	2	55	14	5	2
Future Vol, veh/h	2	26	0	39	126	34	0	2	55	14	5	2
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	2	28	0	42	137	37	0	2	60	15	5	2

Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	174	0	0	28	0	0	189	291	14	260	273	87
Stage 1	-	-	-	-	-	-	33	33	-	240	240	-
Stage 2	-	-	-	-	-	-	156	259	-	20	33	-
Critical Hdwy	4.14	-	-	4.14	-	-	7.54	6.54	6.94	7.54	6.54	6.94
Critical Hdwy Stg 1	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Follow-up Hdwy	2.22	-	-	2.22	-	-	3.52	4.02	3.32	3.52	4.02	3.32
Pot Cap-1 Maneuver	1400	-	-	1583	-	-	754	618	1062	672	633	954
Stage 1	-	-	-	-	-	-	979	867	-	742	705	-
Stage 2	-	-	-	-	-	-	831	692	-	996	867	-
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-
Mov Cap-1 Maneuver	1400	-	-	1583	-	-	724	600	1062	613	614	954
Mov Cap-2 Maneuver	-	-	-	-	-	-	724	600	-	613	614	-
Stage 1	-	-	-	-	-	-	978	866	-	721	686	-
Stage 2	-	-	-	-	-	-	799	673	-	937	866	-

Approach	EB			WB			NB			SB		
HCM Control Delay, s/v	0.55			1.52			8.7			10.88		
HCM LOS							A			B		

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1
Capacity (veh/h)	1034	257	-	-	544	-	-	635
HCM Lane V/C Ratio	0.06	0.002	-	-	0.027	-	-	0.036
HCM Control Delay (s/veh)	8.7	7.6	0	-	7.3	0.1	-	10.9
HCM Lane LOS	A	A	A	-	A	A	-	B
HCM 95th %tile Q(veh)	0.2	0	-	-	0.1	-	-	0.1

HCM 7th TWSC
1: Century PI & Centennial Pkwy

02/05/2025

Intersection													
Int Delay, s/veh	3.5												
Movement	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations													
Traffic Vol, veh/h	1	148	22	17	24	26	6	14	5	26	61	10	5
Future Vol, veh/h	1	148	22	17	24	26	6	14	5	26	61	10	5
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	-	None	-	-	None	-	-	None
Storage Length	100	-	-	-	100	-	-	-	-	-	100	-	-
Veh in Median Storage, #	-	0	-	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	1	161	24	18	26	28	7	15	5	28	66	11	5

Major/Minor	Major1			Major2			Minor1			Minor2			
Conflicting Flow All	35	0	0	-	185	0	0	261	299	173	249	308	32
Stage 1	-	-	-	-	-	-	-	175	175	-	84	121	-
Stage 2	-	-	-	-	-	-	-	86	124	-	166	187	-
Critical Hdwy	4.12	-	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1577	-	-	-	1390	-	-	692	613	871	704	606	1042
Stage 1	-	-	-	-	-	-	-	827	754	-	924	796	-
Stage 2	-	-	-	-	-	-	-	922	793	-	836	745	-
Platoon blocked, %		-	-			-	-						
Mov Cap-1 Maneuver	1577	-	-	~-2	~-2	-	-	676	613	871	675	606	1042
Mov Cap-2 Maneuver	-	-	-	-	-	-	-	676	613	-	675	606	-
Stage 1	-	-	-	-	-	-	-	826	754	-	924	796	-
Stage 2	-	-	-	-	-	-	-	905	793	-	803	745	-

Approach	EB	WB	NB	SB
HCM Control Delay, s/v 0.04			10.02	10.78
HCM LOS			B	B

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1	SBLn2
Capacity (veh/h)	766	1577	-	-	~	-	-	675	704
HCM Lane V/C Ratio	0.064	0.001	-	-	-	-	-	0.098	0.023
HCM Control Delay (s/veh)	10	7.3	-	-	-	-	-	10.9	10.2
HCM Lane LOS	B	A	-	-	-	-	-	B	B
HCM 95th %tile Q(veh)	0.2	0	-	-	-	-	-	0.3	0.1

Notes			
~: Volume exceeds capacity	\$: Delay exceeds 300s	+: Computation Not Defined	*: All major volume in platoon

Intersection												
Int Delay, s/veh	6.4											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	3	241	29	114	53	20	14	3	215	35	0	6
Future Vol, veh/h	3	241	29	114	53	20	14	3	215	35	0	6
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	80	-	-	100	-	50	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	3	262	32	124	58	22	15	3	234	38	0	7
Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	79	0	0	293	0	0	590	611	278	576	605	58
Stage 1	-	-	-	-	-	-	284	284	-	305	305	-
Stage 2	-	-	-	-	-	-	305	327	-	270	300	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1519	-	-	1268	-	-	419	408	761	429	412	1009
Stage 1	-	-	-	-	-	-	723	676	-	704	662	-
Stage 2	-	-	-	-	-	-	704	648	-	736	666	-
Platoon blocked, %		-	-		-	-						
Mov Cap-1 Maneuver	1519	-	-	1268	-	-	375	368	761	265	371	1009
Mov Cap-2 Maneuver	-	-	-	-	-	-	375	368	-	265	371	-
Stage 1	-	-	-	-	-	-	721	675	-	635	597	-
Stage 2	-	-	-	-	-	-	631	584	-	506	664	-
Approach	EB			WB			NB			SB		
HCM Control Delay, s/v	0.08			4.97			12.88			19.23		
HCM LOS							B			C		
Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1				
Capacity (veh/h)	707	1519	-	-	1268	-	-	297				
HCM Lane V/C Ratio	0.356	0.002	-	-	0.098	-	-	0.15				
HCM Control Delay (s/veh)	12.9	7.4	-	-	8.1	-	-	19.2				
HCM Lane LOS	B	A	-	-	A	-	-	C				
HCM 95th %tile Q(veh)	1.6	0	-	-	0.3	-	-	0.5				

Queues

3: McCaslin Blvd & Centennial Pkwy

02/05/2025

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Group Flow (vph)	234	90	210	295	38	105	32	820	210	115	1198	134
v/c Ratio	0.76	0.15	0.13	0.64	0.15	0.07	0.18	0.55	0.13	0.38	0.71	0.08
Control Delay (s/veh)	62.5	41.0	0.2	55.2	45.7	0.1	9.7	12.7	0.2	19.2	30.3	0.1
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	62.5	41.0	0.2	55.2	45.7	0.1	9.7	12.7	0.2	19.2	30.3	0.1
Queue Length 50th (ft)	173	31	0	112	26	0	4	65	0	42	404	0
Queue Length 95th (ft)	253	53	0	153	58	0	m8	256	0	88	#627	0
Internal Link Dist (ft)		360			352			447			338	
Turn Bay Length (ft)	100		100	150			325		125	315		50
Base Capacity (vph)	383	766	1583	743	403	1583	198	1495	1583	327	1695	1583
Starvation Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.61	0.12	0.13	0.40	0.09	0.07	0.16	0.55	0.13	0.35	0.71	0.08

Intersection Summary

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

m Volume for 95th percentile queue is metered by upstream signal.

HCM 7th Signalized Intersection Summary

3: McCaslin Blvd & Centennial Pkwy

02/05/2025

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	215	83	193	271	35	97	29	754	193	106	1102	123
Future Volume (veh/h)	215	83	193	271	35	97	29	754	193	106	1102	123
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Lane Width Adj.	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	234	90	0	295	38	0	32	820	0	115	1198	0
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	272	543		381	206		230	1737		465	1811	
Arrive On Green	0.15	0.15	0.00	0.11	0.11	0.00	0.05	0.98	0.00	0.05	0.51	0.00
Sat Flow, veh/h	1781	3554	1585	3456	1870	1585	1781	3554	1585	1781	3554	1585
Grp Volume(v), veh/h	234	90	0	295	38	0	32	820	0	115	1198	0
Grp Sat Flow(s),veh/h/ln	1781	1777	1585	1728	1870	1585	1781	1777	1585	1781	1777	1585
Q Serve(g_s), s	15.4	2.6	0.0	10.0	2.2	0.0	1.1	1.1	0.0	3.8	29.9	0.0
Cycle Q Clear(g_c), s	15.4	2.6	0.0	10.0	2.2	0.0	1.1	1.1	0.0	3.8	29.9	0.0
Prop In Lane	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	272	543		381	206		230	1737		465	1811	
V/C Ratio(X)	0.86	0.17		0.77	0.18		0.14	0.47		0.25	0.66	
Avail Cap(c_a), veh/h	386	770		749	405		285	1737		528	1811	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	2.00	2.00	2.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	49.6	44.2	0.0	51.9	48.5	0.0	17.2	0.7	0.0	13.8	21.8	0.0
Incr Delay (d2), s/veh	13.9	0.2	0.0	4.0	0.5	0.0	0.1	0.9	0.0	0.1	1.9	0.0
Initial Q Delay(d3), s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	7.8	1.2	0.0	4.5	1.1	0.0	0.4	0.5	0.0	1.5	12.2	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d), s/veh	63.4	44.4	0.0	56.0	49.0	0.0	17.3	1.6	0.0	13.9	23.7	0.0
LnGrp LOS	E	D		E	D		B	A		B	C	
Approach Vol, veh/h	324			333			852			1313		
Approach Delay, s/veh	58.1			55.2			2.2			22.8		
Approach LOS	E			E			A			C		
Timer - Assigned Phs	1	2		4	5	6		8				
Phs Duration (G+Y+Rc), s	11.8	64.7		24.3	9.3	67.1		19.2				
Change Period (Y+Rc), s	6.0	6.0		6.0	6.0	6.0		6.0				
Max Green Setting (Gmax), s	10.0	34.0		26.0	7.0	37.0		26.0				
Max Q Clear Time (g_c+l1), s	5.8	3.1		17.4	3.1	31.9		12.0				
Green Ext Time (p_c), s	0.0	9.0		1.0	0.0	3.7		1.3				

Intersection Summary

HCM 7th Control Delay, s/veh	24.5
HCM 7th LOS	C

Notes

User approved pedestrian interval to be less than phase max green.

Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.

Intersection												
Int Delay, s/veh	2.4											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations			↗			↗	↗ ↑ ↑ ↑			↗ ↑ ↑ ↑		
Traffic Vol, veh/h	0	0	203	0	0	59	164	917	54	54	1396	116
Future Vol, veh/h	0	0	203	0	0	59	164	917	54	54	1396	116
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	Stop	-	-	Stop	-	-	None	-	-	None
Storage Length	-	-	0	-	-	0	150	-	-	250	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	0	221	0	0	64	178	997	59	59	1517	126

Major/Minor	Minor2		Minor1		Major1		Major2					
Conflicting Flow All	-	-	822	-	-	528	1643	0	0	1055	0	0
Stage 1	-	-	-	-	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-	-	-	-	-
Critical Hdwy	-	-	7.14	-	-	7.14	5.34	-	-	5.34	-	-
Critical Hdwy Stg 1	-	-	-	-	-	-	-	-	-	-	-	-
Critical Hdwy Stg 2	-	-	-	-	-	-	-	-	-	-	-	-
Follow-up Hdwy	-	-	3.92	-	-	3.92	3.12	-	-	3.12	-	-
Pot Cap-1 Maneuver	0	0	*692	0	0	*781	406	-	-	608	-	-
Stage 1	0	0	-	0	0	-	-	-	-	-	-	-
Stage 2	0	0	-	0	0	-	-	-	-	-	-	-
Platoon blocked, %			0			0	0	-	-	0	-	-
Mov Cap-1 Maneuver	-	-	*692	-	-	*781	406	-	-	608	-	-
Mov Cap-2 Maneuver	-	-	-	-	-	-	-	-	-	-	-	-
Stage 1	-	-	-	-	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-	-	-	-	-

Approach	EB		WB		NB		SB	
HCM Control Delay, s/v12.61			10.02		2.98		0.4	
HCM LOS	B		B					

Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1	WBLn1	SBL	SBT	SBR
Capacity (veh/h)	406	-	-	692	781	608	-	-
HCM Lane V/C Ratio	0.439	-	-	0.319	0.082	0.097	-	-
HCM Control Delay (s/veh)	20.6	-	-	12.6	10	11.6	-	-
HCM Lane LOS	C	-	-	B	B	B	-	-
HCM 95th %tile Q(veh)	2.2	-	-	1.4	0.3	0.3	-	-

Notes			
~: Volume exceeds capacity	\$: Delay exceeds 300s	+: Computation Not Defined	*: All major volume in platoon

Queues

5: McCaslin Blvd & Dillon Rd

02/05/2025

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Group Flow (vph)	84	125	267	608	112	176	277	974	499	278	1403	57
v/c Ratio	0.41	0.59	0.17	0.94	0.23	0.11	0.88	0.64	0.32	1.22	0.68	0.04
Control Delay (s/veh)	60.0	61.3	0.2	71.0	36.6	0.1	82.2	29.9	0.5	177.2	37.6	0.0
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	60.0	61.3	0.2	71.0	36.6	0.1	82.2	29.9	0.5	177.2	37.6	0.0
Queue Length 50th (ft)	32	94	0	240	71	0	111	306	0	~139	324	0
Queue Length 95th (ft)	59	151	0	#347	116	0	#188	408	0	#230	456	m0
Internal Link Dist (ft)		457			420			285			453	
Turn Bay Length (ft)	130		150	280		250	450		150	250		100
Base Capacity (vph)	228	465	1583	657	698	1583	314	1521	1583	228	2058	1583
Starvation Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.37	0.27	0.17	0.93	0.16	0.11	0.88	0.64	0.32	1.22	0.68	0.04

Intersection Summary

~ Volume exceeds capacity, queue is theoretically infinite.

Queue shown is maximum after two cycles.

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

m Volume for 95th percentile queue is metered by upstream signal.

HCM 7th Signalized Intersection Summary

5: McCaslin Blvd & Dillon Rd

02/05/2025

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	77	115	246	559	103	162	255	896	459	256	1291	52
Future Volume (veh/h)	77	115	246	559	103	162	255	896	459	256	1291	52
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Lane Width Adj.	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	84	125	0	608	112	0	277	974	0	278	1403	0
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	135	162		657	445		317	1622		230	2203	
Arrive On Green	0.04	0.09	0.00	0.19	0.24	0.00	0.09	0.46	0.00	0.02	0.14	0.00
Sat Flow, veh/h	3456	1870	1585	3456	1870	1585	3456	3554	1585	3456	5106	1585
Grp Volume(v), veh/h	84	125	0	608	112	0	277	974	0	278	1403	0
Grp Sat Flow(s),veh/h/ln	1728	1870	1585	1728	1870	1585	1728	1777	1585	1728	1702	1585
Q Serve(g_s), s	2.9	7.8	0.0	20.8	5.8	0.0	9.5	24.6	0.0	8.0	31.1	0.0
Cycle Q Clear(g_c), s	2.9	7.8	0.0	20.8	5.8	0.0	9.5	24.6	0.0	8.0	31.1	0.0
Prop In Lane	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	135	162		657	445		317	1622		230	2203	
V/C Ratio(X)	0.62	0.77		0.93	0.25		0.87	0.60		1.21	0.64	
Avail Cap(c_a), veh/h	230	468		662	701		317	1622		230	2203	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.33	0.33	0.33
Upstream Filter(I)	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	56.8	53.6	0.0	47.8	37.1	0.0	53.8	24.4	0.0	58.7	42.6	0.0
Incr Delay (d2), s/veh	3.4	7.5	0.0	18.8	0.3	0.0	22.4	1.7	0.0	126.5	1.4	0.0
Initial Q Delay(d3), s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	1.3	4.0	0.0	10.4	2.7	0.0	5.1	10.5	0.0	7.7	14.5	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d), s/veh	60.2	61.1	0.0	66.6	37.4	0.0	76.2	26.1	0.0	185.2	44.0	0.0
LnGrp LOS	E	E		E	D		E	C		F	D	
Approach Vol, veh/h	209				720				1251			
Approach Delay, s/veh	60.7				62.0				37.2			
Approach LOS	E				E				D			
Timer - Assigned Phs	1	2	3	4	5	6	7	8				
Phs Duration (G+Y+Rc), s	14.0	60.8	28.8	16.4	17.0	57.8	10.7	34.5				
Change Period (Y+Rc), s	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0				
Max Green Setting (Gmax), s	8.0	35.0	23.0	30.0	11.0	32.0	8.0	45.0				
Max Q Clear Time (g_c+I1), s	10.0	26.6	22.8	9.8	11.5	33.1	4.9	7.8				
Green Ext Time (p_c), s	0.0	5.7	0.1	0.6	0.0	0.0	0.0	0.6				

Intersection Summary

HCM 7th Control Delay, s/veh	56.2
HCM 7th LOS	E

Notes

Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.

Intersection												
Int Delay, s/veh	6											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↔		↔	↔			↔		↔		
Traffic Vol, veh/h	4	206	9	100	91	177	2	1	96	136	0	2
Future Vol, veh/h	4	206	9	100	91	177	2	1	96	136	0	2
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	175	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	4	224	10	109	99	192	2	1	104	148	0	2

Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	291	0	0	234	0	0	504	746	117	534	655	146
Stage 1	-	-	-	-	-	-	237	237	-	413	413	-
Stage 2	-	-	-	-	-	-	267	509	-	121	242	-
Critical Hdwy	4.14	-	-	4.14	-	-	7.54	6.54	6.94	7.54	6.54	6.94
Critical Hdwy Stg 1	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Follow-up Hdwy	2.22	-	-	2.22	-	-	3.52	4.02	3.32	3.52	4.02	3.32
Pot Cap-1 Maneuver	1267	-	-	1331	-	-	450	340	913	429	384	875
Stage 1	-	-	-	-	-	-	744	707	-	587	592	-
Stage 2	-	-	-	-	-	-	716	537	-	870	704	-
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-
Mov Cap-1 Maneuver	1267	-	-	1331	-	-	411	311	913	347	352	875
Mov Cap-2 Maneuver	-	-	-	-	-	-	411	311	-	347	352	-
Stage 1	-	-	-	-	-	-	742	705	-	539	544	-
Stage 2	-	-	-	-	-	-	655	493	-	767	701	-

Approach	EB			WB			NB			SB		
HCM Control Delay, s/v 0.17				2.16			9.69			22.8		
HCM LOS							A			C		

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1
Capacity (veh/h)	874	62	-	-	1331	-	-	350
HCM Lane V/C Ratio	0.123	0.003	-	-	0.082	-	-	0.429
HCM Control Delay (s/veh)	9.7	7.9	0	-	7.9	-	-	22.8
HCM Lane LOS	A	A	A	-	A	-	-	C
HCM 95th %tile Q(veh)	0.4	0	-	-	0.3	-	-	2.1

Intersection												
Int Delay, s/veh	4.6											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↔↔			↔↔			↔			↔	
Traffic Vol, veh/h	0	86	0	29	31	27	1	9	45	50	7	0
Future Vol, veh/h	0	86	0	29	31	27	1	9	45	50	7	0
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	93	0	32	34	29	1	10	49	54	8	0
Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	63	0	0	93	0	0	177	220	47	163	205	32
Stage 1	-	-	-	-	-	-	93	93	-	111	111	-
Stage 2	-	-	-	-	-	-	84	126	-	52	93	-
Critical Hdwy	4.14	-	-	4.14	-	-	7.54	6.54	6.94	7.54	6.54	6.94
Critical Hdwy Stg 1	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Follow-up Hdwy	2.22	-	-	2.22	-	-	3.52	4.02	3.32	3.52	4.02	3.32
Pot Cap-1 Maneuver	1538	-	-	1499	-	-	769	678	1012	786	690	1035
Stage 1	-	-	-	-	-	-	903	817	-	882	802	-
Stage 2	-	-	-	-	-	-	915	791	-	955	817	-
Platoon blocked, %		-	-		-	-						
Mov Cap-1 Maneuver	1538	-	-	1499	-	-	744	663	1012	722	676	1035
Mov Cap-2 Maneuver	-	-	-	-	-	-	744	663	-	722	676	-
Stage 1	-	-	-	-	-	-	903	817	-	863	785	-
Stage 2	-	-	-	-	-	-	887	774	-	898	817	-
Approach	EB			WB			NB			SB		
HCM Control Delay, s/v	0			2.5			9.15			10.51		
HCM LOS							A			B		
Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1				
Capacity (veh/h)	926	1538	-	-	727	-	-	716				
HCM Lane V/C Ratio	0.065	-	-	-	0.021	-	-	0.087				
HCM Control Delay (s/veh)	9.2	0	-	-	7.5	0.1	-	10.5				
HCM Lane LOS	A	A	-	-	A	A	-	B				
HCM 95th %tile Q(veh)	0.2	0	-	-	0.1	-	-	0.3				

HCM 7th TWSC
1: Century PI & Centennial Pkwy

02/05/2025

Intersection													
Int Delay, s/veh	1.2												
Movement	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations													
Traffic Vol, veh/h	0	74	11	11	15	176	78	10	12	11	6	5	2
Future Vol, veh/h	0	74	11	11	15	176	78	10	12	11	6	5	2
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	-	None	-	-	None	-	-	None
Storage Length	100	-	-	-	100	-	-	-	-	-	100	-	-
Veh in Median Storage, #	-	0	-	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	80	12	12	16	191	85	11	13	12	7	5	2
Major/Minor	Major1			Major2			Minor1			Minor2			
Conflicting Flow All	276	0	0	-	92	0	0	313	419	86	353	383	234
Stage 1	-	-	-	-	-	-	-	86	86	-	266	290	-
Stage 2	-	-	-	-	-	-	-	227	333	-	87	92	-
Critical Hdwy	4.12	-	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1287	-	-	-	1502	-	-	640	525	972	602	551	805
Stage 1	-	-	-	-	-	-	-	921	823	-	739	672	-
Stage 2	-	-	-	-	-	-	-	776	644	-	921	818	-
Platoon blocked, %		-	-			-	-						
Mov Cap-1 Maneuver	1287	-	-	~ -2	~ -2	-	-	632	525	972	580	551	805
Mov Cap-2 Maneuver	-	-	-	-	-	-	-	632	525	-	580	551	-
Stage 1	-	-	-	-	-	-	-	921	823	-	739	672	-
Stage 2	-	-	-	-	-	-	-	768	644	-	895	818	-
Approach	EB			WB			NB			SB			
HCM Control Delay, s/v	0						10.77			11.14			
HCM LOS							B			B			
Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1	SBLn2				
Capacity (veh/h)	660	1287	-	-	~	-	-	580	605				
HCM Lane V/C Ratio	0.054	-	-	-	-	-	-	0.011	0.013				
HCM Control Delay (s/veh)	10.8	0	-	-	-	-	-	11.3	11				
HCM Lane LOS	B	A	-	-	-	-	-	B	B				
HCM 95th %tile Q(veh)	0.2	0	-	-	-	-	-	0	0				
Notes													
~: Volume exceeds capacity		\$: Delay exceeds 300s			+: Computation Not Defined				*: All major volume in platoon				

Intersection

Int Delay, s/veh 4.2

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	7	108	8	57	242	39	14	3	89	51	1	24
Future Vol, veh/h	7	108	8	57	242	39	14	3	89	51	1	24
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	80	-	-	100	-	50	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	8	117	9	62	263	42	15	3	97	55	1	26

Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	305	0	0	126	0	0	524	566	122	521	528	263
Stage 1	-	-	-	-	-	-	137	137	-	387	387	-
Stage 2	-	-	-	-	-	-	388	429	-	134	141	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1255	-	-	1460	-	-	464	433	929	466	456	776
Stage 1	-	-	-	-	-	-	866	783	-	637	610	-
Stage 2	-	-	-	-	-	-	636	584	-	869	780	-
Platoon blocked, %		-	-		-	-						
Mov Cap-1 Maneuver	1255	-	-	1460	-	-	425	413	929	394	434	776
Mov Cap-2 Maneuver	-	-	-	-	-	-	425	413	-	394	434	-
Stage 1	-	-	-	-	-	-	861	778	-	610	584	-
Stage 2	-	-	-	-	-	-	588	559	-	771	775	-

Approach	EB			WB			NB			SB		
HCM Control Delay, s/v	0.45			1.28			10.42			14.35		
HCM LOS							B			B		

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1
Capacity (veh/h)	780	1255	-	-	1460	-	-	467
HCM Lane V/C Ratio	0.148	0.006	-	-	0.042	-	-	0.177
HCM Control Delay (s/veh)	10.4	7.9	-	-	7.6	-	-	14.3
HCM Lane LOS	B	A	-	-	A	-	-	B
HCM 95th %tile Q(veh)	0.5	0	-	-	0.1	-	-	0.6

Queues

3: McCaslin Blvd & Centennial Pkwy

02/05/2025

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Group Flow (vph)	142	52	75	327	52	142	234	1120	153	85	777	82
v/c Ratio	0.63	0.11	0.05	0.66	0.19	0.09	0.60	0.65	0.10	0.37	0.53	0.05
Control Delay (s/veh)	61.0	44.8	0.1	54.9	45.5	0.1	13.8	13.9	0.1	19.1	30.2	0.1
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	61.0	44.8	0.1	54.9	45.5	0.1	13.8	13.9	0.1	19.1	30.2	0.1
Queue Length 50th (ft)	106	18	0	125	36	0	23	299	0	28	228	0
Queue Length 95th (ft)	166	m36	0	165	71	0	m65	539	m0	63	371	0
Internal Link Dist (ft)		360			352			447			338	
Turn Bay Length (ft)	100		100	150			325		125	315		50
Base Capacity (vph)	383	766	1583	743	403	1583	468	1723	1583	261	1480	1583
Starvation Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.37	0.07	0.05	0.44	0.13	0.09	0.50	0.65	0.10	0.33	0.53	0.05
Intersection Summary												
m Volume for 95th percentile queue is metered by upstream signal.												

HCM 7th Signalized Intersection Summary

3: McCaslin Blvd & Centennial Pkwy

02/05/2025

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	131	48	69	301	48	131	215	1030	141	78	715	75
Future Volume (veh/h)	131	48	69	301	48	131	215	1030	141	78	715	75
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Lane Width Adj.	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	142	52	0	327	52	0	234	1120	0	85	777	0
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	178	356		417	226		456	1919		379	1758	
Arrive On Green	0.10	0.10	0.00	0.12	0.12	0.00	0.17	1.00	0.00	0.04	0.49	0.00
Sat Flow, veh/h	1781	3554	1585	3456	1870	1585	1781	3554	1585	1781	3554	1585
Grp Volume(v), veh/h	142	52	0	327	52	0	234	1120	0	85	777	0
Grp Sat Flow(s),veh/h/ln	1781	1777	1585	1728	1870	1585	1781	1777	1585	1781	1777	1585
Q Serve(g_s), s	9.4	1.6	0.0	11.0	3.0	0.0	7.9	0.0	0.0	2.8	17.0	0.0
Cycle Q Clear(g_c), s	9.4	1.6	0.0	11.0	3.0	0.0	7.9	0.0	0.0	2.8	17.0	0.0
Prop In Lane	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	178	356		417	226		456	1919		379	1758	
V/C Ratio(X)	0.80	0.15		0.78	0.23		0.51	0.58		0.22	0.44	
Avail Cap(c_a), veh/h	386	770		749	405		602	1919		442	1758	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	2.00	2.00	2.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	52.8	49.3	0.0	51.2	47.7	0.0	12.4	0.0	0.0	13.7	19.6	0.0
Incr Delay (d2), s/veh	9.3	0.2	0.0	3.9	0.6	0.0	0.3	1.3	0.0	0.1	0.8	0.0
Initial Q Delay(d3), s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	4.6	0.7	0.0	5.0	1.4	0.0	2.6	0.3	0.0	1.1	6.9	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d), s/veh	62.1	49.5	0.0	55.2	48.3	0.0	12.7	1.3	0.0	13.8	20.4	0.0
LnGrp LOS	E	D		E	D		B	A		B	C	
Approach Vol, veh/h	194			379			1354			862		
Approach Delay, s/veh	58.8			54.2			3.3			19.8		
Approach LOS	E			D			A			B		
Timer - Assigned Phs	1	2		4	5	6		8				
Phs Duration (G+Y+Rc), s	10.7	70.8		18.0	16.2	65.4		20.5				
Change Period (Y+Rc), s	6.0	6.0		6.0	6.0	6.0		6.0				
Max Green Setting (Gmax), s	9.0	35.0		26.0	20.0	24.0		26.0				
Max Q Clear Time (g_c+I1), s	4.8	2.0		11.4	9.9	19.0		13.0				
Green Ext Time (p_c), s	0.0	13.7		0.7	0.2	2.7		1.4				

Intersection Summary

HCM 7th Control Delay, s/veh	19.2
HCM 7th LOS	B

Notes

User approved pedestrian interval to be less than phase max green.

Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.

Intersection												
Int Delay, s/veh	1.4											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations			↱			↱	↱↑↑↑			↱↑↑↑		
Traffic Vol, veh/h	0	0	98	0	0	69	112	1317	59	39	978	68
Future Vol, veh/h	0	0	98	0	0	69	112	1317	59	39	978	68
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	Stop	-	-	Stop	-	-	None	-	-	None
Storage Length	-	-	0	-	-	0	150	-	-	250	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	0	107	0	0	75	122	1432	64	42	1063	74

Major/Minor	Minor2		Minor1		Major1		Major2	
Conflicting Flow All	-	-	568	-	-	748	1137	0
Stage 1	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-
Critical Hdwy	-	-	7.14	-	-	7.14	5.34	-
Critical Hdwy Stg 1	-	-	-	-	-	-	-	-
Critical Hdwy Stg 2	-	-	-	-	-	-	-	-
Follow-up Hdwy	-	-	3.92	-	-	3.92	3.12	-
Pot Cap-1 Maneuver	0	0	*766	0	0	*707	584	-
Stage 1	0	0	-	0	0	-	-	-
Stage 2	0	0	-	0	0	-	-	-
Platoon blocked, %			0			0	0	-
Mov Cap-1 Maneuver	-	-	*766	-	-	*707	584	-
Mov Cap-2 Maneuver	-	-	-	-	-	-	-	-
Stage 1	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-

Approach	EB	WB	NB	SB
HCM Control Delay, s/v10.45		10.69	0.96	0.48
HCM LOS	B	B		

Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1WBLn1	SBL	SBT	SBR
Capacity (veh/h)	584	-	-	766	707	469	-
HCM Lane V/C Ratio	0.209	-	-	0.139	0.106	0.09	-
HCM Control Delay (s/veh)	12.8	-	-	10.5	10.7	13.4	-
HCM Lane LOS	B	-	-	B	B	B	-
HCM 95th %tile Q(veh)	0.8	-	-	0.5	0.4	0.3	-

Notes			
~: Volume exceeds capacity	\$: Delay exceeds 300s	+: Computation Not Defined	*: All major volume in platoon

Queues

5: McCaslin Blvd & Dillon Rd

02/05/2025

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Group Flow (vph)	41	55	133	601	100	358	282	1218	554	227	896	47
v/c Ratio	0.22	0.34	0.08	1.00	0.27	0.23	1.24	0.72	0.35	0.75	0.35	0.03
Control Delay (s/veh)	56.9	57.3	0.1	86.8	42.3	0.3	184.3	29.5	0.6	62.9	26.8	0.0
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	56.9	57.3	0.1	86.8	42.3	0.3	184.3	29.5	0.6	62.9	26.8	0.0
Queue Length 50th (ft)	15	41	0	~242	66	0	~139	407	0	95	188	0
Queue Length 95th (ft)	34	83	0	#365	116	0	#228	513	0	#144	222	m0
Internal Link Dist (ft)		457			420			285			453	
Turn Bay Length (ft)	130		150	280		250	450		150	250		100
Base Capacity (vph)	314	465	1583	600	621	1583	228	1682	1583	314	2530	1583
Starvation Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.13	0.12	0.08	1.00	0.16	0.23	1.24	0.72	0.35	0.72	0.35	0.03

Intersection Summary

~ Volume exceeds capacity, queue is theoretically infinite.

Queue shown is maximum after two cycles.

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

m Volume for 95th percentile queue is metered by upstream signal.

HCM 7th Signalized Intersection Summary

5: McCaslin Blvd & Dillon Rd

02/05/2025

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	38	51	122	553	92	329	259	1121	510	209	824	43
Future Volume (veh/h)	38	51	122	553	92	329	259	1121	510	209	824	43
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Lane Width Adj.	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	41	55	0	601	100	0	282	1218	0	227	896	0
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	107	156		605	425		230	1636		282	2426	
Arrive On Green	0.03	0.08	0.00	0.17	0.23	0.00	0.07	0.46	0.00	0.11	0.63	0.00
Sat Flow, veh/h	3456	1870	1585	3456	1870	1585	3456	3554	1585	3456	5106	1585
Grp Volume(v), veh/h	41	55	0	601	100	0	282	1218	0	227	896	0
Grp Sat Flow(s),veh/h/ln	1728	1870	1585	1728	1870	1585	1728	1777	1585	1728	1702	1585
Q Serve(g_s), s	1.4	3.3	0.0	20.8	5.2	0.0	8.0	33.8	0.0	7.7	10.1	0.0
Cycle Q Clear(g_c), s	1.4	3.3	0.0	20.8	5.2	0.0	8.0	33.8	0.0	7.7	10.1	0.0
Prop In Lane	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	107	156		605	425		230	1636		282	2426	
V/C Ratio(X)	0.38	0.35		0.99	0.24		1.22	0.74		0.81	0.37	
Avail Cap(c_a), veh/h	317	468		605	623		230	1636		317	2426	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.33	1.33	1.33
Upstream Filter(I)	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	57.0	52.0	0.0	49.4	37.9	0.0	56.0	26.6	0.0	52.6	13.5	0.0
Incr Delay (d2), s/veh	1.7	1.4	0.0	34.9	0.3	0.0	133.1	3.1	0.0	12.2	0.4	0.0
Initial Q Delay(d3), s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	0.6	1.6	0.0	11.7	2.4	0.0	7.7	14.5	0.0	3.7	3.5	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d), s/veh	58.7	53.3	0.0	84.4	38.1	0.0	189.1	29.7	0.0	64.8	13.9	0.0
LnGrp LOS	E	D		F	D		F	C		E	B	
Approach Vol, veh/h	96			701			1500			1123		
Approach Delay, s/veh	55.6			77.8			59.7			24.2		
Approach LOS	E			E			E			C		
Timer - Assigned Phs	1	2	3	4	5	6	7	8				
Phs Duration (G+Y+Rc), s	15.8	61.2	27.0	16.0	14.0	63.0	9.7	33.3				
Change Period (Y+Rc), s	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0				
Max Green Setting (Gmax), s	11.0	34.0	21.0	30.0	8.0	37.0	11.0	40.0				
Max Q Clear Time (g_c+I1), s	9.7	35.8	22.8	5.3	10.0	12.1	3.4	7.2				
Green Ext Time (p_c), s	0.1	0.0	0.0	0.2	0.0	11.4	0.0	0.5				

Intersection Summary

HCM 7th Control Delay, s/veh	51.6
HCM 7th LOS	D

Notes

Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.

Intersection												
Int Delay, s/veh	2.3											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	0	123	3	38	260	94	0	0	29	59	1	0
Future Vol, veh/h	0	123	3	38	260	94	0	0	29	59	1	0
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	175	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	134	3	41	283	102	0	0	32	64	1	0
Major/Minor	Major1		Major2			Minor1			Minor2			
Conflicting Flow All	385	0	0	137	0	0	360	603	68	483	553	192
Stage 1	-	-	-	-	-	-	135	135	-	416	416	-
Stage 2	-	-	-	-	-	-	224	467	-	67	137	-
Critical Hdwy	4.14	-	-	4.14	-	-	7.54	6.54	6.94	7.54	6.54	6.94
Critical Hdwy Stg 1	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Follow-up Hdwy	2.22	-	-	2.22	-	-	3.52	4.02	3.32	3.52	4.02	3.32
Pot Cap-1 Maneuver	1170	-	-	1445	-	-	571	412	981	466	439	817
Stage 1	-	-	-	-	-	-	854	783	-	584	590	-
Stage 2	-	-	-	-	-	-	758	560	-	936	782	-
Platoon blocked, %		-	-		-	-						
Mov Cap-1 Maneuver	1170	-	-	1445	-	-	553	400	981	439	427	817
Mov Cap-2 Maneuver	-	-	-	-	-	-	553	400	-	439	427	-
Stage 1	-	-	-	-	-	-	854	783	-	568	573	-
Stage 2	-	-	-	-	-	-	735	544	-	906	782	-
Approach	EB		WB			NB			SB			
HCM Control Delay, s/v	0		0.73			8.79			14.64			
HCM LOS						A			B			
Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1				
Capacity (veh/h)	981	1170	-	-	1445	-	-	438				
HCM Lane V/C Ratio	0.032	-	-	-	0.029	-	-	0.149				
HCM Control Delay (s/veh)	8.8	0	-	-	7.6	-	-	14.6				
HCM Lane LOS	A	A	-	-	A	-	-	B				
HCM 95th %tile Q(veh)	0.1	0	-	-	0.1	-	-	0.5				

Intersection

Int Delay, s/veh 2.8

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↔↔			↔↔			↔			↔	
Traffic Vol, veh/h	2	51	0	39	178	34	0	2	55	14	5	2
Future Vol, veh/h	2	51	0	39	178	34	0	2	55	14	5	2
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	2	55	0	42	193	37	0	2	60	15	5	2

Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	230	0	0	55	0	0	244	375	28	330	357	115
Stage 1	-	-	-	-	-	-	60	60	-	297	297	-
Stage 2	-	-	-	-	-	-	184	315	-	33	60	-
Critical Hdwy	4.14	-	-	4.14	-	-	7.54	6.54	6.94	7.54	6.54	6.94
Critical Hdwy Stg 1	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Follow-up Hdwy	2.22	-	-	2.22	-	-	3.52	4.02	3.32	3.52	4.02	3.32
Pot Cap-1 Maneuver	1335	-	-	1548	-	-	690	555	1041	600	568	915
Stage 1	-	-	-	-	-	-	945	844	-	687	666	-
Stage 2	-	-	-	-	-	-	800	654	-	979	844	-
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-
Mov Cap-1 Maneuver	1335	-	-	1548	-	-	660	537	1041	546	550	915
Mov Cap-2 Maneuver	-	-	-	-	-	-	660	537	-	546	550	-
Stage 1	-	-	-	-	-	-	943	843	-	667	647	-
Stage 2	-	-	-	-	-	-	768	635	-	919	843	-

Approach	EB			WB			NB			SB		
HCM Control Delay, s/v	0.3			1.26			8.81			11.6		
HCM LOS							A			B		

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1
Capacity (veh/h)	1008	136	-	-	457	-	-	569
HCM Lane V/C Ratio	0.061	0.002	-	-	0.027	-	-	0.04
HCM Control Delay (s/veh)	8.8	7.7	0	-	7.4	0.2	-	11.6
HCM Lane LOS	A	A	A	-	A	A	-	B
HCM 95th %tile Q(veh)	0.2	0	-	-	0.1	-	-	0.1

HCM 7th TWSC
1: Century PI & Centennial Pkwy

02/05/2025

Intersection													
Int Delay, s/veh	3.1												
Movement	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations													
Traffic Vol, veh/h	1	207	22	17	24	42	6	14	5	26	61	10	5
Future Vol, veh/h	1	207	22	17	24	42	6	14	5	26	61	10	5
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	-	None	-	-	None	-	-	None
Storage Length	100	-	-	-	100	-	-	-	-	-	100	-	-
Veh in Median Storage, #	-	0	-	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	1	225	24	18	26	46	7	15	5	28	66	11	5

Major/Minor	Major1			Major2			Minor1			Minor2			
Conflicting Flow All	52	0	0	-	249	0	0	342	380	237	331	389	49
Stage 1	-	-	-	-	-	-	-	239	239	-	101	138	-
Stage 2	-	-	-	-	-	-	-	103	141	-	230	251	-
Critical Hdwy	4.12	-	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1554	-	-	-	1317	-	-	612	552	802	622	546	1020
Stage 1	-	-	-	-	-	-	-	764	707	-	905	782	-
Stage 2	-	-	-	-	-	-	-	903	780	-	773	699	-
Platoon blocked, %		-	-			-	-						
Mov Cap-1 Maneuver	1554	-	-	~-2	~-2	-	-	596	552	802	594	546	1020
Mov Cap-2 Maneuver	-	-	-	-	-	-	-	596	552	-	594	546	-
Stage 1	-	-	-	-	-	-	-	764	707	-	905	782	-
Stage 2	-	-	-	-	-	-	-	885	780	-	739	699	-

Approach	EB	WB	NB	SB
HCM Control Delay, s/v 0.03			10.59	11.6
HCM LOS			B	B

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1	SBLn2
Capacity (veh/h)	693	1554	-	-	~	-	-	594	646
HCM Lane V/C Ratio	0.071	0.001	-	-	-	-	-	0.112	0.025
HCM Control Delay (s/veh)	10.6	7.3	-	-	-	-	-	11.8	10.7
HCM Lane LOS	B	A	-	-	-	-	-	B	B
HCM 95th %tile Q(veh)	0.2	0	-	-	-	-	-	0.4	0.1

Notes			
~: Volume exceeds capacity	\$: Delay exceeds 300s	+: Computation Not Defined	*: All major volume in platoon

Intersection												
Int Delay, s/veh	6.4											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	3	300	29	114	69	20	14	3	215	35	0	6
Future Vol, veh/h	3	300	29	114	69	20	14	3	215	35	0	6
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	80	-	-	100	-	50	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	3	326	32	124	75	22	15	3	234	38	0	7

Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	97	0	0	358	0	0	671	693	342	657	687	75
Stage 1	-	-	-	-	-	-	348	348	-	323	323	-
Stage 2	-	-	-	-	-	-	323	345	-	334	364	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1497	-	-	1201	-	-	370	367	701	378	370	986
Stage 1	-	-	-	-	-	-	668	634	-	689	650	-
Stage 2	-	-	-	-	-	-	689	636	-	680	624	-
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-
Mov Cap-1 Maneuver	1497	-	-	1201	-	-	329	328	701	224	331	986
Mov Cap-2 Maneuver	-	-	-	-	-	-	329	328	-	224	331	-
Stage 1	-	-	-	-	-	-	666	632	-	618	583	-
Stage 2	-	-	-	-	-	-	614	571	-	450	622	-

Approach	EB	WB	NB	SB
HCM Control Delay, s/v	0.07	4.68	14.07	22.33
HCM LOS			B	C

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1
Capacity (veh/h)	647	1497	-	-	1201	-	-	252
HCM Lane V/C Ratio	0.39	0.002	-	-	0.103	-	-	0.177
HCM Control Delay (s/veh)	14.1	7.4	-	-	8.3	-	-	22.3
HCM Lane LOS	B	A	-	-	A	-	-	C
HCM 95th %tile Q(veh)	1.8	0	-	-	0.3	-	-	0.6

Queues

3: McCaslin Blvd & Centennial Pkwy

02/05/2025

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Group Flow (vph)	243	100	254	352	42	127	37	1009	255	139	1448	141
v/c Ratio	0.77	0.16	0.16	0.67	0.15	0.08	0.25	0.72	0.16	0.60	0.90	0.09
Control Delay (s/veh)	63.1	40.9	0.2	54.2	43.6	0.1	20.5	16.7	0.2	29.0	40.7	0.1
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	63.1	40.9	0.2	54.2	43.6	0.1	20.5	16.7	0.2	29.0	40.7	0.1
Queue Length 50th (ft)	180	34	0	134	29	0	5	187	0	55	572	0
Queue Length 95th (ft)	262	57	0	176	60	0	m8	#511	m0	109	#871	0
Internal Link Dist (ft)		360			352			447			338	
Turn Bay Length (ft)	100		100	150			325		125	315		50
Base Capacity (vph)	383	766	1583	743	403	1583	164	1400	1583	246	1616	1583
Starvation Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.63	0.13	0.16	0.47	0.10	0.08	0.23	0.72	0.16	0.57	0.90	0.09

Intersection Summary

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

m Volume for 95th percentile queue is metered by upstream signal.

HCM 7th Signalized Intersection Summary

3: McCaslin Blvd & Centennial Pkwy

02/05/2025

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	224	92	234	324	39	117	34	928	235	128	1332	130
Future Volume (veh/h)	224	92	234	324	39	117	34	928	235	128	1332	130
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Lane Width Adj.	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	243	100	0	352	42	0	37	1009	0	139	1448	0
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	281	561		441	239		161	1623		386	1723	
Arrive On Green	0.16	0.16	0.00	0.13	0.13	0.00	0.06	0.91	0.00	0.06	0.48	0.00
Sat Flow, veh/h	1781	3554	1585	3456	1870	1585	1781	3554	1585	1781	3554	1585
Grp Volume(v), veh/h	243	100	0	352	42	0	37	1009	0	139	1448	0
Grp Sat Flow(s),veh/h/ln	1781	1777	1585	1728	1870	1585	1781	1777	1585	1781	1777	1585
Q Serve(g_s), s	16.0	2.9	0.0	11.9	2.4	0.0	1.3	6.8	0.0	4.9	42.5	0.0
Cycle Q Clear(g_c), s	16.0	2.9	0.0	11.9	2.4	0.0	1.3	6.8	0.0	4.9	42.5	0.0
Prop In Lane	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	281	561		441	239		161	1623		386	1723	
V/C Ratio(X)	0.86	0.18		0.80	0.18		0.23	0.62		0.36	0.84	
Avail Cap(c_a), veh/h	386	770		749	405		212	1623		432	1723	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	2.00	2.00	2.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	49.3	43.8	0.0	50.8	46.7	0.0	22.5	3.1	0.0	15.6	26.9	0.0
Incr Delay (d2), s/veh	14.8	0.2	0.0	4.0	0.4	0.0	0.3	1.8	0.0	0.2	5.1	0.0
Initial Q Delay(d3), s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	8.2	1.3	0.0	5.3	1.1	0.0	0.5	1.7	0.0	2.0	18.1	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d), s/veh	64.0	44.0	0.0	54.9	47.1	0.0	22.8	4.9	0.0	15.8	32.0	0.0
LnGrp LOS	E	D		D	D		C	A		B	C	
Approach Vol, veh/h	343			394			1046			1587		
Approach Delay, s/veh	58.2			54.0			5.6			30.6		
Approach LOS	E			D			A			C		
Timer - Assigned Phs	1	2		4	5	6		8				
Phs Duration (G+Y+Rc), s	12.9	60.8		25.0	9.5	64.2		21.3				
Change Period (Y+Rc), s	6.0	6.0		6.0	6.0	6.0		6.0				
Max Green Setting (Gmax), s	10.0	34.0		26.0	7.0	37.0		26.0				
Max Q Clear Time (g_c+I1), s	6.9	8.8		18.0	3.3	44.5		13.9				
Green Ext Time (p_c), s	0.0	10.6		1.0	0.0	0.0		1.5				

Intersection Summary

HCM 7th Control Delay, s/veh	28.4
HCM 7th LOS	C

Notes

User approved pedestrian interval to be less than phase max green.

Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.

Intersection												
Int Delay, s/veh	2.8											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations			↗			↗	↗ ↑↑↑			↗ ↑↑↑		
Traffic Vol, veh/h	0	0	203	0	0	59	164	1138	54	54	1720	116
Future Vol, veh/h	0	0	203	0	0	59	164	1138	54	54	1720	116
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	Stop	-	-	Stop	-	-	None	-	-	None
Storage Length	-	-	0	-	-	0	150	-	-	250	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	0	221	0	0	64	178	1237	59	59	1870	126

Major/Minor	Minor2		Minor1		Major1		Major2					
Conflicting Flow All	-	-	998	-	-	648	1996	0	0	1296	0	0
Stage 1	-	-	-	-	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-	-	-	-	-
Critical Hdwy	-	-	7.14	-	-	7.14	5.34	-	-	5.34	-	-
Critical Hdwy Stg 1	-	-	-	-	-	-	-	-	-	-	-	-
Critical Hdwy Stg 2	-	-	-	-	-	-	-	-	-	-	-	-
Follow-up Hdwy	-	-	3.92	-	-	3.92	3.12	-	-	3.12	-	-
Pot Cap-1 Maneuver	0	0	*648	0	0	*737	292	-	-	540	-	-
Stage 1	0	0	-	0	0	-	-	-	-	-	-	-
Stage 2	0	0	-	0	0	-	-	-	-	-	-	-
Platoon blocked, %			0			0	0	-	-	0	-	-
Mov Cap-1 Maneuver	-	-	*648	-	-	*737	292	-	-	540	-	-
Mov Cap-2 Maneuver	-	-	-	-	-	-	-	-	-	-	-	-
Stage 1	-	-	-	-	-	-	-	-	-	-	-	-
Stage 2	-	-	-	-	-	-	-	-	-	-	-	-

Approach	EB		WB		NB		SB	
HCM Control Delay, s/v	13.4		10.35		4.22		0.36	
HCM LOS	B		B					

Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1WBLn1	SBL	SBT	SBR
Capacity (veh/h)	292	-	-	648	737	540	-
HCM Lane V/C Ratio	0.611	-	-	0.341	0.087	0.109	-
HCM Control Delay (s/veh)	34.9	-	-	13.4	10.4	12.5	-
HCM Lane LOS	D	-	-	B	B	B	-
HCM 95th %tile Q(veh)	3.7	-	-	1.5	0.3	0.4	-

Notes			
~: Volume exceeds capacity	\$: Delay exceeds 300s	+: Computation Not Defined	*: All major volume in platoon

Queues

5: McCaslin Blvd & Dillon Rd

02/05/2025

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Group Flow (vph)	99	142	313	734	128	204	320	1171	603	330	1688	72
v/c Ratio	0.47	0.63	0.20	1.12	0.27	0.13	1.02	0.79	0.38	1.45	0.84	0.05
Control Delay (s/veh)	61.6	61.7	0.3	116.4	37.0	0.2	109.5	35.6	0.7	259.8	44.8	0.0
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	61.6	61.7	0.3	116.4	37.0	0.2	109.5	35.6	0.7	259.8	44.8	0.0
Queue Length 50th (ft)	38	106	0	~336	81	0	~132	406	0	~184	434	0
Queue Length 95th (ft)	68	167	0	#457	128	0	#228	536	0	m#241	#581	m0
Internal Link Dist (ft)		457			420			285			453	
Turn Bay Length (ft)	130		150	280		250	450		150	250		100
Base Capacity (vph)	228	465	1583	657	698	1583	314	1484	1583	228	2006	1583
Starvation Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.43	0.31	0.20	1.12	0.18	0.13	1.02	0.79	0.38	1.45	0.84	0.05

Intersection Summary

~ Volume exceeds capacity, queue is theoretically infinite.

Queue shown is maximum after two cycles.

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

m Volume for 95th percentile queue is metered by upstream signal.

HCM 7th Signalized Intersection Summary

5: McCaslin Blvd & Dillon Rd

02/05/2025

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	91	131	288	675	118	188	294	1077	555	304	1553	66
Future Volume (veh/h)	91	131	288	675	118	188	294	1077	555	304	1553	66
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Lane Width Adj.	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	99	142	0	734	128	0	320	1171	0	330	1688	0
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	151	180		662	457		317	1583		230	2146	
Arrive On Green	0.04	0.10	0.00	0.19	0.24	0.00	0.09	0.45	0.00	0.02	0.14	0.00
Sat Flow, veh/h	3456	1870	1585	3456	1870	1585	3456	3554	1585	3456	5106	1585
Grp Volume(v), veh/h	99	142	0	734	128	0	320	1171	0	330	1688	0
Grp Sat Flow(s),veh/h/ln	1728	1870	1585	1728	1870	1585	1728	1777	1585	1728	1702	1585
Q Serve(g_s), s	3.4	8.9	0.0	23.0	6.7	0.0	11.0	32.7	0.0	8.0	38.4	0.0
Cycle Q Clear(g_c), s	3.4	8.9	0.0	23.0	6.7	0.0	11.0	32.7	0.0	8.0	38.4	0.0
Prop In Lane	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	151	180		662	457		317	1583		230	2146	
V/C Ratio(X)	0.66	0.79		1.11	0.28		1.01	0.74		1.43	0.79	
Avail Cap(c_a), veh/h	230	468		662	701		317	1583		230	2146	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.33	0.33	0.33
Upstream Filter(I)	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	56.5	53.0	0.0	48.5	36.8	0.0	54.5	27.5	0.0	58.7	46.5	0.0
Incr Delay (d2), s/veh	3.6	7.4	0.0	68.5	0.3	0.0	53.2	3.2	0.0	217.7	3.0	0.0
Initial Q Delay(d3), s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	1.6	4.6	0.0	16.0	3.0	0.0	7.1	14.1	0.0	10.6	18.1	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d), s/veh	60.1	60.5	0.0	117.0	37.1	0.0	107.7	30.7	0.0	276.4	49.5	0.0
LnGrp LOS	E	E		F	D		F	C		F	D	
Approach Vol, veh/h	241			862			1491			2018		
Approach Delay, s/veh	60.3			105.1			47.2			86.6		
Approach LOS	E			F			D			F		
Timer - Assigned Phs	1	2	3	4	5	6	7	8				
Phs Duration (G+Y+Rc), s	14.0	59.4	29.0	17.6	17.0	56.4	11.2	35.3				
Change Period (Y+Rc), s	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0				
Max Green Setting (Gmax), s	8.0	35.0	23.0	30.0	11.0	32.0	8.0	45.0				
Max Q Clear Time (g_c+I1), s	10.0	34.7	25.0	10.9	13.0	40.4	5.4	8.7				
Green Ext Time (p_c), s	0.0	0.2	0.0	0.7	0.0	0.0	0.0	0.7				

Intersection Summary

HCM 7th Control Delay, s/veh	75.9
HCM 7th LOS	E

Notes

User approved pedestrian interval to be less than phase max green.

Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.

Intersection												
Int Delay, s/veh	7											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	4	266	9	119	140	177	2	1	108	136	0	2
Future Vol, veh/h	4	266	9	119	140	177	2	1	108	136	0	2
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	175	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	4	289	10	129	152	192	2	1	117	148	0	2
Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	345	0	0	299	0	0	638	906	149	661	815	172
Stage 1	-	-	-	-	-	-	303	303	-	507	507	-
Stage 2	-	-	-	-	-	-	335	603	-	154	308	-
Critical Hdwy	4.14	-	-	4.14	-	-	7.54	6.54	6.94	7.54	6.54	6.94
Critical Hdwy Stg 1	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Follow-up Hdwy	2.22	-	-	2.22	-	-	3.52	4.02	3.32	3.52	4.02	3.32
Pot Cap-1 Maneuver	1211	-	-	1259	-	-	362	275	870	348	310	841
Stage 1	-	-	-	-	-	-	682	662	-	516	537	-
Stage 2	-	-	-	-	-	-	653	486	-	833	659	-
Platoon blocked, %	0	-	-	-	-	-	0	0	-	0	0	0
Mov Cap-1 Maneuver	1211	-	-	1259	-	-	322	245	870	268	277	841
Mov Cap-2 Maneuver	-	-	-	-	-	-	322	245	-	268	277	-
Stage 1	-	-	-	-	-	-	679	660	-	463	482	-
Stage 2	-	-	-	-	-	-	584	436	-	717	657	-
Approach	EB			WB			NB			SB		
HCM Control Delay, s/v	0.14			2.23			10.1			33.68		
HCM LOS							B			D		
Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1				
Capacity (veh/h)	826	49	-	-	1259	-	-	271				
HCM Lane V/C Ratio	0.146	0.004	-	-	0.103	-	-	0.554				
HCM Control Delay (s/veh)	10.1	8	0	-	8.2	-	-	33.7				
HCM Lane LOS	B	A	A	-	A	-	-	D				
HCM 95th %tile Q(veh)	0.5	0	-	-	0.3	-	-	3.1				

Intersection												
Int Delay, s/veh	3.6											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	0	146	0	29	80	27	1	9	45	50	7	0
Future Vol, veh/h	0	146	0	29	80	27	1	9	45	50	7	0
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	159	0	32	87	29	1	10	49	54	8	0
Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	116	0	0	159	0	0	269	338	79	249	323	58
Stage 1	-	-	-	-	-	-	159	159	-	165	165	-
Stage 2	-	-	-	-	-	-	110	179	-	84	159	-
Critical Hdwy	4.14	-	-	4.14	-	-	7.54	6.54	6.94	7.54	6.54	6.94
Critical Hdwy Stg 1	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.54	5.54	-	6.54	5.54	-
Follow-up Hdwy	2.22	-	-	2.22	-	-	3.52	4.02	3.32	3.52	4.02	3.32
Pot Cap-1 Maneuver	1470	-	-	1418	-	-	662	582	965	684	593	996
Stage 1	-	-	-	-	-	-	828	765	-	821	761	-
Stage 2	-	-	-	-	-	-	883	750	-	914	765	-
Platoon blocked, %		-	-		-	-						
Mov Cap-1 Maneuver	1470	-	-	1418	-	-	639	568	965	624	579	996
Mov Cap-2 Maneuver	-	-	-	-	-	-	639	568	-	624	579	-
Stage 1	-	-	-	-	-	-	828	765	-	802	743	-
Stage 2	-	-	-	-	-	-	854	733	-	857	765	-
Approach	EB			WB			NB			SB		
HCM Control Delay, s/v	0			1.68			9.5			11.47		
HCM LOS							A			B		
Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1				
Capacity (veh/h)	859	1470	-	-	567	-	-	618				
HCM Lane V/C Ratio	0.07	-	-	-	0.022	-	-	0.1				
HCM Control Delay (s/veh)	9.5	0	-	-	7.6	0.1	-	11.5				
HCM Lane LOS	A	A	-	-	A	A	-	B				
HCM 95th %tile Q(veh)	0.2	0	-	-	0.1	-	-	0.3				

Timings

5: McCaslin Blvd & Dillon Rd - Optimized Signal Timings

04/14/2025

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	77	115	246	559	103	162	255	896	459	256	1291	52
Future Volume (vph)	77	115	246	559	103	162	255	896	459	256	1291	52
Turn Type	Prot	NA	Free	Prot	NA	Free	Prot	NA	Free	Prot	NA	Free
Protected Phases	7	4		3	8		5	2		1	6	
Permitted Phases			Free			Free			Free			Free
Detector Phase	7	4		3	8		5	2		1	6	
Switch Phase												
Minimum Initial (s)	5.0	10.0		5.0	5.0		5.0	10.0		5.0	10.0	
Minimum Split (s)	11.0	36.0		11.0	39.0		11.0	32.0		11.0	30.0	
Total Split (s)	12.0	36.0		28.0	52.0		18.0	38.0		18.0	38.0	
Total Split (%)	10.0%	30.0%		23.3%	43.3%		15.0%	31.7%		15.0%	31.7%	
Yellow Time (s)	3.0	4.0		4.0	4.0		4.0	4.0		4.0	4.0	
All-Red Time (s)	3.0	2.0		2.0	2.0		2.0	2.0		2.0	2.0	
Lost Time Adjust (s)	0.0	0.0		0.0	0.0		0.0	0.0		0.0	0.0	
Total Lost Time (s)	6.0	6.0		6.0	6.0		6.0	6.0		6.0	6.0	
Lead/Lag	Lead	Lag		Lead	Lag		Lead	Lag		Lead	Lag	
Lead-Lag Optimize?	Yes	Yes		Yes	Yes		Yes	Yes		Yes	Yes	
Recall Mode	None	None		None	None		None	C-Max		None	C-Max	
Act Effect Green (s)	5.9	13.7	120.0	22.0	32.1	120.0	11.8	48.5	120.0	11.8	48.5	120.0
Actuated g/C Ratio	0.05	0.11	1.00	0.18	0.27	1.00	0.10	0.40	1.00	0.10	0.40	1.00
v/c Ratio	0.50	0.59	0.17	0.97	0.22	0.11	0.82	0.68	0.32	0.82	0.68	0.04
Control Delay (s/veh)	66.0	61.3	0.2	77.5	36.0	0.1	73.2	33.0	0.5	76.6	37.7	0.0
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	66.0	61.3	0.2	77.5	36.0	0.1	73.2	33.0	0.5	76.6	37.7	0.0
LOS	E	E	A	E	D	A	E	C	A	E	D	A
Approach Delay (s/veh)		27.9			57.1			30.1			42.7	
Approach LOS		C			E			C			D	

Intersection Summary

Cycle Length: 120

Actuated Cycle Length: 120

Offset: 20 (17%), Referenced to phase 2:NBT and 6:SBT, Start of Yellow

Natural Cycle: 105

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.97

Intersection Signal Delay (s/veh): 39.3


Intersection LOS: D

Intersection Capacity Utilization 69.8%

ICU Level of Service C

Analysis Period (min) 15

Splits and Phases: 5: McCaslin Blvd & Dillon Rd



Queues

5: McCaslin Blvd & Dillon Rd - Optimized Signal Timings

04/14/2025

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Group Flow (vph)	84	125	267	608	112	176	277	974	499	278	1403	57
v/c Ratio	0.50	0.59	0.17	0.97	0.22	0.11	0.82	0.68	0.32	0.82	0.68	0.04
Control Delay (s/veh)	66.0	61.3	0.2	77.5	36.0	0.1	73.2	33.0	0.5	76.6	37.7	0.0
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	66.0	61.3	0.2	77.5	36.0	0.1	73.2	33.0	0.5	76.6	37.7	0.0
Queue Length 50th (ft)	33	94	0	243	70	0	109	321	0	117	324	0
Queue Length 95th (ft)	60	151	0	#359	114	0	#176	427	0	#180	456	m0
Internal Link Dist (ft)		457			420			285			453	
Turn Bay Length (ft)	130		150	280		250	450		150	250		100
Base Capacity (vph)	171	465	1583	629	714	1583	343	1431	1583	343	2056	1583
Starvation Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.49	0.27	0.17	0.97	0.16	0.11	0.81	0.68	0.32	0.81	0.68	0.04

Intersection Summary

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

m Volume for 95th percentile queue is metered by upstream signal.

HCM 7th Signalized Intersection Summary

5: McCaslin Blvd & Dillon Rd - Optimized Signal Timings

04/14/2025

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	77	115	246	559	103	162	255	896	459	256	1291	52
Future Volume (veh/h)	77	115	246	559	103	162	255	896	459	256	1291	52
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Lane Width Adj.	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	84	125	0	608	112	0	277	974	0	278	1403	0
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	135	162		634	432		331	1538		335	2216	
Arrive On Green	0.04	0.09	0.00	0.18	0.23	0.00	0.10	0.43	0.00	0.03	0.14	0.00
Sat Flow, veh/h	3456	1870	1585	3456	1870	1585	3456	3554	1585	3456	5106	1585
Grp Volume(v), veh/h	84	125	0	608	112	0	277	974	0	278	1403	0
Grp Sat Flow(s),veh/h/ln	1728	1870	1585	1728	1870	1585	1728	1777	1585	1728	1702	1585
Q Serve(g_s), s	2.9	7.8	0.0	20.9	5.9	0.0	9.5	25.7	0.0	9.6	31.1	0.0
Cycle Q Clear(g_c), s	2.9	7.8	0.0	20.9	5.9	0.0	9.5	25.7	0.0	9.6	31.1	0.0
Prop In Lane	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	135	162		634	432		331	1538		335	2216	
V/C Ratio(X)	0.62	0.77		0.96	0.26		0.84	0.63		0.83	0.63	
Avail Cap(c_a), veh/h	173	468		634	717		346	1538		346	2216	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.33	0.33	0.33
Upstream Filter(I)	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	56.8	53.6	0.0	48.6	37.7	0.0	53.3	26.6	0.0	57.1	42.4	0.0
Incr Delay (d2), s/veh	3.4	7.5	0.0	25.9	0.3	0.0	15.3	2.0	0.0	14.8	1.4	0.0
Initial Q Delay(d3), s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	1.3	4.0	0.0	11.1	2.7	0.0	4.8	11.0	0.0	5.1	14.5	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d), s/veh	60.2	61.1	0.0	74.5	38.1	0.0	68.7	28.6	0.0	71.9	43.8	0.0
LnGrp LOS	E	E		E	D		E	C		E	D	
Approach Vol, veh/h	209			720			1251			1681		
Approach Delay, s/veh	60.7			68.8			37.5			48.4		
Approach LOS	E			E			D			D		
Timer - Assigned Phs	1	2	3	4	5	6	7	8				
Phs Duration (G+Y+Rc), s	17.6	57.9	28.0	16.4	17.5	58.1	10.7	33.7				
Change Period (Y+Rc), s	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0				
Max Green Setting (Gmax), s	12.0	32.0	22.0	30.0	12.0	32.0	6.0	46.0				
Max Q Clear Time (g_c+l1), s	11.6	27.7	22.9	9.8	11.5	33.1	4.9	7.9				
Green Ext Time (p_c), s	0.0	3.2	0.0	0.6	0.0	0.0	0.0	0.6				
Intersection Summary												
HCM 7th Control Delay, s/veh	49.3											
HCM 7th LOS	D											
Notes												
Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.												

Timings

5: McCaslin Blvd & Dillon Rd - Optimized Signal Timings

04/14/2025

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	↰↱	↱	↱	↰↱	↱	↱	↰↱	↱↱	↱	↰↱	↱↱↱	↱
Traffic Volume (vph)	91	131	288	675	118	188	294	1077	555	304	1553	66
Future Volume (vph)	91	131	288	675	118	188	294	1077	555	304	1553	66
Turn Type	Prot	NA	Free	Prot	NA	Free	Prot	NA	Free	Prot	NA	Free
Protected Phases	7	4		3	8		5	2		1	6	
Permitted Phases			Free			Free			Free			Free
Detector Phase	7	4		3	8		5	2		1	6	
Switch Phase												
Minimum Initial (s)	5.0	10.0		5.0	5.0		5.0	10.0		5.0	10.0	
Minimum Split (s)	11.0	36.0		11.0	39.0		11.0	32.0		11.0	30.0	
Total Split (s)	14.0	33.0		32.0	51.0		30.0	27.0		28.0	25.0	
Total Split (%)	11.7%	27.5%		26.7%	42.5%		25.0%	22.5%		23.3%	20.8%	
Yellow Time (s)	3.0	4.0		4.0	4.0		4.0	4.0		4.0	4.0	
All-Red Time (s)	3.0	2.0		2.0	2.0		2.0	2.0		2.0	2.0	
Lost Time Adjust (s)	0.0	0.0		0.0	0.0		0.0	0.0		0.0	0.0	
Total Lost Time (s)	6.0	6.0		6.0	6.0		6.0	6.0		6.0	6.0	
Lead/Lag	Lead	Lag		Lead	Lag		Lead	Lag		Lead	Lag	
Lead-Lag Optimize?	Yes	Yes		Yes	Yes		Yes	Yes		Yes	Yes	
Recall Mode	None	None		None	None		None	C-Max		None	C-Max	
Act Effect Green (s)	7.4	14.6	120.0	26.0	33.2	120.0	16.0	39.1	120.0	16.3	39.4	120.0
Actuated g/C Ratio	0.06	0.12	1.00	0.22	0.28	1.00	0.13	0.33	1.00	0.14	0.33	1.00
v/c Ratio	0.47	0.63	0.20	0.99	0.25	0.13	0.70	1.02	0.38	0.71	1.01	0.05
Control Delay (s/veh)	61.6	61.8	0.3	77.3	34.4	0.2	58.0	71.4	0.7	66.1	67.2	0.0
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	61.6	61.8	0.3	77.3	34.4	0.2	58.0	71.4	0.7	66.1	67.2	0.0
LOS	E	E	A	E	C	A	E	E	A	E	E	A
Approach Delay (s/veh)		27.0			57.4			49.0			64.7	
Approach LOS		C			E			D			E	

Intersection Summary

Cycle Length: 120

Actuated Cycle Length: 120

Offset: 20 (17%), Referenced to phase 2:NBT and 6:SBT, Start of Yellow

Natural Cycle: 145

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 1.02

Intersection Signal Delay (s/veh): 54.1


Intersection LOS: D

Intersection Capacity Utilization 86.0%

ICU Level of Service E

Analysis Period (min) 15

Splits and Phases: 5: McCaslin Blvd & Dillon Rd



Queues

5: McCaslin Blvd & Dillon Rd - Optimized Signal Timings

04/14/2025

												
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Group Flow (vph)	99	142	313	734	128	204	320	1171	603	330	1688	72
v/c Ratio	0.47	0.63	0.20	0.99	0.25	0.13	0.70	1.02	0.38	0.71	1.01	0.05
Control Delay (s/veh)	61.6	61.8	0.3	77.3	34.4	0.2	58.0	71.4	0.7	66.1	67.2	0.0
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay (s/veh)	61.6	61.8	0.3	77.3	34.4	0.2	58.0	71.4	0.7	66.1	67.2	0.0
Queue Length 50th (ft)	38	106	0	294	78	0	123	~487	0	138	~443	0
Queue Length 95th (ft)	68	167	0	#422	123	0	165	#760	0	m163	#740	m0
Internal Link Dist (ft)		457			420			285			453	
Turn Bay Length (ft)	130		150	280		250	450		150	250		100
Base Capacity (vph)	228	419	1583	743	698	1583	686	1152	1583	629	1669	1583
Starvation Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.43	0.34	0.20	0.99	0.18	0.13	0.47	1.02	0.38	0.52	1.01	0.05

Intersection Summary

~ Volume exceeds capacity, queue is theoretically infinite.

Queue shown is maximum after two cycles.

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

m Volume for 95th percentile queue is metered by upstream signal.

HCM 7th Signalized Intersection Summary

5: McCaslin Blvd & Dillon Rd - Optimized Signal Timings

04/14/2025

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	91	131	288	675	118	188	294	1077	555	304	1553	66
Future Volume (veh/h)	91	131	288	675	118	188	294	1077	555	304	1553	66
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Lane Width Adj.	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	99	142	0	734	128	0	320	1171	0	330	1688	0
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	151	179		749	503		389	1323		398	1914	
Arrive On Green	0.04	0.10	0.00	0.22	0.27	0.00	0.11	0.37	0.00	0.12	0.37	0.00
Sat Flow, veh/h	3456	1870	1585	3456	1870	1585	3456	3554	1585	3456	5106	1585
Grp Volume(v), veh/h	99	142	0	734	128	0	320	1171	0	330	1688	0
Grp Sat Flow(s),veh/h/ln	1728	1870	1585	1728	1870	1585	1728	1777	1585	1728	1702	1585
Q Serve(g_s), s	3.4	8.9	0.0	25.4	6.4	0.0	10.9	37.0	0.0	11.2	37.0	0.0
Cycle Q Clear(g_c), s	3.4	8.9	0.0	25.4	6.4	0.0	10.9	37.0	0.0	11.2	37.0	0.0
Prop In Lane	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	151	179		749	503		389	1323		398	1914	
V/C Ratio(X)	0.66	0.79		0.98	0.25		0.82	0.88		0.83	0.88	
Avail Cap(c_a), veh/h	230	421		749	701		691	1323		634	1914	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	56.5	53.1	0.0	46.7	34.4	0.0	52.1	35.3	0.0	51.9	35.0	0.0
Incr Delay (d2), s/veh	3.6	7.6	0.0	27.9	0.3	0.0	3.3	8.9	0.0	4.1	6.3	0.0
Initial Q Delay(d3), s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	1.6	4.6	0.0	13.5	2.9	0.0	4.8	17.2	0.0	5.0	16.0	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d), s/veh	60.1	60.7	0.0	74.6	34.7	0.0	55.4	44.2	0.0	56.0	41.3	0.0
LnGrp LOS	E	E		E	C		E	D		E	D	
Approach Vol, veh/h	241			862			1491			2018		
Approach Delay, s/veh	60.4			68.7			46.6			43.7		
Approach LOS	E			E			D			D		
Timer - Assigned Phs	1	2	3	4	5	6	7	8				
Phs Duration (G+Y+Rc), s	19.8	50.7	32.0	17.5	19.5	51.0	11.2	38.3				
Change Period (Y+Rc), s	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0				
Max Green Setting (Gmax), s	22.0	21.0	26.0	27.0	24.0	19.0	8.0	45.0				
Max Q Clear Time (g_c+l1), s	13.2	39.0	27.4	10.9	12.9	39.0	5.4	8.4				
Green Ext Time (p_c), s	0.6	0.0	0.0	0.6	0.6	0.0	0.0	0.7				

Intersection Summary

HCM 7th Control Delay, s/veh	50.2
HCM 7th LOS	D

Notes

User approved pedestrian interval to be less than phase max green.
 Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.